

## 10GbE and 10GFC Compliant Transceiver

### TEST FEATURES

- Extensive control of loopback, BIST, and operating modes via an 802.3 compliant MDC/MDIO serial interface (1.2 V).
- On-chip packet generator/checker provides at-speed diagnostics.
- Extensive built-in error counters per channel.
- Support for IEEE 1149.1 JTAG testing on all pins.
- Comprehensive evaluation platform for easy customer qualification.

### PHYSICAL CHARACTERISTICS


- 1.2/2.5 V, 0.13  $\mu\text{m}$  CMOS technology.
- Small footprint 289-ball CABGA (19 mm x 19 mm).
- 1.3 W typical power at 3.2 Gbit/s (non redundant mode).

### APPLICATIONS

- High-speed serial backplanes.
- 10GbE (XAUI) and 1GbE line cards.
- 10GFC and 2GFC line cards.
- Infiniband transceivers.
- OC-48 Serializer/Deserializer.
- PCI Express
- Serial Rapid I/O
- OBSAI RP3
- XAUI retimer.

## TYPICAL APPLICATION

### 10GE AND 10GFC BACKPLANE DRIVER



Head Office:  
PMC-Sierra, Inc.  
8555 Baxter Place  
Burnaby, B.C. V5A 4V7  
Canada  
Tel: 1.604.415.6000  
Fax: 1.604.415.6200

To order documentation,  
send email to:  
document@pmc-sierra.com  
or contact the head office,  
Attn: Document Coordinator

All product documentation is available  
on our web site at:  
<http://www.pmc-sierra.com>  
For corporate information,  
send email to:  
info@pmc-sierra.com

PMC-2020255 (p5)  
For a complete list of PMC-Sierra's  
trademarks, see our web site at  
<<http://www.pmc-sierra.com/legal/>>.  
Other product and company names  
mentioned herein may be the trademarks of  
their respective owners.