

# 1 Characteristics

**Table 2: Absolute ratings (limiting values, per diode, at 25 °C, unless otherwise specified)**

| Symbol              | Parameter   |                               |                         |  | Value       | Unit |
|---------------------|---|-------------------------------|-------------------------|--|-------------|------|
| V <sub>RRM</sub>    | Repetitive peak reverse voltage                       |                               |                         |  | 100         | V    |
| I <sub>F(RMS)</sub> | Forward rms current                                   |                               |                         |  | 10          | A    |
| I <sub>F(AV)</sub>  | Average forward current<br>δ = 0.5, square wave       | TO-220AB / D <sup>2</sup> PAK | T <sub>C</sub> = 165 °C | Per diode  | 5           | A    |
|                     |   |                               |                         | Per device   | 10          |      |
|                     |   | TO-220FPAB                    | T <sub>C</sub> = 155 °C | Per diode  | 5           |      |
|                     |   |                               | T <sub>C</sub> = 150 °C | Per device   | 10          |      |
| I <sub>FSM</sub>    | Surge non repetitive forward current                  |                               |                         | t <sub>p</sub> = 10 ms<br>sinusoidal               | 180         | A    |
| P <sub>ARM</sub>    | Repetitive peak avalanche power                       |                               |                         | t <sub>p</sub> = 10 μs,<br>T <sub>j</sub> = 125 °C | 515         | W    |
| T <sub>stg</sub>    | Storage temperature range                             |                               |                         |  | -65 to +175 | °C   |
| T <sub>j</sub>      | Maximum operating junction temperature <sup>(1)</sup> |                               |                         |  | 175         |      |

**Notes:**

<sup>(1)</sup>(dP<sub>tot</sub>/dT<sub>j</sub>) < (1/R<sub>th(j-a)</sub>) condition to avoid thermal runaway for a diode on its own heatsink.

**Table 3: Thermal parameters**

| Symbol               | Parameter        |                               |           | Max. value | Unit |
|----------------------|------------------|-------------------------------|-----------|------------|------|
| R <sub>th(j-c)</sub> | Junction to case | TO-220FPAB                    | Per diode | 4.5        | °C/W |
|                      |                  |                               | Total     | 3.5        |      |
|                      |                  | TO-220AB / D <sup>2</sup> PAK | Per diode | 2.2        |      |
|                      |                  |                               | Total     | 1.3        |      |
| R <sub>th(c)</sub>   | Coupling         | TO-220FPAB                    |           | 2.5        |      |
|                      |                  | TO-220AB / D <sup>2</sup> PAK |           | 0.3        |      |

When the diodes 1 and 2 are used simultaneously:

$$\Delta T_j (\text{diode1}) = P_{(\text{diode1})} \times R_{th(j-c)} (\text{per diode}) + P_{(\text{diode2})} \times R_{th(c)}$$

Table 4: Static electrical characteristics (per diode)

| Symbol      | Parameter               | Test conditions                     |                     | Min. | Typ. | Max. | Unit          |
|-------------|-------------------------|-------------------------------------|---------------------|------|------|------|---------------|
| $I_R^{(1)}$ | Reverse leakage current | $T_J = 25\text{ }^{\circ}\text{C}$  | $V_R = V_{RRM}$     | -    |      | 3.5  | $\mu\text{A}$ |
|             |                         | $T_J = 125\text{ }^{\circ}\text{C}$ |                     | -    | 1.3  | 4.5  | mA            |
| $V_F^{(2)}$ | Forward voltage drop    | $T_J = 25\text{ }^{\circ}\text{C}$  | $I_F = 5\text{ A}$  | -    |      | 0.73 | V             |
|             |                         | $T_J = 125\text{ }^{\circ}\text{C}$ |                     | -    | 0.57 | 0.61 |               |
|             |                         | $T_J = 25\text{ }^{\circ}\text{C}$  | $I_F = 10\text{ A}$ | -    |      | 0.85 |               |
|             |                         | $T_J = 125\text{ }^{\circ}\text{C}$ |                     | -    | 0.66 | 0.71 |               |

**Notes:**


<sup>(1)</sup>Pulse test:  $t_p = 5\text{ ms}$ ,  $\delta < 2\%$

<sup>(2)</sup>Pulse test:  $t_p = 380\text{ }\mu\text{s}$ ,  $\delta < 2\%$


To evaluate the conduction losses, use the following equation:

$$P = 0.51 \times I_{F(AV)} + 0.02 \times I_{F(RMS)}^2$$


## 1.1 Characteristics (curves)




**Figure 2: Average forward current versus ambient temperature ( $\delta = 0.5$ , per diode)**




**Figure 3: Normalized avalanche power deratings versus pulse duration ( $T_j = 125^\circ C$ )**




**Figure 4: Reverse leakage current versus reverse voltage applied (typical values, per diode)**




**Figure 5: Relative variation of thermal impedance junction to case versus pulse duration (TO-220AB, D<sup>2</sup>PAK)**




**Figure 6: Relative variation of thermal impedance junction to case versus pulse duration (TO-220FPAB)**




**Figure 7: Junction capacitance versus reverse voltage applied (typical values, per diode)**



**Figure 8: Forward voltage drop versus forward current (maximum values, per diode)**



**Figure 9: Thermal resistance junction to ambient versus copper surface under tab for D<sup>2</sup>PAK (typical values)**



## 2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: **[www.st.com](http://www.st.com)**. ECOPACK® is an ST trademark.

- Cooling method: by conduction (C)
- Epoxy meets UL 94,V0
- Recommended torque value: 0.55 N·m for TO-220AB
- Maximum torque value: 0.7 N·m for TO-220AB

## 2.1 TO-220AB package information

Figure 10: TO-220AB package outline




Table 5: TO-220AB package mechanical data

| Ref. | Dimensions  |       |            |       |
|------|-------------|-------|------------|-------|
|      | Millimeters |       | Inches     |       |
|      | Min.        | Max.  | Min.       | Max.  |
| A    | 4.40        | 4.60  | 0.173      | 0.181 |
| b    | 0.61        | 0.88  | 0.240      | 0.035 |
| b1   | 1.14        | 1.70  | 0.045      | 0.067 |
| c    | 0.48        | 0.70  | 0.019      | 0.028 |
| D    | 15.25       | 15.75 | 0.600      | 0.620 |
| D1   | 1.27 typ.   |       | 0.050 typ. |       |
| E    | 10.00       | 10.40 | 0.394      | 0.409 |
| e    | 2.40        | 2.70  | 0.094      | 0.106 |
| e1   | 4.95        | 5.15  | 0.195      | 0.203 |
| F    | 1.23        | 1.32  | 0.048      | 0.052 |
| H1   | 6.20        | 6.60  | 0.244      | 0.260 |
| J1   | 2.40        | 2.72  | 0.094      | 0.107 |
| L    | 13.00       | 14.00 | 0.512      | 0.551 |
| L1   | 3.50        | 3.93  | 0.138      | 0.155 |
| L20  | 16.40 typ.  |       | 0.646 typ. |       |
| L30  | 28.90 typ.  |       | 1.138 typ. |       |
| θP   | 3.75        | 3.85  | 0.148      | 0.152 |
| Q    | 2.65        | 2.95  | 0.104      | 0.116 |

## 2.2 TO-220FPAB package information

Figure 11: TO-220FPAB package outline







Table 6: TO-220FPAB package mechanical data

| Ref. | Dimensions  |      |           |       |
|------|-------------|------|-----------|-------|
|      | Millimeters |      | Inches    |       |
|      | Min.        | Max. | Min.      | Max.  |
| A    | 4.40        | 4.60 | 0.173     | 0.181 |
| B    | 2.5         | 2.7  | 0.098     | 0.106 |
| D    | 2.5         | 2.75 | 0.098     | 0.108 |
| E    | 0.45        | 0.70 | 0.018     | 0.028 |
| F    | 0.75        | 1    | 0.030     | 0.039 |
| F1   | 1.15        | 1.70 | 0.045     | 0.067 |
| F2   | 1.15        | 1.70 | 0.045     | 0.067 |
| G    | 4.95        | 5.2  | 0.195     | 0.205 |
| G1   | 2.4         | 2.7  | 0.094     | 0.106 |
| H    | 10          | 10.4 | 0.394     | 0.409 |
| L2   | 16 typ.     |      | 0.63 typ. |       |
| L3   | 28.60       | 30.6 | 1.126     | 1.205 |
| L4   | 9.8         | 10.6 | 0.386     | 0.417 |
| L5   | 2.9         | 3.6  | 0.114     | 0.142 |
| L6   | 15.9        | 16.4 | 0.626     | 0.646 |
| L7   | 9           | 9.3  | 0.354     | 0.366 |
| Dia  | 3           | 3.2  | 0.118     | 0.126 |


## 2.3 D<sup>2</sup>PAK package information

Figure 12: D<sup>2</sup>PAK package outline

This package drawing may slightly differ from the physical package. However, all the specified dimensions are guaranteed.

Table 7: D<sup>2</sup>PAK package mechanical data

| Ref. | Dimensions  |       |        |       |
|------|-------------|-------|--------|-------|
|      | Millimeters |       | Inches |       |
|      | Min.        | Max.  | Min.   | Max.  |
| A    | 4.36        | 4.60  | 0.172  | 0.181 |
| A1   | 0.00        | 0.25  | 0.000  | 0.010 |
| b    | 0.70        | 0.93  | 0.028  | 0.037 |
| b2   | 1.14        | 1.70  | 0.045  | 0.067 |
| c    | 0.38        | 0.69  | 0.015  | 0.027 |
| c2   | 1.19        | 1.36  | 0.047  | 0.053 |
| D    | 8.60        | 9.35  | 0.339  | 0.368 |
| D1   | 6.90        | 8.00  | 0.272  | 0.311 |
| D2   | 1.10        | 1.50  | 0.043  | 0.060 |
| E    | 10.00       | 10.55 | 0.394  | 0.415 |
| E1   | 8.10        | 8.90  | 0.319  | 0.346 |
| E2   | 6.85        | 7.25  | 0.266  | 0.282 |
| e    | 2.54 typ.   |       | 0.100  |       |
| e1   | 4.88        | 5.28  | 0.190  | 0.205 |
| H    | 15.00       | 15.85 | 0.591  | 0.624 |
| J1   | 2.49        | 2.90  | 0.097  | 0.112 |
| L    | 1.90        | 2.79  | 0.075  | 0.110 |
| L1   | 1.27        | 1.65  | 0.049  | 0.065 |
| L2   | 1.30        | 1.78  | 0.050  | 0.070 |
| R    | 0.4 typ.    |       | 0.015  |       |
| V2   | 0°          | 8°    | 0°     | 8°    |

Figure 13: D<sup>2</sup>PAK recommended footprint (dimensions in mm)

### 3 Ordering information

Table 8: Ordering information

| Order code      | Marking       | Package            | Weight | Base qty. | Delivery mode |
|-----------------|---------------|--------------------|--------|-----------|---------------|
| STPS10H100CT    | STPS10H100CT  | TO-220AB           | 1.9 g  | 50        | Tube          |
| STPS10H100CFP   | STPS10H100CFP | TO-220FPAB         | 1.9 g  | 50        | Tube          |
| STPS10H100CG-TR | STPS10H100CG  | D <sup>2</sup> PAK | 1.38 g | 1000      | Tape and reel |

### 4 Revision history

Table 9: Document revision history

| Date        | Revision | Changes  |
|-------------|----------|--|
| 20-Dec-2013 | 1        | Recovered contents of document STPS10H100, July 2003, Revision 3F (DocID6476), and removed I <sup>2</sup> PAK package.   |
| 17-Oct-2016 | 2        | Updated cover page, and <a href="#">Section 3.1: "Characteristics (curves)"</a> , <a href="#">Section 3: "Characteristics"</a> , <a href="#">Section 5: "Ordering information"</a> and <a href="#">Section 4.4: "D<sup>2</sup>PAK package information"</a> . |

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2016 STMicroelectronics – All rights reserved