

# TISP4290

## SYMMETRICAL TRANSIENT VOLTAGE SUPPRESSORS

APRIL 1987 - REVISED SEPTEMBER 1997

### absolute maximum ratings at 25°C case temperature (unless otherwise noted)

RATING	SYMBOL	VALUE	UNIT
Non-repetitive peak on-state pulse current (see Notes 1, 2 and 3)	$I_{TSP}$	150	A
8/20 $\mu$ s (ANSI C62.41, open-circuit voltage wave shape 1.2/50 $\mu$ s)		60	
10/160 $\mu$ s (FCC Part 68, open-circuit voltage wave shape 10/160 $\mu$ s)		50	
5/200 $\mu$ s (VDE 0433, open-circuit voltage wave shape 2 kV, 10/700 $\mu$ s)		38	
0.2/310 $\mu$ s (RLM 88, open-circuit voltage wave shape 1.5 kV, 0.5/700 $\mu$ s)		50	
5/310 $\mu$ s (CCITT IX K17/K20, open-circuit voltage wave shape 2 kV, 10/700 $\mu$ s)		50	
5/310 $\mu$ s (FTZ R12, open-circuit voltage wave shape 2 kV, 10/700 $\mu$ s)		45	
10/560 $\mu$ s (FCC Part 68, open-circuit voltage wave shape 10/560 $\mu$ s)		35	
10/1000 $\mu$ s (REA PE-60, open-circuit voltage wave shape 10/1000 $\mu$ s)			
Non-repetitive peak on-state current, 50 Hz, 2.5 s (see Notes 1 and 2)	$I_{TSM}$	10	A rms
Initial rate of rise of on-state current, Linear current ramp, Maximum ramp value < 38 A	$di_T/dt$	250	A/ $\mu$ s
Junction temperature	$T_J$	150	°C
Operating free - air temperature range		0 to 70	°C
Storage temperature range	$T_{stg}$	-40 to +150	°C
Lead temperature 1.5 mm from case for 10 s	$T_{lead}$	260	°C

- NOTES: 1. Above 70°C, derate linearly to zero at 150°C case temperature  
2. This value applies when the initial case temperature is at (or below) 70°C. The surge may be repeated after the device has returned to thermal equilibrium.  
3. Most PTT's quote an unloaded voltage waveform. In operation the TISP essentially shorts the generator output. The resulting loaded current waveform is specified.

### electrical characteristics, $T_J = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
$V_Z$ Reference zener voltage	$I_Z = \pm 1\text{ mA}$	$\pm 200$			V
$\alpha V_Z$ Temperature coefficient of reference voltage			0.1		%/°C
$V_{(BO)}$ Breakover voltage	(see Notes 4 and 5)			$\pm 290$	V
$I_{(BO)}$ Breakover current	(see Note 4)	$\pm 0.15$		$\pm 0.6$	A
$V_{TM}$ Peak on-state voltage	$I_T = \pm 5\text{ A}$ (see Notes 4 and 5)		$\pm 1.9$	$\pm 3$	V
$I_H$ Holding current	(see Note 4)	$\pm 150$			mA
$dv/dt$ Critical rate of rise of off-state voltage	(see Note 6)			$\pm 5$	kV/ $\mu$ s
$I_D$ Off-state leakage current	$V_D = \pm 50\text{ V}$			$\pm 10$	$\mu$ A
$C_{off}$ Off-state capacitance	$V_D = 0$ $f = 1\text{ kHz}$		110	200	pF

- NOTES: 4. These parameters must be measured using pulse techniques,  $t_w = 100\text{ }\mu\text{s}$ , duty cycle  $\leq 2\%$ .  
5. These parameters are measured with voltage sensing contacts separate from the current carrying contacts located within 3.2 mm (0.125 inch) from the device body.  
6. Linear rate of rise, maximum voltage limited to 80 %  $V_Z$  (minimum).

### thermal characteristics

PARAMETER	MIN	TYP	MAX	UNIT
$R_{\theta JA}$ Junction to free air thermal resistance			62.5	°C/W

## PRODUCT INFORMATION

# PARAMETER MEASUREMENT INFORMATION





Figure 1. VOLTAGE-CURRENT CHARACTERISTIC FOR TERMINALS A AND B

**TYPICAL CHARACTERISTICS**  
**A and B terminals**




**Figure 2.**

## MECHANICAL DATA

### DO-220

#### 2-pin plastic flange-mount package

This single-in-line package consists of a circuit mounted on a lead frame and encapsulated within a plastic compound. The compound will withstand soldering temperature with no deformation, and circuit performance characteristics will remain stable when operated in high humidity conditions. Leads require no additional cleaning or processing when used in soldered assembly.



- NOTES: A. Tie bar short stand off height according to package version.  
 Version 1, pin 1 is in electrical contact with the mounting tab via tie bar short - stand off height : 2,0 mm maximum.  
 Version 2, pin 1 is in electrical contact with the mounting tab (no external tie bar short).  
 B. Mounting tab corner profile according to package version.  
 C. Typical fixing hole centre stand off height according to package version.  
 Version 1, 18,0 mm. Version 2, 17,6 mm.

## PRODUCT INFORMATION

# **TISP4290**

## **SYMMETRICAL TRANSIENT VOLTAGE SUPPRESSORS**

APRIL 1987 - REVISED SEPTEMBER 1997

---

### **IMPORTANT NOTICE**

Power Innovations Limited (PI) reserves the right to make changes to its products or to discontinue any semiconductor product or service without notice, and advises its customers to verify, before placing orders, that the information being relied on is current.

PI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with PI's standard warranty. Testing and other quality control techniques are utilized to the extent PI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except as mandated by government requirements.

PI accepts no liability for applications assistance, customer product design, software performance, or infringement of patents or services described herein. Nor is any license, either express or implied, granted under any patent right, copyright, design right, or other intellectual property right of PI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used.

PI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, INTENDED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT APPLICATIONS, DEVICES OR SYSTEMS.

Copyright © 1997, Power Innovations Limited

### **PRODUCT INFORMATION**