

**PROTECTION PRODUCTS**
**Absolute Maximum Rating**

| Rating                                                                                   | Symbol    | Value            | Units |
|------------------------------------------------------------------------------------------|-----------|------------------|-------|
| Peak Pulse Power ( $t_p = 8/20\mu s$ ) <sup>1</sup>                                      | $P_{pk}$  | 1200 - 1500      | Watts |
| ESD per IEC 61000-4-2 (Air) <sup>2</sup><br>ESD per IEC 61000-4-2 (Contact) <sup>2</sup> | $V_{ESD}$ | +/- 30<br>+/- 30 | kV    |
| Operating Temperature                                                                    | $T_J$     | -40 to +125      | °C    |
| Storage Temperature                                                                      | $T_{STG}$ | -55 to +150      | °C    |

**Electrical Characteristics (T=25°C unless otherwise specified)**
**uClamp0571P**

| Parameter                          | Symbol    | Conditions                                    | Minimum | Typical | Maximum | Units |
|------------------------------------|-----------|-----------------------------------------------|---------|---------|---------|-------|
| Reverse Stand-Off Voltage          | $V_{RWM}$ | Pin 1 to 2                                    |         |         | 5       | V     |
| Reverse Breakdown Voltage          | $V_{BR}$  | $I_t = 1mA$<br>Pin 1 to 2                     | 6       | 7       | 9       | V     |
| Reverse Leakage Current            | $I_R$     | $V_{RWM} = 5V, T=25^\circ C$<br>Pin 1 to 2    |         | <10     | 100     | nA    |
| Peak Pulse Current                 | $I_{PP}$  | $t_p = 8/20\mu s$<br>Pin 1 to 2               |         |         | 80      | A     |
| Clamping Voltage                   | $V_C$     | $I_{PP} = 40A, t_p = 8/20\mu s$<br>Pin 1 to 2 |         |         | 10      | V     |
| Clamping Voltage                   | $V_C$     | $I_{PP} = 80A, t_p = 8/20\mu s$<br>Pin 1 to 2 |         |         | 15      | V     |
| Dynamic Resistance <sup>3, 4</sup> | $R_{DYN}$ | $t_{lp} = 0.2 / 100ns$                        |         | 0.05    |         | Ohms  |
| Junction Capacitance               | $C_j$     | $V_R = 0V, f = 1MHz$                          |         |         | 675     | pF    |

## PROTECTION PRODUCTS

## uClamp0871P

| Parameter                          | Symbol    | Conditions                                    | Minimum | Typical | Maximum | Units |
|------------------------------------|-----------|-----------------------------------------------|---------|---------|---------|-------|
| Reverse Stand-Off Voltage          | $V_{RWM}$ | Pin 1 to 2                                    |         |         | 8       | V     |
| Reverse Breakdown Voltage          | $V_{BR}$  | $I_t = 1mA$<br>Pin 1 to 2                     | 9.5     | 11      | 13      | V     |
| Reverse Leakage Current            | $I_R$     | $V_{RWM} = 8V, T=25^{\circ}C$<br>Pin 1 to 2   |         | <10     | 100     | nA    |
| Peak Pulse Current                 | $I_{PP}$  | $t_p = 8/20\mu s$<br>Pin 1 to 2               |         |         | 65      | A     |
| Clamping Voltage                   | $V_C$     | $I_{PP} = 10A, t_p = 8/20\mu s$<br>Pin 1 to 2 |         |         | 15      | V     |
| Clamping Voltage                   | $V_C$     | $I_{PP} = 65A, t_p = 8/20\mu s$<br>Pin 1 to 2 |         |         | 23      | V     |
| Dynamic Resistance <sup>3, 4</sup> | $R_{DYN}$ | $t_{lp} = 0.2 / 100ns$                        |         | 0.05    |         | Ohms  |
| Junction Capacitance               | $C_J$     | $V_R = 0V, f = 1MHz$                          |         |         | 475     | pF    |

## uClamp1071P

| Parameter                          | Symbol    | Conditions                                    | Minimum | Typical | Maximum | Units |
|------------------------------------|-----------|-----------------------------------------------|---------|---------|---------|-------|
| Reverse Stand-Off Voltage          | $V_{RWM}$ | Pin 1 to 2                                    |         |         | 10      | V     |
| Reverse Breakdown Voltage          | $V_{BR}$  | $I_t = 1mA$<br>Pin 1 to 2                     | 12      | 13.5    | 15.5    | V     |
| Reverse Leakage Current            | $I_R$     | $V_{RWM} = 10V, T=25^{\circ}C$<br>Pin 1 to 2  |         | <10     | 100     | nA    |
| Peak Pulse Current                 | $I_{PP}$  | $t_p = 8/20\mu s$<br>Pin 1 to 2               |         |         | 60      | A     |
| Clamping Voltage                   | $V_C$     | $I_{PP} = 10A, t_p = 8/20\mu s$<br>Pin 1 to 2 |         |         | 17      | V     |
| Clamping Voltage                   | $V_C$     | $I_{PP} = 60A, t_p = 8/20\mu s$<br>Pin 1 to 2 |         |         | 25      | V     |
| Dynamic Resistance <sup>3, 4</sup> | $R_{DYN}$ | $t_{lp} = 0.2 / 100ns$                        |         | 0.05    |         | Ohms  |
| Junction Capacitance               | $C_J$     | $V_R = 0V, f = 1MHz$                          |         |         | 350     | pF    |

**PROTECTION PRODUCTS**

Electrical Characteristics (T=25°C unless otherwise specified)

| <b>uClamp1271P</b>                 |               |                                               |                |                |                |              |
|------------------------------------|---------------|-----------------------------------------------|----------------|----------------|----------------|--------------|
| <b>Parameter</b>                   | <b>Symbol</b> | <b>Conditions</b>                             | <b>Minimum</b> | <b>Typical</b> | <b>Maximum</b> | <b>Units</b> |
| Reverse Stand-Off Voltage          | $V_{RWM}$     | Pin 1 to 2                                    |                |                | 12             | V            |
| Reverse Breakdown Voltage          | $V_{BR}$      | $I_t = 1mA$<br>Pin 1 to 2                     | 14             | 16             | 19             | V            |
| Reverse Leakage Current            | $I_R$         | $V_{RWM} = 12V, T=25^\circ C$<br>Pin 1 to 2   |                | <10            | 100            | nA           |
| Peak Pulse Current                 | $I_{PP}$      | $t_p = 8/20\mu s$<br>Pin 1 to 2               |                |                | 45             | A            |
| Clamping Voltage                   | $V_C$         | $I_{PP} = 10A, t_p = 8/20\mu s$<br>Pin 1 to 2 |                |                | 22             | V            |
| Clamping Voltage                   | $V_C$         | $I_{PP} = 45A, t_p = 8/20\mu s$<br>Pin 1 to 2 |                |                | 30             | V            |
| Dynamic Resistance <sup>3, 4</sup> | $R_{DYN}$     | $t_{lp} = 0.2 / 100ns$                        |                | 0.05           |                | Ohms         |
| Junction Capacitance               | $C_j$         | $V_R = 0V, f = 1MHz$                          |                |                | 275            | pF           |

| <b>uClamp1571P</b>                 |               |                                               |                |                |                |              |
|------------------------------------|---------------|-----------------------------------------------|----------------|----------------|----------------|--------------|
| <b>Parameter</b>                   | <b>Symbol</b> | <b>Conditions</b>                             | <b>Minimum</b> | <b>Typical</b> | <b>Maximum</b> | <b>Units</b> |
| Reverse Stand-Off Voltage          | $V_{RWM}$     | Pin 1 to 2                                    |                |                | 15             | V            |
| Reverse Breakdown Voltage          | $V_{BR}$      | $I_t = 1mA$<br>Pin 1 to 2                     | 17.5           | 20             | 23             | V            |
| Reverse Leakage Current            | $I_R$         | $V_{RWM} = 15V, T=25^\circ C$<br>Pin 1 to 2   |                | <10            | 100            | nA           |
| Peak Pulse Current                 | $I_{PP}$      | $t_p = 8/20\mu s$<br>Pin 1 to 2               |                |                | 40             | A            |
| Clamping Voltage                   | $V_C$         | $I_{PP} = 10A, t_p = 8/20\mu s$<br>Pin 1 to 2 |                |                | 25             | V            |
| Clamping Voltage                   | $V_C$         | $I_{PP} = 40A, t_p = 8/20\mu s$<br>Pin 1 to 2 |                |                | 40             | V            |
| Dynamic Resistance <sup>3, 4</sup> | $R_{DYN}$     | $t_{lp} = 0.2 / 100ns$                        |                | 0.05           |                | Ohms         |
| Junction Capacitance               | $C_j$         | $V_R = 0V, f = 1MHz$                          |                |                | 220            | pF           |

**PROTECTION PRODUCTS**

| <b>uClamp1871P</b>                 |               |                                               |                |                |                |              |
|------------------------------------|---------------|-----------------------------------------------|----------------|----------------|----------------|--------------|
| <b>Parameter</b>                   | <b>Symbol</b> | <b>Conditions</b>                             | <b>Minimum</b> | <b>Typical</b> | <b>Maximum</b> | <b>Units</b> |
| Reverse Stand-Off Voltage          | $V_{RWM}$     | Pin 1 to 2                                    |                |                | 18             | V            |
| Reverse Breakdown Voltage          | $V_{BR}$      | $I_t = 1mA$<br>Pin 1 to 2                     | 20             | 22             | 25             | V            |
| Reverse Leakage Current            | $I_R$         | $V_{RWM} = 18V, T=25^{\circ}C$<br>Pin 1 to 2  |                | <10            | 100            | nA           |
| Peak Pulse Current                 | $I_{PP}$      | $t_p = 8/20\mu s$<br>Pin 1 to 2               |                |                | 35             | A            |
| Clamping Voltage                   | $V_C$         | $I_{PP} = 10A, t_p = 8/20\mu s$<br>Pin 1 to 2 |                |                | 28             | V            |
| Clamping Voltage                   | $V_C$         | $I_{PP} = 35A, t_p = 8/20\mu s$<br>Pin 1 to 2 |                |                | 45             | V            |
| Dynamic Resistance <sup>3, 4</sup> | $R_{DYN}$     | $t_{lp} = 0.2 / 100ns$                        |                | 0.10           |                | Ohms         |
| Junction Capacitance               | $C_J$         | $V_R = 0V, f = 1MHz$                          |                |                | 225            | pF           |

| <b>uClamp2271P</b>                 |               |                                               |                |                |                |              |
|------------------------------------|---------------|-----------------------------------------------|----------------|----------------|----------------|--------------|
| <b>Parameter</b>                   | <b>Symbol</b> | <b>Conditions</b>                             | <b>Minimum</b> | <b>Typical</b> | <b>Maximum</b> | <b>Units</b> |
| Reverse Stand-Off Voltage          | $V_{RWM}$     | Pin 1 to 2                                    |                |                | 22             | V            |
| Reverse Breakdown Voltage          | $V_{BR}$      | $I_t = 1mA$<br>Pin 1 to 2                     | 25.5           | 29             | 33.5           | V            |
| Reverse Leakage Current            | $I_R$         | $V_{RWM} = 22V, T=25^{\circ}C$<br>Pin 1 to 2  |                | <10            | 100            | nA           |
| Peak Pulse Current                 | $I_{PP}$      | $t_p = 8/20\mu s$<br>Pin 1 to 2               |                |                | 25             | A            |
| Clamping Voltage                   | $V_C$         | $I_{PP} = 10A, t_p = 8/20\mu s$<br>Pin 1 to 2 |                |                | 40             | V            |
| Clamping Voltage                   | $V_C$         | $I_{PP} = 25A, t_p = 8/20\mu s$<br>Pin 1 to 2 |                |                | 55             | V            |
| Dynamic Resistance <sup>3, 4</sup> | $R_{DYN}$     | $t_{lp} = 0.2 / 100ns$                        |                | 0.10           |                | Ohms         |
| Junction Capacitance               | $C_J$         | $V_R = 0V, f = 1MHz$                          |                |                | 165            | pF           |

**PROTECTION PRODUCTS**

Electrical Characteristics (T=25°C unless otherwise specified)

**uClamp2671P**

| Parameter                          | Symbol    | Conditions                                    | Minimum | Typical | Maximum | Units |
|------------------------------------|-----------|-----------------------------------------------|---------|---------|---------|-------|
| Reverse Stand-Off Voltage          | $V_{RWM}$ | Pin 1 to 2                                    |         |         | 26      | V     |
| Reverse Breakdown Voltage          | $V_{BR}$  | $I_t = 1mA$<br>Pin 1 to 2                     | 29      | 32      | 35      | V     |
| Reverse Leakage Current            | $I_R$     | $V_{RWM} = 26V, T=25^\circ C$<br>Pin 1 to 2   |         | <10     | 100     | nA    |
| Peak Pulse Current                 | $I_{PP}$  | $t_p = 8/20\mu s$<br>Pin 1 to 2               |         |         | 23      | A     |
| Clamping Voltage                   | $V_C$     | $I_{PP} = 10A, t_p = 8/20\mu s$<br>Pin 1 to 2 |         |         | 50      | V     |
| Clamping Voltage                   | $V_C$     | $I_{PP} = 23A, t_p = 8/20\mu s$<br>Pin 1 to 2 |         |         | 65      | V     |
| Dynamic Resistance <sup>3, 4</sup> | $R_{DYN}$ | $t_{lp} = 0.2 / 100ns$                        |         | 0.15    |         | Ohms  |
| Junction Capacitance               | $C_J$     | $V_R = 0V, f = 1MHz$                          |         |         | 155     | pF    |

**uClamp3671P**

| Parameter                          | Symbol    | Conditions                                     | Minimum | Typical | Maximum | Units |
|------------------------------------|-----------|------------------------------------------------|---------|---------|---------|-------|
| Reverse Stand-Off Voltage          | $V_{RWM}$ | Pin 1 to 2                                     |         |         | 36      | V     |
| Reverse Breakdown Voltage          | $V_{BR}$  | $I_t = 1mA$<br>Pin 1 to 2                      | 37      |         | 44      | V     |
| Reverse Leakage Current            | $I_R$     | $V_{RWM} = 36V, T=25^\circ C$<br>Pin 1 to 2    |         | <10     | 100     | nA    |
| Peak Pulse Current                 | $I_{PP}$  | $t_p = 8/20\mu s$<br>Pin 1 to 2                |         |         | 18      | A     |
| Clamping Voltage                   | $V_C$     | $I_{PP} = 2A, t_p = 1.2/50\mu s$<br>Pin 1 to 2 |         |         | 48      | V     |
| Clamping Voltage                   | $V_C$     | $I_{PP} = 18A, t_p = 8/20\mu s$<br>Pin 1 to 2  |         |         | 80      | V     |
| Dynamic Resistance <sup>3, 4</sup> | $R_{DYN}$ | $t_{lp} = 0.2 / 100ns$                         |         | 0.29    |         | Ohms  |
| Junction Capacitance               | $C_J$     | $V_R = 0V, f = 1MHz$                           |         |         | 150     | pF    |

**Notes**

 1) Peak Pulse Power =  $V_C(\max) \times I_{PP(\max)}$  ( $t_p = 8/20\mu s$ )

2) ESD gun return path connected to ESD ground reference plane.


 3) Transmission Line Pulse Test (TLP) Settings:  $t_p = 100ns$ ,  $t_r = 0.2ns$ ,  $I_{TLP}$  and  $V_{TLP}$  averaging window:  $t_1 = 70ns$  to  $t_2 = 90ns$ .

 4) Dynamic resistance calculated from  $I_{TLP} = 4A$  to  $I_{TLP} = 16A$


## PROTECTION PRODUCTS

### Typical Characteristics


**Non-Repetitive Peak Pulse Power vs. Pulse Time**




**Clamping Voltage vs. Peak Pulse Current ( $t_p=8/20\mu$ s)**




**Forward Voltage vs. Peak Pulse Current ( $t_p=8/20\mu$ s)**




**TLP Characteristic**















**ESD Clamping - uClamp0571P  
(+8kV Contact per IEC 61000-4-2)**



**ESD Clamping - uClamp0571P  
(-8kV Contact per IEC 61000-4-2)**




**PROTECTION PRODUCTS**
**Typical Characteristics**
**ESD Clamping - uClamp0871P  
(+8kV Contact per IEC 61000-4-2)**

**ESD Clamping - uClamp0871P  
(-8kV Contact per IEC 61000-4-2)**

**ESD Clamping - uClamp1071P  
(+8kV Contact per IEC 61000-4-2)**

**ESD Clamping - uClamp1071P  
(-8kV Contact per IEC 61000-4-2)**

**ESD Clamping - uClamp1271P  
(+8kV Contact per IEC 61000-4-2)**

**ESD Clamping - uClamp1271P  
(-8kV Contact per IEC 61000-4-2)**


**PROTECTION PRODUCTS**
**Typical Characteristics**
**ESD Clamping - uClamp1571P  
(+8kV Contact per IEC 61000-4-2)**

**ESD Clamping - uClamp1571P  
(-8kV Contact per IEC 61000-4-2)**

**ESD Clamping - uClamp1871P  
(+8kV Contact per IEC 61000-4-2)**

**ESD Clamping - uClamp1871P  
(-8kV Contact per IEC 61000-4-2)**

**ESD Clamping - uClamp2271P  
(+8kV Contact per IEC 61000-4-2)**

**ESD Clamping - uClamp2271P  
(-8kV Contact per IEC 61000-4-2)**



# PROTECTION PRODUCTS

## Typical Characteristics


**ESD Clamping - uClamp2671P**  
(+8kV Contact per IEC 61000-4-2)




**ESD Clamping - uClamp2671P**  
(-8kV Contact per IEC 61000-4-2)



**ESD Clamping - uClamp3671P**  
(+8kV Contact per IEC 61000-4-2)



**ESD Clamping - uClamp3671P**  
(-8kV Contact per IEC 61000-4-2)




## PROTECTION PRODUCTS

### Applications Information

#### Assembly Guidelines

The table below provides Semtech's recommended assembly guidelines for mounting this device. The figure at the right details Semtech's recommended aperture based on the below recommendations. Note that these are only recommendations and should serve only as a starting point for design since there are many factors that affect the assembly process. The exact manufacturing parameters will require some experimentation to get the desired solder application.



| Assembly Parameter       | Recommendation                   |
|--------------------------|----------------------------------|
| Solder Stencil Design    | Laser cut, Electro-polished      |
| Aperture shape           | Rectangular with rounded corners |
| Solder Stencil Thickness | 0.125 mm (0.005")                |
| Solder Paste Type        | Type 3 size sphere or smaller    |
| Solder Reflow Profile    | Per JEDEC J-STD-020              |
| PCB Solder Pad Design    | Non-Solder mask defined          |
| PCB Pad Finish           | OSP OR NiAu                      |



All Dimensions are in mm.


 Land Pad. 
  Stencil opening 
  Component

#### Recommended Mounting Pattern

**PROTECTION PRODUCTS**
**Outline Drawing - SGP1610N2**

**Land Pattern - SGP1610N2**


## PROTECTION PRODUCTS

### Example Device Marking



#### Notes:

1) Marking includes marking code, pin 1 bar, and 2x5 matrix date code

### Ordering Information


| Part Number     | Marking Code | Working Voltage | Qty per Reel |
|-----------------|--------------|-----------------|--------------|
| uClamp0571P.TNT | 06           | 5V              | 10,000       |
| uClamp0871P.TNT | 11           | 8V              | 10,000       |
| uClamp1071P.TNT | 12           | 10V             | 10,000       |
| uClamp1271P.TNT | 16           | 12V             | 10,000       |
| uClamp1571P.TNT | 18           | 15V             | 10,000       |
| uClamp1871P.TNT | 24           | 18V             | 10,000       |
| uClamp2271P.TNT | 26           | 22V             | 10,000       |
| uClamp2671P.TNT | 30           | 26V             | 10,000       |
| uClamp3671P.TNT | 37           | 36V             | 10,000       |

#### Notes:

MicroClamp, uClamp and  $\mu$ Clamp are trademarks of Semtech Corporation

## PROTECTION PRODUCTS


## Carrier Tape Specification



SECTION A-A

NOTES: 1.) ALL DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.

Note: All dimensions in mm unless otherwise specified



PIN 1 Location  
(Towards Sprocket Holes)

## Device Orientation in Tape

## Contact Information

Semtech Corporation  
Protection Products Division  
200 Flynn Rd., Camarillo, CA 93012  
Phone: (805)498-2111 FAX (805)498-3804