

Datasheet	VSC7428-02 and VSC7429-02 Caracal Datasheet		4.0	10/12/2012		8 MB
Application Note	Magnetics Guide		2.0	06/27/2012		626 kB
Application Note	Distributed Transparent Clock over Microwave		1.0	11/01/2012		193 kB
Application Note	IEEE1588 Configuration Guide		1.0	04/04/2011		473 kB
Application Note	IEEE1588v2 and SyncE - Applications and Operation Using Vitesse's Synchronization Solution		3.0	11/01/2012		2 MB
Application Note	PTP Clock Implementation Using the Caracal Switch		1.0	10/12/2011		223 kB
Application Note	Service OAM		1.0	11/18/2010		550 kB
Application Note	Using the SparX-III Serial GPIO/LED Controller		1.0	08/02/2012		2 MB
Application Note	Vitesse Linux BSP		1.1	12/14/2010		155 kB
Reference Design	Reference Design 24 Cu ports + 2 SFP Managed Switch and PHY		2.3	10/01/2012		61 MB
Software	Embedded Configurable Operating System (eCos-3.0) Vitesse repository and arm-elf tools		3.0	06/07/2012		66 MB
Software	Vitesse Linux BSP		2.2	12/13/2010		8 MB
Software	API Release Notes		4.30	05/07/2013		26 kB
Software	eCos Operating System		1.0	06/20/2013		21 MB
Software	WebStaX, SMBStaX, and CEServices Release Notes		3.30	05/07/2013		128 kB
Software	WebStaX-III, SMBStaX-III, and CEServices Release Note		2.80f	11/27/2012		78 kB
White Paper	Precise Timing for Base Stations in the Evolution to LTE		00-04	02/19/2013		4 MB
White Paper	The Vitesse Service Aware Architecture (ViSAA) for Carrier Ethernet Switches		1.0	05/30/2013		2 MB
Reports	VSC7424XJG, VSC7425XJG, VSC7426XJG, VSC7427XJG, VSC7428XJG, VSC7429XJG and VSC8512XJG Material Composition Declaration - (A109160 Substrate)		2.0	10/10/2011		22 kB
Reports	VSC7424XJG-01, VSC7425XJG-01, VSC7426XJG-01, VSC7427XJG-01, VSC7428XJG-01, VSC7429XJG-01, VSC8512XJG-01 Material Composition Declaration - Au Wire		1.0	04/13/2012		22 kB

Reports	VSC7424XJG-02, VSC7425XJG-02, VSC7426XJG-02, VSC7427XJG-02, VSC7428XJG-02, VSC7429XJG-02, VSC8512XJG-02 and VSC8512XJG-03 Material Composition Declaration - Cu Wire		3.0	01/31/2013		22 kB
Reports	First Level Product Qualification Report for VSC7429XJG-02 - Cu Wire		3.0	06/19/2013		88 kB



Product Brochures

- [Solutions Guide](#)
- [Product Line Guide](#)
- [Cloud Business Services](#)
- [EcoEthernet Overview](#)
- [FlexEQ Overview](#)
- [Intellisec](#)
- [IP Licensing](#)
- [Mobile Access Solutions](#)
- [UTM Solutions](#)
- [VeriTime](#)
- [ViSAA](#)
- [VScope Overview](#)

Quick Links

- [Knowledge Base](#)
- [Sales & Support](#)

Key Features

- Integrated Cu PHYs
- IEEE 1588 and Synchronous Ethernet network timing
- Supports IEEE802.3az and green energy efficiency modes with ActiPHY™ and PerfectReach™

Applications

- Ethernet Access Devices (EAD): CPE, NTE, and MTU
- Mobile backhaul
- Carrier Ethernet switches

Related Products

- [Ethernet Switches](#)
- [Ethernet MACs](#)

Feedback on this product?

[Click here to comment](#)

