



6 Lake Street, Lawrence, MA 01841  
1-800-446-1158 / (978) 620-2600 / Fax: (978) 689-0803  
Website: <http://www.microsemi.com>

# TECHNICAL DATA SHEET

Gort Road Business Park, Ennis, Co. Clare, Ireland  
Tel: +353 (0) 65 6840044 Fax: +353 (0) 65 6822298

## APPLICATIONS / BENEFITS

- Protection from switching transients and induced RF
- Protects TTL, ECL, DTL, MOS, MSI, and other integrated circuits requiring 5.0 V or lower power supplies
- Protection from ESD and EFT per IEC 61000-4-2 and IEC 61000-4-4
- Secondary lightning protection per IEC61000-4-5 with 42 Ohms source impedance: Class 1 thru 4
- Secondary lightning protection per IEC61000-4-5 with 12 Ohms source impedance: Class 1 thru 4
- Secondary lightning protection per IEC61000-4-5 with 2 Ohms source impedance: Class 2 & 3
- 1N5907 Inherently radiation hard as described in Microsemi MicroNote 050

## MAXIMUM RATINGS

- 1500 Watts for 10/1000  $\mu$ s at lead temperature ( $T_L$ ) 25°C (See Figs. 1, 2, and 4) with repetition rate of 0.01% or less\*
- Operating & Storage Temperatures: -65° to +175°C for 1N5907
- THERMAL RESISTANCE (junction to lead): 50°C/W for 1N5907
- THERMAL RESISTANCE (junction to ambient): 110°C/W for 1N5907
- DC Power Dissipation\* (1N5907): 1 Watt at  $T_L \leq 125^\circ\text{C}$  3/8" (10 mm) from body, or 1 Watt at  $T_A \leq +65^\circ\text{C}$  when mounted on FR4 PC board as described for thermal resistance junction to ambient
- Forward surge current: 200 A for 8.3ms half-sine wave at  $T_A = +25^\circ\text{C}$
- Solder Temperatures: 260 ° C for 10 s (maximum)

## MECHANICAL AND PACKAGING

- CASE (1N5907): DO-13 (DO-202AA) welded hermetically sealed metal and glass
- FINISH: External metal surfaces are Tin-Lead (Sn-Pb) plated and solderable per MIL-STD-750 method 2026
- POLARITY: Polarity indicated by diode symbol or cathode band (cathode connected to case for 1N5907)
- MARKING: Part number and polarity symbol
- WEIGHT: 1.4 grams. (Approx)
- TAPE & REEL option: Standard per EIA-296 (add "TR" suffix to part number)
- See package dimension on last page

\* TVS devices are not typically used for dc power dissipation and are instead operated at or less than their rated standoff voltage ( $V_{WM}$ ) except for transients that briefly drive the device into avalanche breakdown ( $V_{BR}$  to  $V_C$  region).

## ELECTRICAL CHARACTERISTICS @ 25°C

JEDEC Type No.	Reverse Standoff Voltage $V_{WM}$ (NOTE 1)	Minimum Breakdown Voltage $V_{(BR)}$ @ 1 mA	Maximum Standby Current $I_D$ @ $V_{WM}$	Maximum Clamping Voltage $V_C$ @ $I_{PP1}$ (FIG. 3)	Peak Pulse Current $I_{PP1}$ (FIG. 3)	Maximum Clamping Voltage $V_C$ @ $I_{PP2}$ (FIG. 3)	Peak Pulse Current $I_{PP2}$ (FIG. 3)	Maximum Clamping Voltage $V_C$ @ $I_{PP3}$ (FIG. 3)	Peak Pulse Current $I_{PP3}$ (FIG. 3)
	Volts	Volts	$\mu A$	Volts	Amps	Volts	Amps	Volts	Amps
1N5907 *	5.0	6.0	300	7.6	30	8.0	60	8.5	120


\* Also available in military qualified types with a JAN, JANTX, or JANTXV prefix per MIL-PRF-19500/500.

**NOTE 1:** A TVS is normally selected according to the reverse “Standoff Voltage”  $V_{WM}$  which should be equal to or greater than the dc or continuous peak operating voltage level.


## SYMBOLS & DEFINITIONS

Symbol	Definition
$V_{WM}$	Standoff Voltage: Applied Reverse Voltage to assure a nonconductive condition. (See Note 1 above)
$V_{(BR)}$	Breakdown Voltage: This is the Breakdown Voltage the device will exhibit at 25°C
$V_C$	Maximum Clamping Voltage: The maximum peak voltage appearing across the TVS when subjected to the peak pulse current in a one millisecond time interval. The peak pulse voltage is the combination of voltage rise due to both the series resistance and thermal rise and positive temperature coefficient ( $\alpha_{V(BR)}$ )
$I_{PP}$	Peak Pulse Current: The peak current during the impulse (See Figure 2)
$P_{PP}$	Peak Pulse Power: The pulse power as determined by the product of $V_C$ and $I_{PP}$
$I_D$	Standby Current: The current at the standoff voltage ( $V_{WM}$ )
$I_{(BR)}$	Breakdown Current: The current used for measuring Breakdown Voltage ( $V_{(BR)}$ )


## GRAPHS




**FIGURE 1**  
PEAK PULSE POWER VS. PULSE TIME



**FIGURE 2**  
DERATING CURVE




**FIGURE 3**  
PULSE WAVEFORM



**FIGURE 4** TYPICAL CLAMPING VOLTAGE ( $V_c$ )  
VS. PEAK PULSE CURRENT ( $I_{pp}$ )

## PACKAGE DIMENSIONS



### NOTES:

1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. The major diameter is essentially constant along its length.
4. Within this zone, diameter may vary to allow for lead finishes and irregularities.
5. Dimension to allow for pinch or seal deformation anywhere along tubulation.
6. Lead 1 (cathode) shall be electrically connected to the case.
7. In accordance with ASME Y14.5M, diameters are equivalent to  $\phi$ x symbology.

Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
BD	.215	.235	5.46	5.97	
BL	.293	.357	7.44	9.07	3
BLT		.570		14.48	
CD	.045	.100	1.14	2.54	5
LD	.025	.035	0.64	0.89	
LL	1.000	1.625	25.40	41.28	4
LU		.188		4.78	4

**FIGURE 1.** Physical dimensions (DO-13).