

3SBH1139A2 Product Details



3SBH1139A2

(1-1617076-1)

TE Internal Number: 1-1617076-1

Active

Military/Aerospace High Performance Relays

Not EU RoHS or ELV Compliant

- Product Highlights:

 - 3SBH 1/5-Size Relay Series
 - Input Voltage = 26.5 VDC
 - Contact Arrangement = 4 Form C, 4PDT, 4 C/O
 - Contact Current Rating = 2 A
 - Non Polarized, Monostable Coil Magnetic System

View all Features

Quick Links

- Check Pricing & Availability

Search for Tooling

Product Feature Selector

Contact Us About This Product

Add to My Part List

Request Sample

Find Similar Products

Buy Product

Documentation & Additional Information	
Product Drawings: - None Available Catalog Pages/Data Sheets: - RELAY (PDF, English) Product Specifications: - None Available Application Specifications: - None Available Instruction Sheets: - None Available CAD Files: - None Available	Additional Information: - Product Line Information Related Products: - Tooling
List all Documents	

Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: - Termination Type = PC Pins Electrical Characteristics: - Input Voltage (VDC) = 26.5 - Contact Current Rating (A) = 2 - Coil Polarity Protection Diode = Without - Transistor Driver = Without - Coil Resistance (Ω) = 720 - MOSFET Driver = Without - Coil Power Measurement = Milliwatts - Coil Power, Nominal (mW) = 975 - Actuating System = DC - Shock = 75 G's, 6ms - Vibration = 30G's, 10 to 3000Hz Body Related Features: - Series = 3SBH 1/5-Size Relay Contact Related Features: - Mounting Options = PC Board - Enclosure Type = Hermetically Sealed - Approved Standards = M39016 Qualified, M Level	Configuration Related Features: - Contact Arrangement = 4 Form C, 4PDT, 4 C/O - Coil Magnetic System = Non Polarized, Monostable - Coil Suppression Diode = Without Industry Standards: - Government/Industry Qualification = Yes - Government/Industry Part Number = M39016/14-002M - RoHS/ELV Compliance = Not ELV/RoHS compliant - Lead Free Solder Processes = Not suitable for lead free processing Conditions for Usage: - Temperature Range (°C) = -65 - +125 Other: - Brand = CII

BOOKMARK