

November 2011

# MPSA64 / MMBTA64 / PZTA64 PNP Darlington Transistor

### Features

- This device is designed for applications requiring extremely high current gain at currents to 800 mA.
- Sourced from Process 61.



### Absolute Maximum Ratings\* $T_a = 25^{\circ}C$ unless otherwise noted

Symbol	Parameter	Value	Units
V <sub>CES</sub>	Collector-Emitter Voltage	-30	V
V <sub>CBO</sub>	Collector-Base Voltage	-30	V
V <sub>EBO</sub>	Emitter-Base Voltage	-10	V
۱ <sub>C</sub>	Collector Current - Continuous	-1.2	A
T <sub>J,</sub> T <sub>stg</sub>	Operating and Storage Junction Temperature Range	-55 to +150	٦°

\* These ratings are limiting values above which the serviceability of any semiconductor device may be impaired. **NOTES:** 

1) These ratings are based on a maximum junction temperature of 150 degrees C.

2) These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

## Thermal Characteristics $T_a = 25^{\circ}C$ unless otherwise noted

Symbol	Parameter	Max.			Units
Symbol		MPSA64	*MMBTA64	**PZTA64	Units
P <sub>D</sub>	Total Device Dissipation Derate above 25°C	625 5.0	350 2.8	1,000 8.0	mW mW/°C
$R_{ extsf{ heta}JC}$	Thermal Resistance, Junction to Case	83.3			°C/W
R <sub>0JA</sub>	Thermal Resistance, Junction to Ambient	200	357	125	°C/W

\* Device mounted on FR-4 PCB 1.6" X 1.6" X 0.06."


\*\* Device mounted on FR-4 PCB 36 mm X 18 mm X 1.5 mm; mounting pad for the collector lead min. 6 cm<sup>2</sup>.


© 2011 Fairchild Semiconductor Corporation MPSA64 / MMBTA64 / PZTA64 Rev. B0

Symbol	Parameter	Test Condition	Min.	Max.	Units
OFF CHARAG	TERISTICS				
V <sub>(BR)CES</sub>	Collector-Emitter Breakdown Voltage	$I_{\rm C} = -100 \mu A, I_{\rm B} = 0$	-30		V
I <sub>CBO</sub>	Collector-Cutoff Current	$V_{CB} = -30V, I_E = 0$		-100	nA
I <sub>EBO</sub>	Emitter-Cutoff Current	$V_{EB} = -10V, I_{C} = 0$		-100	nA
ON CHARAC	TERISTICS*				
h <sub>FE</sub>	DC Current Gain	$I_{C} = -10$ mA, $V_{CE} = -5.0$ V $I_{C} = -100$ mA, $V_{CE} = -5.0$ V	10,000 20,000		
V <sub>CE(sat)</sub>	Collector-Emitter Saturation Voltage	I <sub>C</sub> = -100mA, I <sub>B</sub> = -0.1mA		-1.5	V
V <sub>BE(on)</sub>	Base-Emitter On Voltage	$I_{C} = -100 \text{mA}, V_{CE} = -5.0 \text{V}$		-2.0	V
	AL CHARACTERISTICS				
f <sub>T</sub>	Current Gain - Bandwidth Product	$I_{C} = -10$ mA, $V_{CE} = -5.0$ V, f = 100MHz	125		MHz

\* Pulse Test: Pulse Width  $\leq 300 \mu \text{s},$  Duty Cycle  $\leq 2.0\%$ 


# **Typical Performance Characteristics**





© 2011 Fairchild Semiconductor Corporation MPSA64 / MMBTA64 / PZTA64 Rev. B0 www.fairchildsemi.com

MPSA64 / MMBTA64 / PZTA64 — PNP Darlington Transistor



www.fairchildsemi.com

MPSA64 / MMBTA64 / PZTA64 — PNP Darlington Transistor

#### FAIRCHILD

SEMICONDUCTOR

#### TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

2Cool™ AccuPower™ Auto-SPM™ AX-CAP™\* BitSiC<sup>®</sup> Build it Now™ CorePLUS™ CorePOWER™ CROSSVOLT™ CTL™ Current Transfer Logic™ DEUXPEED® Dual Cool™ EcoSPARK<sup>®</sup> EfficientMax™ ESBC™ R F Fairchild® Fairchild Semiconductor® FACT Quiet Series™ FACT<sup>®</sup> FAST<sup>®</sup> FastvCore™ FETBench™ FlashWriter®\*

FPS™ F-PFS™ **FRFET**® Global Power Resource<sup>SM</sup> Green FPS™ Green FPS™ e-Series™ Gmax™ GTO™ IntelliMAX™ ISOPLANAR™ Making Small Speakers Sound Louder and Better™ MegaBuck™ MICROCOUPLER™ MicroFET™ MicroPak™ MicroPak2™ MillerDrive™ MotionMax™ Motion-SPM™ mWSaver™ OptoHiT™ **OPTOLOGIC® OPTOPLANAR<sup>®</sup>** 

PDP SPM™ Power-SPM™ PowerTrench<sup>®</sup> PowerXS™ Programmable Active Droop™ OFFT QS™ Quiet Series™ RapidConfigure™ Saving our world, 1mW/W/kW at a time™ SignalWise™ SmartMax™

SMART START™

SPM®

STEALTH™

SuperFET<sup>®</sup>

SuperSOT™-3

SuperSOT™-6

SuperSOT™-8

SupreMOS<sup>®</sup>

SyncFET™

Sync-Lock™

puwer franchise TinyBoost™ TinyBuck™ TinvCalc™ TinyLogic® **TINYOPTO™** TinyPower™ TinyPWM™ TinyWire™ TranSiC TriFault Detect™ TRUECURRENT®\* μSerDes™

The Power Franchise®

UHC UniFET™

Ultra EREET™ **VCX™** VisualMax™ VoltagePlus™ XS™

\* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

#### DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN, FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

#### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
- 2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

#### ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

#### **PRODUCT STATUS DEFINITIONS**

Datasheet Identification	Product Status	Definition
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.
		Rev. 157

© Fairchild Semiconductor Corporation

www.fairchildsemi.com

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at <u>www.onsemi.com/site/pdf/Patent-Marking.pdf</u>. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor haves against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death a

#### PUBLICATION ORDERING INFORMATION

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com N. American Technical Support: 800–282–9855 Toll Free USA/Canada Europe, Middle East and Africa Technical Support: Phone: 421 33 790 2910 Japan Customer Focus Center Phone: 81–3–5817–1050 ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

© Semiconductor Components Industries, LLC

Downloaded from Arrow.com.