

NLV32-EFD type

CHARACTERISTICS SPECIFICATION TABLE

L	Q	L, Q measuring frequency	Self-resonant frequency	DC resistance	Rated current	Part No.
(μH)	Tolerance	min.	(MHz)	(MHz)min.	(Ω)max.	(mA)max.
0.12	±5%	30	25.2	500	0.22	450
0.15	±5%	30	25.2	450	0.25	450
0.18	±5%	30	25.2	400	0.28	450
0.22	±5%	30	25.2	350	0.32	450
0.27	±5%	30	25.2	320	0.36	450
0.33	±5%	30	25.2	300	0.4	450
0.39	±5%	30	25.2	250	0.45	450
0.47	±5%	30	25.2	220	0.5	450
0.56	±5%	30	25.2	180	0.55	450
0.68	±5%	30	25.2	160	0.6	450
0.82	±5%	30	25.2	140	0.65	450
1	±5%	30	7.96	120	0.7	400
1.2	±5%	30	7.96	100	0.75	390
1.5	±5%	30	7.96	85	0.85	370
1.8	±5%	30	7.96	80	0.9	350
2.2	±5%	30	7.96	75	1	320
2.7	±5%	30	7.96	70	1.1	290
3.3	±5%	30	7.96	60	1.2	260
3.9	±5%	30	7.96	55	1.3	250
4.7	±5%	30	7.96	50	1.5	220
5.6	±5%	30	7.96	45	1.6	200
6.8	±5%	30	7.96	40	1.8	180
8.2	±5%	30	7.96	35	2	170
10	±5%	30	2.52	30	2.1	150
12	±5%	30	2.52	20	2.5	140
15	±5%	30	2.52	20	2.8	130
18	±5%	30	2.52	20	3.3	120
22	±5%	30	2.52	20	3.7	110
27	±5%	30	2.52	20	5	80
33	±5%	30	2.52	17	5.6	70
39	±5%	30	2.52	16	6.4	65
47	±5%	30	2.52	15	7	60
56	±5%	30	2.52	13	8	55
68	±5%	30	2.52	12	9	50
82	±5%	30	2.52	11	10	45
100	±5%	20	0.796	10	10	40
120	±5%	20	0.796	10	11	70
150	±5%	20	0.796	8	15	65
180	±5%	20	0.796	7	17	60
220	±5%	20	0.796	7	21	50
270	±5%	20	0.796	6	28	45
330	±5%	20	0.796	5	34	40
390	±5%	20	0.796	5	36	35
470	±5%	20	0.796	4	40	25


Measurement equipment

Measurement item	Product No.	Manufacturer
L, Q	4294A+16197A 4294A+16093B	Keysight Technologies
Self-resonant frequency	E5063A	Keysight Technologies
DC resistance	AX-114N	ADEX

* Equivalent measurement equipment may be used.

NLV32-EFD type

L FREQUENCY CHARACTERISTICS




Measurement equipment

Product No.	Manufacturer
4294A	Keysight Technologies

* Equivalent measurement equipment may be used.

NLV32-EFD type

Q FREQUENCY CHARACTERISTICS



Measurement equipment

Product No.	Manufacturer
4294A	Keysight Technologies

* Equivalent measurement equipment may be used.

REMINDERS FOR USING THESE PRODUCTS

Before using these products, be sure to request the delivery specifications.

SAFETY REMINDERS

Please pay sufficient attention to the warnings for safe designing when using this products.

REMINDERS

- The storage period is less than 6 months. Be sure to follow the storage conditions (temperature: 5 to 40°C, humidity: 10 to 75% RH or less).
If the storage period elapses, the soldering of the terminal electrodes may deteriorate.
- Do not use or store in locations where there are conditions such as gas corrosion (salt, acid, alkali, etc.).
- Before soldering, be sure to preheat components.
The preheating temperature should be set so that the temperature difference between the solder temperature and chip temperature does not exceed 150°C.
- Soldering corrections after mounting should be within the range of the conditions determined in the specifications.
If overheated, a short circuit, performance deterioration, or lifespan shortening may occur.
- When embedding a printed circuit board where a chip is mounted to a set, be sure that residual stress is not given to the chip due to the overall distortion of the printed circuit board and partial distortion such as at screw tightening portions.
- Self heating (temperature increase) occurs when the power is turned ON, so the tolerance should be sufficient for the set thermal design.
- Carefully lay out the coil for the circuit board design of the non-magnetic shield type.
A malfunction may occur due to magnetic interference.
- Use a wrist band to discharge static electricity in your body through the grounding wire.
- Do not expose the products to magnets or magnetic fields.
- Do not use for a purpose outside of the contents regulated in the delivery specifications.
- The products listed on this catalog are intended for use in general electronic equipment (AV equipment, telecommunications equipment, home appliances, amusement equipment, computer equipment, personal equipment, office equipment, measurement equipment, industrial robots) under a normal operation and use condition.
The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality require a more stringent level of safety or reliability, or whose failure, malfunction or trouble could cause serious damage to society, person or property.
If you intend to use the products in the applications listed below or if you have special requirements exceeding the range or conditions set forth in the each catalog, please contact us.

- (1) Aerospace/aviation equipment
- (2) Transportation equipment (electric trains, ships, etc.)
- (3) Medical equipment
- (4) Power-generation control equipment
- (5) Atomic energy-related equipment
- (6) Seabed equipment
- (7) Transportation control equipment

- (8) Public information-processing equipment
- (9) Military equipment
- (10) Electric heating apparatus, burning equipment
- (11) Disaster prevention/crime prevention equipment
- (12) Safety equipment
- (13) Other applications that are not considered general-purpose applications

When designing your equipment even for general-purpose applications, you are kindly requested to take into consideration securing protection circuit/device or providing backup circuits in your equipment.