

SERIES

プラグ/リセ ST SMT

Plug/Receptacle Vertical SMT

Technical drawings of the vacuum furnace, including dimensions in inches:

- Top View:** Shows the overall footprint with dimensions $A \pm 0.1$, B , and E . It includes a central section labeled $[0.4] \text{ TYP.}$ and a section labeled $[0.18] X$. A vacuum area is indicated with a width of 0.17 .
- Front View:** Shows the height profile with dimensions 2.35 , 0.81 (VACUUM AREA), 0.17 , and 0.08 . It includes a section labeled $[0.18] X$ and a vacuum area width of 0.17 .
- Side View:** Shows the profile with dimensions 0.3 , 0.18 , 0.08 , and 0.66 . It includes a section labeled $[0.18] X$ and a vacuum area width of 0.17 .
- SECT. Z-Z:** A cross-section showing the internal structure with dimensions 1.55 , 0.33 ± 0.08 (GAP), 0.81 (VACUUM AREA), 0.23 , and 0.47 .
- SECT. S-S:** A cross-section showing the internal structure with dimensions 2.35 , 1.75 , 0.3 , and 0.08 .
- SECT. R-R:** A cross-section showing the internal structure with dimensions 2.5 and 0.08 .

NO. OF POS.	A	B	C	E
10	1.6	3.76	4.6	3.2
12	2.0	4.16	5.0	3.6
14	2.4	4.56	5.4	4.0
16	2.8	4.96	5.8	4.4
18	3.2	5.36	6.2	4.8
20	3.6	5.76	6.6	5.2
22	4.0	6.16	7.0	5.6
24	4.4	6.56	7.4	6.0
26	4.8	6.96	7.8	6.4
30	5.6	7.76	8.6	7.2
32	6.0	7.06	9.0	7.6
34	6.4	8.56	9.4	8.0
40	7.6	9.76	10.6	9.2
44	8.4	10.56	11.4	10.0
50	9.6	11.76	12.6	11.2
54	10.4	12.56	13.4	12.0
60	11.6	13.76	14.6	13.2

傳 數 NO. OF POS.	P	Q
10	5.5	12.0
12	5.5	12.0
14	7.5	16.0
16	7.5	16.0
18	7.5	16.0
20	7.5	16.0
22	7.5	16.0
24	7.5	16.0
26	7.5	16.0
30	7.5	16.0
32	7.5	16.0
34	11.5	24.0
40	11.5	24.0
44	11.5	24.0
50	11.5	24.0
54	11.5	24.0
60	11.5	24.0

14 5802 0XX 002 829 X+

極数 Number of positions

RoHS Compliant Product

無し : 16 ~ 32 Positions
K : 34 ~ 60 Positions

注) 生産可能極数については営業部にご確認願います。
Note) Feel free to contact our sales department
for available numbers of positions.

梱包数量：2000個/リール
PACKING QUANTITY：2000/Reel

Technical drawing of a mechanical part, likely a valve or actuator, showing multiple views: front, side, and cross-sections. The drawing includes dimensions in millimeters (mm) and inches (in). Key dimensions include: overall length 1.5, width 0.52, height 1.67, and various internal features like holes and grooves. The drawing is labeled with 'A0.1', 'E', and 'F'.

No. of Pos.	A	C	E
10	1.6	4.6	3.6
12	2.0	5.0	4.0
14	2.4	5.4	4.4
16	2.8	5.8	4.8
18	3.2	6.2	5.2
20	3.6	6.6	5.6
22	4.0	7.0	6.0
24	4.4	7.4	6.4
26	4.8	7.8	6.8
30	5.6	8.6	7.6
32	6.0	9.0	8.0
34	6.4	9.4	8.4
40	7.6	10.6	9.6
44	8.4	11.4	10.4
50	9.6	12.6	11.6
54	10.4	13.4	12.4
60	11.6	14.6	13.6

番 號 NO. OF POS.	P	Q
10	5.5	12.0
12	5.5	12.0
14	7.5	16.0
16	7.5	16.0
18	7.5	16.0
20	7.5	16.0
22	7.5	16.0
24	7.5	16.0
26	7.5	16.0
30	7.5	16.0
32	7.5	16.0
34	11.5	24.0
40	11.5	24.0
44	11.5	24.0
50	11.5	24.0
54	11.5	24.0
60	11.5	24.0

24 5802 0XX 002 829 S+

極数 Number of positions

RoHS Compliant Product

注) 生産可能極数については営業部にご確認願います。
Note) Feel free to contact our sales department
for available numbers of positions.

梱包数量：3000個/リール
PACKING QUANTITY：3000/Reel