

CASE SIZE & PERMISSIBLE RIPPLE CURRENT OF STANDARD PRODUCTS

D x L: mm

CAP. RATED VOLTAGE WV (SURGE VOLTAGE WV)

(μF)	4 (5)			6.3 (8)			10 (13)			16 (20)		
	SIZE	RIPPLE CURRENT	DISSIPATION FACTOR	SIZE	RIPPLE CURRENT	DISSIPATION FACTOR	SIZE	RIPPLE CURRENT	DISSIPATION FACTOR	SIZE	RIPPLE CURRENT	DISSIPATION FACTOR
4.7										4 x 5.4	20	0.16
10							4 x 5.4	14	0.30	4 x 5.4	28	0.16
22	4 x 5.4	19	0.35	4 x 5.4	20	0.26	4 x 5.4	28	0.30	4 x 5.4	27	0.26
										5 x 5.4	39	0.16
33	4 x 5.4	26	0.35	5 x 5.4	22	0.26	4 x 5.4	29	0.30	5 x 5.4	45	0.26
							5 x 5.4	43	0.20	6.3 x 5.4	66	0.16
47	4 x 5.4	34	0.35	4 x 5.4	38	0.26	5 x 5.4	43	0.30	6.3 x 5.4	70	0.16
				5 x 5.4	46	0.26	6.3 x 5.4	46	0.30	6.3 x 7.7	75	0.18
100	5 x 5.4	61	0.35	6.3 x 5.4	71	0.26	5 x 5.4	60	0.30	6.3 x 5.4	70	0.20
							6.3 x 5.4	70	0.26	6.3 x 7.7	85	0.20
										8 x 6.5	86	0.20
220	6.3 x 5.4	82	0.35	6.3 x 5.4	190	0.26	6.3 x 7.7	105	0.26	6.3 x 7.7	105	0.20
				6.3 x 7.7	235	0.35	8 x 6.5	250	0.26	8 x 10.5	280	0.20
				8 x 6.5	250	0.35						
330				6.3 x 7.7	280	0.35	8 x 10.5	330	0.26	8 x 10.5	316	0.20
				8 x 6.5	300	0.35				10 x 10.5	380	0.20
				8 x 10.5	340	0.35						
470				8 x 10.5	380	0.35	8 x 10.5	330	0.26	8 x 10.5	350	0.20
							10 x 10.5	400	0.26	10 x 10.5	420	0.20
1000				8 x 10.5	580	0.35	10 x 10.5	580	0.26			
				10 x 10.5	700	0.35						
1500				10 x 10.5	1000	0.35						

Note: 1. Ripple Current: (mA/rms) 85°C, 120Hz

2. Dissipation Factor: 20°C, 120Hz



CASE SIZE & PERMISSIBLE RIPPLE CURRENT OF STANDARD PRODUCTS

D × L: mm

CAP. (μF)	RATED VOLTAGE WV (SURGE VOLTAGE WV)								
	25 (32) SIZE	RIPPLE CURRENT	DISSIPATION FACTOR	35 (44) SIZE	RIPPLE CURRENT	DISSIPATION FACTOR	50 (63) SIZE	RIPPLE CURRENT	DISSIPATION FACTOR
0.10							4 × 5.4	1	0.12
0.22							4 × 5.4	2	0.12
0.33							4 × 5.4	3	0.12
0.47							4 × 5.4	5	0.12
1.0							4 × 5.4	10	0.12
2.2				4 × 5.4	8	0.12	4 × 5.4	16	0.12
3.3				4 × 5.4	10	0.12	4 × 5.4	16	0.12
4.7	4 × 5.4	22	0.14	4 × 5.4	22	0.12	5 × 5.4	23	0.12
10	4 × 5.4	24	0.20	4 × 5.4	24	0.16	5 × 5.4	28	0.12
	5 × 5.4	28	0.14	5 × 5.4	30	0.12	6.3 × 5.4	35	0.12
22	5 × 5.4	45	0.14	5 × 5.4	49	0.23	6.3 × 5.4	70	0.12
	6.3 × 5.4	55	0.14	6.3 × 5.4	60	0.12	6.3 × 7.7	90	0.12
							8 × 6.5	110	0.12
33	5 × 5.4	53	0.14	6.3 × 5.4	100	0.14	6.3 × 7.7	90	0.12
	6.3 × 5.4	65	0.14	8 × 6.5	130	0.14	8 × 10.5	120	0.12
47	6.3 × 5.4	70	0.20	6.3 × 7.7	150	0.14	6.3 × 7.7	63	0.12
	8 × 6.5	96	0.16	8 × 6.5	165	0.14	8 × 10.5	100	0.12
							10 × 10.5	130	0.12
100	6.3 × 7.7	115	0.16	6.3 × 7.7	140	0.14	8 × 10.5	160	0.12
	8 × 6.5	140	0.16	8 × 6.5	170	0.14	10 × 10.5	190	0.12
	8 × 10.5	180	0.16	10 × 10.5	210	0.14			
220	8 × 6.5	210	0.16	8 × 10.5	250	0.14	10 × 10.5	310	0.12
	8 × 10.5	260	0.16	10 × 10.5	310	0.14			
	10 × 10.5	310	0.16						
330	8 × 10.5	350	0.16	10 × 10.5	400	0.14			
	10 × 10.5	430	0.16						
470	10 × 10.5	480	0.16						

Note: 1. Ripple Current: (mA/rms) 85°C, 120Hz

2. Dissipation Factor: 20°C, 120Hz

CASE SIZE & PERMISSIBLE RIPPLE CURRENT OF STANDARD PRODUCTS

D × L: mm

CAP. (μF)	RATED VOLTAGE WV (SURGE VOLTAGE WV)					
	63 (79) SIZE	RIPPLE CURRENT	DISSIPATION FACTOR	100 (125) SIZE	RIPPLE CURRENT	DISSIPATION FACTOR
3.3				8 × 10.5	30	0.18
4.7	6.3 × 5.4	20	0.18	8 × 10.5	50	0.18
10	6.3 × 5.4	20	0.18	8 × 10.5	55	0.18
22	8 × 10.5	30	0.18	10 × 10.5	60	0.18
33	8 × 10.5	30	0.18	10 × 10.5	65	0.18
47	8 × 10.5	30	0.18			
100	10 × 10.5	60	0.18			

Note: 1. Ripple Current: (mA/rms) 85°C, 120Hz

2. Dissipation Factor: 20°C, 120Hz