

Electrical characteristics

Amp Rating	% of Amp Rating	Opening Time
750mA-20A	100%	4 Hours, min
1-3A	200%	1-60 Seconds
1-5A	250%	5 Seconds, max
1-5A	300%	0.1-3 Seconds
750mA, 6-20A	350%	5 Seconds, max
750mA-20A	1000%	0.2-20mS

Specifications

Catalog Symbol	Current Rating (amps)	Voltage Rating (Vdc)	Interrupting Rating* (amps)	Resistance (Ω)** Typical	Typical Melt (I ² t)† DC	Typical Voltage Drop (mV)‡	Alpha Marking
CC12H750mA	0.75	63	50	0.780	0.15	840	E
CC12H1A	1	63	50	0.470	0.18	490	H
CC12H1.5A	1.5	63	50	0.218	0.4	355	K
CC12H2A	2	63	50	0.133	1.1	305	N
CC12H2.5A	2.5	63	50	0.079	1.7	240	O
CC12H3A	3	63	50	0.049	2.2	185	P
CC12H3.5A	3.5	63	50	0.037	2.7	180	R
CC12H4A	4	63	50	0.033	3.2	169	S
CC12H4.5A	4.5	32	100	0.028	4.2	160	X
CC12H5A	5	32	100	0.023	6.0	140	T
CC12H6A	6	32	100	0.0155	8.0	140	F
CC12H7A	7	32	100	0.011	9.0	120	J
CC12H8A	8	32	100	0.007	12.0	80	M
CC12H10A	10	32	100	0.0065	33	90	U
CC12H12A	12	32	100	0.0045	45	80	W
CC12H15A	15	32	100	0.0030	40	70	Y
CC12H20A	20	32	100	0.0020	50	60	Q

* DC Interrupting Rating (Measured at rated voltage, time constant of less than 50 microseconds, battery source)

** DC Cold Resistance (Measured at 10% of rated current)


† Typical Melting I²t (Measured with a battery bank at rated DC voltage, 10x-rated current, not to exceed interrupting rating, time constant of calibrated circuit less than 50 microseconds)

‡ Typical Voltage Drop (Measured at rated current after temperature stabilizes)


Device designed to carry rated current for four hours minimum. An operating current of 80% or less of rated current is recommended, with further derating required at elevated ambient temperatures.

Dimensions - mm (in)

Drawing not to scale.



Pad layout




Environmental data

- Thermal Shock: MIL-STD-202, Method 107, Test Condition B
- Vibration: MIL-STD-202, Method 204, Test Condition C
- Moisture Resistance: MIL-STD-202, Method 106, 50 day cycle
- Solderability: ANSI/J-STD-002, Test B
- Normal ambient temperature: 23°C
- Operating temperature range -40°C to +125°C


Soldering method

- Wave Solder Immersion: 260°C, 10 seconds maximum.
- Solder Reflow: 260°C, 30 seconds maximum.


Time-current curves — 750mA-5A average melt




Time-current curves — 6A-20A average melt




I²t vs. time curves — 750mA-5A




I²t vs. time curves — 6A-20A



I²t vs. current curves — 750mA-5A



I²t vs. current curves — 6A-20A



Solder reflow profile




Table 1 - Standard SnPb Solder (T_C)

Package Thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5mm	235°C	220°C
≥2.5mm	220°C	220°C

Table 2 - Lead (Pb) Free Solder (T_C)

Package Thickness	Volume mm ³ <350	Volume mm ³ 350 - 2000	Volume mm ³ >2000
<1.6mm	260°C	260°C	260°C
1.6 - 2.5mm	260°C	250°C	245°C
>2.5mm	250°C	245°C	245°C

Reference JEDEC J-STD-020D

Profile Feature	Standard SnPb Solder	Lead (Pb) Free Solder
Preheat and Soak		
• Temperature min. (T_{smin})	100°C	150°C
• Temperature max. (T_{smax})	150°C	200°C
• Time (T_{smin} to T_{smax}) (t_s)	60-120 Seconds	60-120 Seconds
Average ramp up rate T_{smax} to T_P	3°C/ Second Max.	3°C/ Second Max.
Liquidous temperature (T_L)	183°C	217°C
Time at liquidous (t_L)	60-150 Seconds	60-150 Seconds
Peak package body temperature (T_P)*	Table 1	Table 2
Time (t_p)** within 5 °C of the specified classification temperature (T_C)	20 Seconds**	30 Seconds**
Average ramp-down rate (T_P to T_{smax})	6°C/ Second Max.	6°C/ Second Max.
Time 25°C to Peak Temperature	6 Minutes Max.	8 Minutes Max.

* Tolerance for peak profile temperature (T_P) is defined as a supplier minimum and a user maximum.

** Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.

North America

Eaton's Electrical Group
Electronics Division
1225 Broken Sound Parkway NW
Suite F
Boca Raton, FL 33487-3533
Tel: 1-561-998-4100
Fax: 1-561-241-6640
Toll Free: 1-888-414-2645

Eaton's Electrical Group
Electronics Division
P.O. Box 14460
St. Louis, MO 63178-4460
Tel: 1-636-394-2877
Fax: 1-636-527-1607

Europe

Eaton's Electrical Group
Electronics Division
Burton-on-the-Wolds
Leicestershire, LE 12 5th UK
Phone: +44 (0) 1509 882 600
Fax: +44 (0) 1509 882 786

Eaton's Electrical Group
Electronics Division
Avda Santa Eulalia, 290
Terrassa, Barcelona 08223 Spain
Phone: +34-93-736-2813
Fax: +34-93-783-5055

Asia Pacific

Eaton's Electrical Group
Electronics Division
No.2, #06-01
Serangoon North Avenue 5
Singapore 554911
Tel: +65 6645 9888
Fax: +65 6728 3155

The only controlled copy of this Data Sheet is the electronic read-only version located on the Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Life Support Policy: Bussmann does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton's Electrical Group
Electronics Division
114 Old State Road
Ellisville, MO 63021
United States
www.eaton.com/elx

© 2014 Eaton
All Rights Reserved
Publication No. 4309 — BU-SB14479
July 2014

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

www.eaton.com/elx