


ELECTRICAL SPECIFICATIONS (at 25°C unless noted)

Characteristics	Forward Voltage	Forward Voltage	Forward Voltage	Forward Voltage	Forward Voltage	Reverse Breakdown Voltage
Conditions	V_{F1} $I_F = 1 \text{ mAdc}$	V_{F2} $I_F = 10 \text{ mAdc}$	V_{F3} $I_F = 50 \text{ mAdc}$ (pulse)	V_{F4} $I_F = 100 \text{ mAdc}$ (pulse)	V_{F5} $I_F = 200 \text{ mAdc}$ (pulse)	BV $I_R = 5.0 \text{ } \mu\text{Adc}$
Minimum	0.540 Vdc	0.660 Vdc	0.760 Vdc	0.820 Vdc	0.870 Vdc	7.5 Vdc
Maximum	0.620 Vdc	0.740 Vdc	0.860 Vdc	0.920 Vdc	1.00 Vdc	—

Characteristics	Reverse Current	Reverse Current	Junction Capacitance	Reverse Recovery Time	Reverse Recovery Time	Forward Recovery Time
Conditions	I_R $V_R = 50 \text{ Vdc}$	I_R $V_R = 50 \text{ Vdc}$ $T_A = 150^\circ\text{C}$	C $V_R = 0$ $F = 1 \text{ MHz}$ $V_{sig} = 50 \text{ mv (p-p)}$	t_{rr1} $I_F = I_R =$ 10 to 200 mAdc; $R_L = 100 \text{ ohms}$	t_{rr2} $I_F = I_R =$ 200 to 400 mAdc; $R_L = 100 \text{ ohms}$	t_{fr} $I_F = 200 \text{ mAdc};$ $t_p = 100 \text{ nsec};$ $t_r = 0.4 \text{ nsec}$
Maximum	0.1 μAdc	100 μAdc	2.5 pf	4 nsec	6 nsec	10 nsec

Typical Forward Current vs Voltage



Reverse Voltage vs. Reverse Current

