



# NPC-1210 Series Specifications

## Medium Pressure Sensors

### Pressure Ranges

- Gauge and Differential:
  - 5 psi (34 kPa, 0.34 bar)
  - 15 psi (100 kPa, 1.0 bar)
  - 30 psi (210 kPa, 2.1 bar)
  - 50 psi (340 kPa, 3.4 bar)
  - 100 psi (690 kPa, 6.9 bar)
- Absolute:
  - 15 psi (100 kPa, 1.0 bar)
  - 30 psi (210 kPa, 2.1 bar)
  - 50 psi (340 kPa, 3.4 bar)
  - 100 psi (690 kPa, 6.9 bar)
- For other pressure ranges, please contact NovaSensor.

Parameter	Value	Units	Notes		
Environmental					
Temperature Range					
Operating	-40 to 125	°C	(-40° to 257°F)		
Compensated	0 to 60	°C	(32°F to 140°F)		
Storage	-55 to 150	°C	(-67 to 302 °F)		
Mechanical					
Weight	2.5	g	(0.005 lb)		
Media Compatibility	Compatible with exposed materials		7		
Positive differential and gauge ports	Dry gases only				
Absolute and negative differential ports	Dry gases only				
Parameter	Units	Minimum	Typical	Maximum	Notes
Performance Parameters *					
FS Output (FSO)	mV	75	100	150	2, 3
Zero Pressure Output	mV	-2	—	2	3
Linearity	%FSO	-0.1	—	0.1	4, 8
Pressure Hysteresis	%FSO	-0.1	—	0.1	
Input Impedance	Ω	2500	4000	6000	
Output Impedance	Ω	4000	5000	6000	
Thermal Accuracy–Span	%FSO	-0.5	—	0.5	3, 5, 8
Thermal Accuracy–Zero	%FSO	-0.5	—	0.5	3, 5, 8
Temperature Coefficient–Resistance	%/°C	—	0.2	—	5
Thermal Hysteresis–Zero	%FSO	—	0.1	—	5
Input Excitation	mA	—	1.5	2.0	
Pressure Overload	Rated	—	—	3X	6, 9

## Low Pressure Sensors

### Pressure Ranges

- Gauge and Differential:
  - 10 in H<sub>2</sub>O (2.5 kPa, 0.025 bar)
  - 1 psi (6.9 kPa, 0.069 bar)

Parameter	Value	Units	Notes		
Environmental					
Temperature Range					
Operating	−40 to 125	°C	(−40° to 257°F)		
Compensated	0 to 60	°C	(32°F to 140°F)		
Storage	−55 to 150	°C	(−67 to 302 °F)		
Mechanical					
Weight	2.5	g	(0.005 lb)		
Media Compatibility	Compatible with exposed materials		7		
Positive differential and gauge ports	Dry gases only				
Absolute and negative differential ports	Dry gases only				
Performance Parameters *					
FSO 10 inH <sub>2</sub> O	mV	25	50	70	2, 3
FSO 1 psi	mV	50	75	110	2, 3
Zero Pressure Output	mV	-2	—	2	3
Linearity	%FSO	-0.5	—	0.5	4
Pressure Hysteresis	%FSO	-0.1	—	0.1	
Input Impedance	Ω	2500	4000	6000	
Output Impedance	Ω	4000	5000	6000	
Thermal Accuracy—Span	%FSO	-1.0	—	1.0	3, 5
Thermal Accuracy—Zero	%FSO	-1.25	—	1.25	3, 5
Temperature Coefficient—Resistance	%/°C	—	0.22	—	5
Thermal Hysteresis—Zero	%FSO	—	0.1	—	5
Input Excitation	mA	—	1.5	2.0	
Pressure Overload	psi (bar)	5 (0.34)	—	—	—

1. \*Supply current = 1.5 mA and ambient temperature = 77°F (25°C), unless otherwise noted. Gauge and differential pressure devices are calibrated by applying pressure to the positive differential port (P2) and venting to atmosphere the reference port (P1).
2. Output span of unamplified sensor.
3. Compensation resistors are an integral part of the sensor package; no additional external resistors are required. Pins 7 and 8 must be kept open. The NPC-1210 is interchangeable only when used with the gain set resistor shown in the schematic diagram. Maximum gain-set resistor mismatch is 2%.
4. Best fit straight line.
5. Temperature range 32°F to 140°F (0°C to 60°C), reference to 77°F (25°C).
6. 3X or 200 psi (13.78 bar) maximum, whichever is less.
7. Exposed materials are pyrex, ceramic, silicon, epoxy, RTV, and stainless steel.
8. 5 psi (0.34 bar) spec.: Linearity: 0.25 ±%FSO, TC-span: 0.75 ±%FSO, TC-zero: 0.75 ±%FSO, otherwise noted.
9. Port 1 is limited to 60 PSIG for differential and absolute pressure sensors. Contact factory for 50 PSIA/D and 100 PSIA/D units.

# NPC-1210 Series Specifications

## Ordering Information

The code number to be ordered may be specified as follows:

### NPC-1210 (Medium Pressure)

Code	Pressure Range	Code	Type	Code	Lead Configurations	Code	Tube Options
005	5 psi (0.3 bar)	D	Differential	1	Up	L	Long
015	15 psi (1 bar)	A	Absolute	3	Down	S	Short
030	30 psi (2 bar)	G	Gauge			N	None *
050	50 psi (3.4 bar)						
100	100 psi (7 bar)						

NPC-1210 - \_ - \_ - \_ Typical model number

\* Order NPC-1210-XXXG-XN in place of NPC-1210-XXXD-XN

The code number to be ordered may be specified as follows:

### NPC-1210 (Low Pressure)

Code	Pressure Range	Code	Type	Code	Lead Configurations	Code	Tube Options
10W	10 in H <sub>2</sub> O (25 mbar)	D	Differential	1	Up	L	Long
001	1 psi (69 mbar)	G	Gauge	3	Down	S	Short

NPC-1210 - \_ - \_ - \_ Typical model number

## Warranty

Amphenol Advanced Sensors warrants its products against defects in material and workmanship for 12 months from the date of shipment. Products not subjected to misuse will be repaired or replaced. Amphenol Advanced Sensors reserves the right to make changes without further notice to any products herein. NovaSensor makes no warranty, representation or guarantee regarding the suitability of its products for any particular application, nor does Amphenol Advanced Sensors assume any liability arising out of the application or use of any product or circuit and specifically disclaims and all liability without limitation consequential or incidental damages. The foregoing warranties are exclusive and in lieu of all other warranties, whether written, oral, implied or statutory. No implied statutory warranty of merchantability or fitness for particular purpose shall apply.

**Amphenol**  
Advanced Sensors

[www.amphenol-sensors.com](http://www.amphenol-sensors.com)

© 2021 Amphenol Corporation. All Rights Reserved. Specifications are subject to change without notice.  
Other company names and product names used in this document are the registered trademarks or trademarks of their respective owners.

AAS-920-303F - 09/2021