

Overview

Disclaimer

While Tyco Electronics Corporation and its affiliates referenced herein ("Tyco Electronics") have made every reasonable effort to ensure the accuracy of the information in this catalog, Tyco Electronics does not guarantee that it is error-free, nor does Tyco Electronics make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current.

Tyco Electronics reserves the right to make any adjustments to the information contained herein at any time without notice. Tyco Electronics expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. Tyco Electronics' only obligations are those in the Tyco Electronics Standard Terms and Conditions of Sale, and in no case will Tyco Electronics be responsible for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of its products. Users should independently evaluate the suitability of, and test each product for, their application.

The dimensions, specifications, designs, construction, materials and processes in this catalog are for reference purposes only and are subject to change without notice. Please consult Tyco Electronics for the most current product information.

The export of certain Tyco Electronics products is restricted by the Arms Export Control Act (Title 22, U.S.C. Sec 2751, et seq.) or the Export Administration Act of 1979, as amended (Title 50, U.S.C., App. 2401 et seq.). Orders may be subject to export approval by the U.S. Government. Buyer must comply with all applicable export laws of all applicable jurisdictions. © 1998, 2002, 2004 and 2007 by Tyco Electronics Corporation. All Rights Reserved.

AMP, AMP-O-ELECTRIC, AMP-O-MATIC, AMPLIMITE, the TE Logo and TYCO ELECTRONICS are trademarks.

Other products, logos, and company names mentioned herein may be trademarks of their respective owners.

See inside back cover for Global Contacts and phone numbers.

Product Facts

- Connector system designed for exclusive use with I/O and power circuits in the power and control boards of heavy electric systems and FA equipment, process computers, FA computers, PCs, NCs, servodrivers, servomotors, inverters, switching power supplies, etc.
- Consists of wire-side connector and board-side connector
- Diverse housings are available to meet most specific applications
- With contacts standardized, the tool types used can be reduced
- Termination can be automated and field maintenance simplified
- As contacts can be crimped, connector quality is maintained
- Standardization of contacts leads to easier management of inventory
- To help prevent human errors in termination a common identification mark is on hand tools and contacts
- Housing color and design are coordinated

Need more information?

Call Technical Support at the numbers listed below.

Technical Support is staffed with specialists well versed in Tyco Electronics products. They can provide you with:

- Technical Support
- Catalogs
- Technical Documents
- Product Samples
- Tyco Electronics Authorized Distributor Locations

Restriction on the use of Hazardous Substances (RoHS)

At Tyco Electronics, we're ready to support your RoHS requirements. We've assessed more than 1.5 million end items/components for RoHS compliance, and issued new part numbers where any change was required to eliminate the restricted materials. Part numbers in this catalog are identified as:

RoHS Compliant — Part numbers in this catalog are RoHS Compliant, unless marked otherwise. These products comply with European Union Directive 2002/95/EC as amended 1 January 2006 that restricts the use of lead, mercury, cadmium, hexavalent chromium, PBB, and PBDE in certain electrical and electronic products sold into the EU as of 1 July 2006.

NOTE: For purposes of this Catalog, included within the definition of RoHS Compliant are products that are clearly "Out of Scope" of the RoHS Directive such as hand tools and other non-electrical accessories.

NOTE: Information regarding RoHS compliance is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information provided by our suppliers. This information is subject to change. For latest compliance status, refer to our website referenced at right.

Getting the Information You Need

Our comprehensive on-line RoHS Customer Support Center provides a forum to answer your questions and support your RoHS needs. A RoHS FAQ (Frequently Asked Questions) is available with links to more detailed information. You can also submit RoHS questions and receive a response within 24 hours during a normal work week. The Support Center also provides:

- Cross-Reference from Non-compliant to Compliant Products
- Ability to browse RoHS Compliant Products in our on-line catalog
- Downloadable Technical Data Customer Information Presentation
- More detailed information regarding the definitions used above
- So whatever your questions when it comes to RoHS, we've got the answers at www.tycoelectronics.com/leadfree



Note: Connectors are not designed to mate and unmate on energized line.

Table of Contents

Product Facts 2

Table of Contents 3-5

D-1000 Series

Introduction and Product Facts6

D-1 Contacts (Strip and Loose Piece), Application Tooling,
Performance Characteristics and Technical Documents7

D-1100D — 2-Row Type

Dimensions (Mating and External), Receptacle & Tab Housings and
Board-mounting Tab Headers (Horizontal and Vertical) 8, 9

D-1200S

Dimensions (Mating and External), 2-Pos. Receptacle & Tab Housings and
Board-mounting Tab Header (Vertical) 10, 11

D-1200D — 2-Row Type

Dimensions (Mating and External), Receptacle & Tab Housings and
Board-mounting Tab Headers (Horizontal and Vertical) 12, 13

D-1500T

Dimensions (Mating and External), 3-Pos. Receptacle Housing and
Board-mounting Tab Headers (Horizontal and Vertical) 14, 15

D-2000 Series

List of Products by Application (D-2100S, D-2100D and D-2100M) 16

Performance Specifications 17, 18

D-2 Contacts (Strip and Loose Piece) and Application Tooling 19

D-2100S — 1-Row Type

Typical Applications, Mating Combinations and 3-Pos. Housings & Headers 20

Keying 21

Dimensions (Mating and External), 3-Pos. Receptacle & Tab Housings and
3-Pos. Board-mounting Tab Headers (Vertical and Horizontal) 22, 23

D-2100D — 2-Row Type

Typical Applications, Mating Combinations and Housings & Headers 24

Keying 25

Dimensions (Mating and External), Receptacle & Tab Housings and
Board-mounting Tab Headers (Vertical and Horizontal) 26, 27

D-2100M

Drawer Type

Typical Applications and 50-Pos. Receptacle & Tab Housings 28

Dimensions (Mating and External), 50-Pos. Receptacle & Tab Housings 29

50-Pos. Board-mounting Tab Header (Horizontal) 30

Panel Mounting Screws (for 50-Pos. Receptacle & Tab Housings) 30

Screw Lock Type

50-Pos. Receptacle and Tab Assemblies (with Screws) 31

D-2600 — Combination Power & Signal

Introduction, Performance Characteristics and Technical Documents 32

Dimensions (Mating and External), 48-Pos. Receptacle Housing and
Board-mounting Tab Header (Vertical) 33

D-3000 Series

List of Products by Application

D-3100S, D-3100M and D-3100D 34

D-3200S, D-3200M and D-3200T; D-3400F and D-3500D 35

Performance Specifications 36, 37

D-3 Contacts (Strip and Loose Piece) 38

Application Tooling (Hand Tools and Machines) 38-41

Keying Plug 41

Connector Panel-Mounting Hardware (L Fittings and Push Rivets) 42

Table of Contents (Continued)

D-3100S

Standard 1-Row Type

Typical Applications, Mating Combinations and Ordering Information 43

Keying and Typical Applications (Elevators) 44

Dimensions (Mating and External), Receptacle & Tab Housings and
Board-mounting Tab Headers (Horizontal and Vertical) 45, 46

Standard SMT Type

Mating Combinations and Ordering Information 47

Dimensions (Mating and External), Receptacle Housings and
Board-mounting Tab Headers (Horizontal and Vertical) 47, 48

D-3100D — Standard 2-Row Type

Typical Applications, Mating Combinations and Ordering Information 49

Dimensions (Mating and External), Receptacle & Tab Housings and
Board-mounting Tab Headers (Horizontal and Vertical) 50, 51

D-3100M — Modular Type

Typical Applications and 6-Pos. Receptacle Housings & Tab Headers 52

Keying and Mating Combinations 53

Dimensions (Mating and External), 6-Pos. Receptacle Housing and
6-Pos. Board-mounting Tab Headers (Horizontal and Vertical) 54, 55

D-3200S

High Voltage Version of Standard D-3100S

Typical Applications, Mating Combinations and Ordering Information 56

Keying and Typical Application (Switching Regulator) 57

Dimensions (Mating and External), Receptacle & Tab Housings and
Board-mounting Tab Headers (Horizontal and Vertical) 58, 59

SMT Type

Typical Applications and Receptacle Housings & 3-Pos. Tab Header 60

Dimensions (Mating and External), 3-Pos. Board-mounting Tab Header 61

D-3200M

Modular Type

Typical Applications and Ordering Information 62

Keying and Mating Combinations 63

Dimensions (Mating and External), Receptacle & Tab Housings and
Board-mounting Tab Headers (Horizontal and Vertical) 64, 65

Drawer Type

Typical Applications, Mating Combinations and Ordering Information 66

Dimensions (Mating and External), 6-Pos. Receptacle & Tab Housings and
6-Pos. Board-mounting Tab Headers (Horizontal and Vertical) 67, 68

D-3200T — 3-Row Type

Typical Application and 9-Pos. Board-mounting Tab Headers,
Dimensions (Mating and External) and Keying 69

D-3400F — Skyscraper Connectors

Typical Applications, Mating Combinations and Ordering Information 70

Dimensions (Mating and External), Receptacle Housings and
Board-mounting Tab Headers (Horizontal) 71, 72

D-3500D — Sensor Connectors

Typical Applications, Mating Combinations and Ordering Information 73

Dimensions (Mating and External), Receptacle & Tab Housings and
Board-mounting Tab Headers (Horizontal and Vertical) 74, 75

D-3700 — Connectors for Exclusive Use with Servomotors

Typical Applications, 6-Pos. Receptacle Connector Kits 76

Dimensions (Mating and External) and Optional Motor-side Tab Header 77

Table of Contents (Continued)

D-4000 Series

Introduction, Product Facts, Performance Characteristics and
D-4 Contacts (Strip and Loose Piece) and Application Tooling 78

D-4200

Dimensions (Mating and External), Receptacle & Tab Housings and
Board-mounting Tab Headers (Vertical) 79, 80

D-5200 Series

List of Products by Application (D-5200S and D-5200M) 81
Performance Data and Specifications 82, 83
D-5 Contacts (Strip and Loose Piece) and Sequential Clip 84
Application Tooling (Extraction Tool, Hand Crimping Tool and Machine) 84, 85

D-5200S — Standard 1-Row Type

Typical Applications, Mating Combinations and Ordering Information 86
Keying and Servomotor/Servodriver Application 87
Dimensions (Mating and External), Receptacle & Tab Housings and
Board-mounting Tab Headers (Horizontal, Vertical and Sequential) 88, 89

D-5200M — Modular Type

Typical Applications and Ordering Information 90
Keying and Mating Combinations 91
Dimensions (Mating and External), 4- and 6-Pos. Receptacle & Tab Housings and
4- and 8-Pos. Board-mount Tab Headers (Horizontal) 92, 93

D-5200Mα — High Current Type

Typical Applications, Mating Combinations, Ordering Information and Keying 94
Dimensions (Mating and External), Receptacle Housings and
Board-mounting Tab Header (Horizontal) 95, 96

DZ-5200 — Board-to-Board

Performance Characteristics, External Dimensions, and
Receptacle Header (Vertical) 97
Tab Header (Horizontal) 98

D-5300 — Panel Mount Type

Introduction and Performance Characteristics 99
Dimensions (Mating and External), Panel Mount Receptacle & Tab Housing 100

AMP Dynamic with HTS Connectors

Introduction, Performance Characteristics and Contacts (D-2 and D-3) 101
D-2800, 30-Pos. Receptacle & Tab Housings 102
D-3800, 12-Pos. Receptacle & Tab Housings 102
HTS Modular Frames and Metal Housings (Sizes 3, 4, 6 and 8) 104
HTS Cable Gland Fittings (Plastic and Metal) 105

Power Connector — Board-to-Board

Specifications, Typical Applications and Ordering Information 106
Dimensions (Mating and External) 107

Dyna-Tap Connectors

D-3100, 18-Pos. Introduction, Applications and Performance Characteristics 108
Dimensions (Mating and External), 18-Pos. Tab Housing and
6-Pos. Receptacle Housing 109
D-3200, 24-Pos. Introduction and Performance Characteristics 110
Dimensions (Mating and External), 24-Pos. Tab Housing and
4-Pos. Receptacle Housing 111

Dyna-Clamp Kit

Introduction, Applications and Performance Characteristics 112
Dimensions (Mating and External), 3-Pos. Cable Clamp Kit and Mating Connectors .. 113

Part Number Index114, 115

Global Contacts119


D-1000 Series (Wire-to-Board, Wire-to-Panel and Wire-to-Wire)

Product Facts


- Header and tab connectors have enough length from the tip of contact to top of housing to help prevent contact from bending when receptacle mates to tab connector.
- D-1000 has housing lance structure. Without contact lance, it is expected to avoid contact lance broken in terminal process handling
- Clear identification of circuit number provides for correct wiring
- Metal retention leg assembly tab header helps prevent damage from unexpected cable tension
- Housing lock design



D-1100



D-1200



D-1500

D-1000 Series are the smallest connectors for signal lines in the Dynamic connector series. D-1000 Series occupies 40% less volume than the D-2000 Series, so it can contribute to customers' equipment miniaturizing requirement.

D-1000 Series receptacle and tab contacts have a wide wire range, 30 through 18 AWG with 2.2 mm wire insulation diameter maximum, which is commonly used for electrical cabinet wiring.

D-1000 Series housings consist of D-1110 Series for 2.0 mm centerline and D-1200 Series for 2.5 mm centerline as the standard type. In addition, D-1500 Series housings are for 3.5 mm centerline sensor applications or branch connection of power lines.

D-1000 Series has gold plated contacts as standard and also tin plated contacts for economical market needs. Customers have a choice of contacts depending on specifications, application, and cost.

Crimping hand tool features a changeable die set structure. It offers minimal installation tooling cost. This tooling system will evolve to D-2000, D-3000 and D-4000 Series in the future.

D-1000 Series (Continued)

D-1 Contact and
Performance Specifications

Crimp Type

Applicable Wire Range		Wire Ins. Diameter mm	Wire Range Mark	Contact Part Numbers					Tool Numbers	
				Style	Receptacle Contact		Tab Contact		Mini Applicator	Hand Tool ¹ (Dies Only)
					Gold Plating	Tin Plating	Gold Plating	Tin Plating		
30	0.05	0.6~1.2	S	Strip Form	1827569-2	—	1903111-2	—	1891033-2	—
28	0.09			Loose Piece	1827586-2	—	1903115-2	—	—	1762952-1 (1762953-1)
28	0.08	1.08~1.6	M	Strip Form	1827570-2	1871303-1	1903112-2	1903120-1	1891035-2	—
26	0.12			Loose Piece	1827587-2	1871743-1	1903116-2	1903124-1	—	1762846-1 (1762847-1)
24	0.20									
22	0.38									
28	0.08	1.08~1.9	L	Strip Form	1827571-2	1871304-1	1903113-2	1903121-1	1891036-2	—
26	0.12			Loose Piece	1827588-2	1871744-1	1903117-2	1903125-1	—	1762950-1 (1762951-1)
24	0.20									
22	0.38									
22	0.34	1.4~2.2	2L	Strip Form	1827572-2	1871731-1	1903114-2	1903122-1	1891037-2	—
20	0.50			Loose Piece	1827589-2	1871745-1	1903118-2	1903126-1	—	1762625-1 (1762626-1)
18	0.86									

Notes: Minimum order quantity for tooling is one.
Tin plating: 2.0 µm.
Mini-Applicators are for use with automachines. (For more information, contact Technical Support at the numbers listed below.
Strip Form contacts are for use with Mini-Applicators (automachines) and Loose-Piece contacts are for Hand tools.
The contacts L and 2L do **not** fit into the D-1100 receptacle housing.
¹ With handle.

Performance Characteristics

Series —	D-1100	D-1200	D-1500
Pitch —	2.0 mm	2.5 mm	3.5 mm
Voltage Rating —	125 VAC	250 VAC	250 VAC
Current Rating (Max.) —	Pos. :3A (AWG 22 wire)	Pos. :5A (AWG 18 wire)	Pos. :5A (AWG 18 wire)
Contact Resistance —	20 mΩ max.	20 mΩ max.	20 mΩ max.
Dielectric Withstanding Voltage —	700 V	1100 V	1100 V
Temperature Range —	-55°C~+105°C	-55°C~+105°C	-55°C~+105°C

*When connectors are used singly.

Material and Finish

Receptacle Contact — Copper alloy, 0.38 µm gold plated over 1.27 µm nickel underplate
Tab Contact — Copper alloy, 0.38 µm gold plated over 1.27 µm nickel underplate
PCB Tab Post — Copper alloy, 0.38 µm gold plated over 1.27 µm nickel underplate, Tab Post 2.0 µm tin plated
Housing — Glass-filled polyester (PBT), UL94V-0

Specifications and
Instruction Sheets

Product Specifications
108-78268 (Gold plating)
108-78298 (Tin plating)
Application Specification
114-5377
Crimping Tool Instruction Sheets
411-78194 (Part Number 1762625-1)
411-78201 (Part Number 1762846-1)
411-78204 (Part Number 1762950-1)
411-78205 (Part Number 1762952-1)


Safety Specifications for D-1000 Series

	Voltage Rating	Current Rating	Temperature Rating
Tyco Electronics Specifications 108-78268 —	125 VAC (2 mm)	3A (1 position)	-55°C~+105°C
	250 VAC (2.5 mm)	5A (1 position)	
	250 VAC (3.5 mm)		
UL File Number — E 28476			
CSA Report Number — Pending Approval			
TUV License Number — Pending Approval			

D-1000 Series (Continued)

D-1100D


Mating Dimensions



External Dimensions


Receptacle Housing

No. of Pos.	Color	Part No.	Dimensions	
			A	B
10	Black	1-1827862-5	12.6	10.9
20	Black	1-1827862-0	22.6	20.9
22	Black	1-1827863-1	24.6	22.9
	Yellow	3-1871057-1		
26	Black	1-1827863-3	28.6	26.9
	Natural	1-1871057-3		
28	Black	1-1827863-4	30.6	28.9
30	Black	1-1827863-5	32.6	30.9
	Natural	1-1871057-5		
	Yellow	3-1871057-5		
32	Black	1-1827863-6	34.6	32.9
34	Black	1-1827863-7	36.6	34.9
40	Black	1-1827863-0	42.6	40.9



Tab Housing

Panel Mount Type/
Free Hanging Type




No. of Pos.	Part No.		Dimensions			
	Panel Mount Type	Free Hanging Type	A	B	C	D
22	1-1903128-1	1-1903127-1	24.6	23.2	23.0	20.0
26	1-1903128-3	1-1903127-3	28.6	27.2	27.0	24.0
28	1-1903128-4	1-1903127-4	30.6	29.2	29.0	26.0
32	1-1903128-6	1-1903127-6	34.6	33.2	33.0	30.0
34	1-1903128-7	1-1903127-7	36.6	35.2	35.0	32.0
40	1-1903128-0	1-1903127-0	42.6	41.2	41.0	38.0

D-1000 Series (Continued)


D-1100D

Board Mount Tab Header
(Horizontal Type)



No. of Pos.	Part No.	Dimensions	
		A	B
10	1-1827873-5	12.6	8.0
20	1-1827873-0	22.6	18.0

Board Mount Tab Header
(Vertical Type)




No. of Pos.	Plating	Color	Part No.	Dimensions	
				A	B
22	Gold	Black	1-1827872-1	24.6	20.0
	Tin	Yellow	3-1871056-1		
26	Gold	Black	1-1827872-3	28.6	24.0
	Tin	Natural	1-1871056-3		
28	Gold	Black	1-1827872-4	30.6	26.0
	Gold	Black	1-1827872-5		
30	Tin	Black	1-1871315-5	32.6	28.0
	Tin	Natural	1-1871056-5		
	Tin	Yellow	3-1871056-5		
32	Gold	Black	1-1827872-6	34.6	30.0
34	Gold	Black	1-1827872-7	36.6	32.0
40	Gold	Black	1-1827872-0	42.6	38.0
	Tin	Black	1-1871315-0		


D-1000 Series (Continued)

D-1200S

Mating Dimensions




Free Hanging Type



Vertical Type


Dimensions

Receptacle Housing



No. of Pos.	Keying	Part No.	Dimensions	
			A	B
2	X	1-1871465-2	7.6	2.5
	Y	—	—	—

Board Mount Tab Header (Vertical Type)




PC Board Layout
Acceptable Board Thickness:
1.0~1.6±0.1

No. of Pos.	Keying	Part No.	Dimensions		
			A	B	C
2	X	1-1871468-2	2.5	6.0	7.6
	Y	—	—	—	—

D-1000 Series (Continued)

D-1200S

Tab Housing
Free Hanging Type




No. of Pos.	Keying	Part No.	Dimensions			
		Free Hanging Type	A	B	C	D
2	X	1-1903129-2	7.6	6.2	6.0	2.5
	Y	—	—	—	—	—

D-1000 Series

D-1200D


Mating Dimensions



Dimensions


Receptacle Housing

No. of Pos.	Keying	Part No.	Dimensions			
			A	B	C	D
4	X	1-1827864-2	7.6	2.5	—	5.9
	Y	2-1827864-2				
6	X	1-1827864-3	10.1	5.0	8.4	8.4
	Y	2-1827864-3				
8	X	1-1827864-4	12.6	7.5	10.9	10.9
	Y	2-1827864-4				
10	X	1-1827864-5	15.1	10.0	10.9	13.4
	Y	2-1827864-5				
12	X	1-1827864-6	17.6	12.5	15.9	15.9
	Y	2-1827864-6				
20	X	1-1827864-0	27.6	22.5	15.9	25.9
	Y	2-1827864-0				



Board Mount Tab Header (Vertical Type)

No. of Pos.	Keying	Part No.	Dimensions	
			A	B
4	X	1-1827875-2	7.6	2.5
	Y	2-1827875-2		
6	X	1-1827875-3	10.1	5.0
	Y	2-1827875-3		
8	X	1-1827875-4	12.6	7.5
	Y	2-1827875-4		
10	X	1-1827875-5	15.1	10.0
	Y	2-1827875-5		
12	X	1-1827875-6	17.6	12.5
	Y	2-1827875-6		
20	X	1-1827875-0	27.6	22.5
	Y	2-1827875-0		




PC Board Layout

Acceptable Board Thickness:
1.0~1.6±0.1

D-1000 Series (Continued)

D-1200D

Board Mount Tab Header
(Horizontal Type)




No. of Pos.	Part No.	Dimensions	
		A	B
4	1-1827876-2 1-1871673-2*	7.6	2.5
6	1-1827876-3	10.1	5.0
8	1-1827876-4	12.6	7.5
12	1-1827876-6 1-1871673-6*	17.6	12.5
20	1-1827876-0	27.6	22.5

* Marked tab posts are tin plated. Other tab posts are gold plated.

Tab Housing

Panel Mount Type/
Free Hanging Type




No. of Pos.	Part No.		Dimensions			
	Panel Mount Type	Free Hanging Type	A	B	C	D
4	1-1903131-2	1-1903130-2	7.6	6.2	6.0	2.5
6	1-1903131-3	1-1903130-3	10.1	8.7	8.5	5.0
8	1-1903131-4	1-1903130-4	12.6	11.2	11.0	7.5
12	1-1903131-6	1-1903130-6	17.6	16.2	16.0	12.5
20	1-1903131-0	1-1903130-0	27.6	26.2	26.0	22.5

Please contact Technical Support about Y-Key.

D-1000 Series (Continued)

D-1500T

Mating Dimensions




Horizontal/Vertical Type



Dimensions

Receptacle Housing


No. of Pos.	Part No.	Dimensions	
		A	B
3	1-1827579-1	16.35	12.3



Board Mount Tab Header (Vertical Type)



PC Board Layout
Acceptable Board Thickness:
1.0~1.6±0.1




No. of Pos.	Part No.	Dimensions	
		A	B
6	1-1827581-2	8.1	3.5
9	1-1827581-3	11.6	7.0
12	1-1827581-4	15.1	10.5

D-1000 Series (Continued)

D-1500T

Board Mount Tab Header
(Horizontal Type)



No. of Pos.	Part No.	Dimensions		
		A	B	C
6	1-1827583-2	3.5	6.5	8.1

D-1000 Series