


## Block Diagram



# 24AA08/24LC08B/24FC08

## 1.0 ELECTRICAL CHARACTERISTICS

### Absolute Maximum Ratings (†)

|                                                     |                                |
|-----------------------------------------------------|--------------------------------|
| V <sub>CC</sub> .....                               | 6.5V                           |
| All inputs and outputs w.r.t. V <sub>SS</sub> ..... | -0.3V to V <sub>CC</sub> +1.0V |
| Storage temperature .....                           | -65°C to +150°C                |
| Ambient temperature with power applied.....         | -40°C to +125°C                |
| ESD protection on all pins .....                    | ≥4 kV                          |

† **NOTICE:** Stresses above those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device at those or any other conditions above those indicated in the operational listings of this specification is not implied. Exposure to maximum rating conditions for extended periods may affect device reliability.

**TABLE 1-1: DC CHARACTERISTICS**

| DC CHARACTERISTICS |                                    |                                                      | Industrial (I): TA = -40°C to +85°C, V <sub>CC</sub> = +1.7V to +5.5V<br>Extended (E): TA = -40°C to +125°C, V <sub>CC</sub> = +2.5V to +5.5V (24LC08B)<br>Extended (E): TA = -40°C to +125°C, V <sub>CC</sub> = +1.7V to +5.5V (24FC08) |         |                     |       |                                                                         |
|--------------------|------------------------------------|------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|---------------------|-------|-------------------------------------------------------------------------|
| Param. No.         | Symbol                             | Characteristic                                       | Min.                                                                                                                                                                                                                                     | Typical | Max.                | Units | Conditions                                                              |
| D1                 | V <sub>IH</sub>                    | High-Level Input Voltage                             | 0.7 V <sub>CC</sub>                                                                                                                                                                                                                      | —       | —                   | V     |                                                                         |
| D2                 | V <sub>IL</sub>                    | Low-Level Input Voltage                              | —                                                                                                                                                                                                                                        | —       | 0.3 V <sub>CC</sub> | V     |                                                                         |
| D3                 | V <sub>HYS</sub>                   | Hysteresis of Schmitt Trigger Inputs (SDA, SCL pins) | 0.05 V <sub>CC</sub>                                                                                                                                                                                                                     | —       | —                   | V     | Note                                                                    |
| D4                 | V <sub>OL</sub>                    | Low-Level Output Voltage                             | —                                                                                                                                                                                                                                        | —       | 0.40                | V     | I <sub>OL</sub> = 3.0 mA, V <sub>CC</sub> = 2.5V                        |
| D5                 | I <sub>LI</sub>                    | Input Leakage Current                                | —                                                                                                                                                                                                                                        | —       | ±1                  | µA    | V <sub>IN</sub> = V <sub>SS</sub> or V <sub>CC</sub>                    |
| D6                 | I <sub>LO</sub>                    | Output Leakage Current                               | —                                                                                                                                                                                                                                        | —       | ±1                  | µA    | V <sub>OUT</sub> = V <sub>SS</sub> or V <sub>CC</sub>                   |
| D7                 | C <sub>IN</sub> , C <sub>OUT</sub> | Pin Capacitance (all inputs/outputs)                 | —                                                                                                                                                                                                                                        | —       | 10                  | pF    | V <sub>CC</sub> = 5.0V (Note)<br>TA = 25°C, F <sub>CLK</sub> = 1 MHz    |
| D8                 | I <sub>CCWRITE</sub>               | Operating Current                                    | —                                                                                                                                                                                                                                        | —       | 3                   | mA    | V <sub>CC</sub> = 5.5V, SCL = 400 kHz                                   |
| D9                 | I <sub>CCREAD</sub>                |                                                      | —                                                                                                                                                                                                                                        | —       | 1                   | mA    | V <sub>CC</sub> = 5.5V, SCL = 400 kHz                                   |
| D10                | I <sub>CCS</sub>                   | Standby Current                                      | —                                                                                                                                                                                                                                        | —       | 1                   | µA    | SDA = SCL = V <sub>CC</sub><br>WP = V <sub>SS</sub> , I-Temp.           |
|                    |                                    |                                                      | —                                                                                                                                                                                                                                        | —       | 3                   | µA    | SDA = SCL = V <sub>CC</sub><br>WP = V <sub>SS</sub> , E-Temp. (24FC08)  |
|                    |                                    |                                                      | —                                                                                                                                                                                                                                        | —       | 5                   | µA    | SDA = SCL = V <sub>CC</sub><br>WP = V <sub>SS</sub> , E-Temp. (24LC08B) |

**Note:** This parameter is periodically sampled and not 100% tested.

# 24AA08/24LC08B/24FC08

**TABLE 1-1 AC CHARACTERISTICS**

| AC CHARACTERISTICS |         |                                                                                  | Industrial (I): TA = -40°C to +85°C, VCC = +1.7V to +5.5V<br>Extended (E): TA = -40°C to +125°C, VCC = +2.5V to +5.5V (24LC08B)<br>Extended (E): TA = -40°C to +125°C, VCC = +1.7V to +5.5V (24FC08) |      |       |                                     |
|--------------------|---------|----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|-------|-------------------------------------|
| Param. No.         | Symbol  | Characteristic                                                                   | Min.                                                                                                                                                                                                 | Max. | Units | Conditions                          |
| 1                  | FCLK    | Clock Frequency                                                                  | —                                                                                                                                                                                                    | 400  | kHz   | 2.5V ≤ VCC ≤ 5.5V                   |
|                    |         |                                                                                  | —                                                                                                                                                                                                    | 100  | kHz   | 1.7V ≤ VCC < 2.5V (24AA08)          |
|                    |         |                                                                                  | —                                                                                                                                                                                                    | 1000 | kHz   | 1.7V ≤ VCC ≤ 5.5V (24FC08)          |
| 2                  | THIGH   | Clock High Time                                                                  | 600                                                                                                                                                                                                  | —    | ns    | 2.5V ≤ VCC ≤ 5.5V                   |
|                    |         |                                                                                  | 4000                                                                                                                                                                                                 | —    | ns    | 1.7V ≤ VCC < 2.5V (24AA08)          |
|                    |         |                                                                                  | 260                                                                                                                                                                                                  | —    | ns    | 1.7V ≤ VCC ≤ 5.5V (24FC08)          |
| 3                  | TLOW    | Clock Low Time                                                                   | 1300                                                                                                                                                                                                 | —    | ns    | 2.5V ≤ VCC ≤ 5.5V                   |
|                    |         |                                                                                  | 4700                                                                                                                                                                                                 | —    | ns    | 1.7V ≤ VCC < 2.5V (24AA08)          |
|                    |         |                                                                                  | 500                                                                                                                                                                                                  | —    | ns    | 1.7V ≤ VCC ≤ 5.5V (24FC08)          |
| 4                  | TR      | SDA and SCL Rise Time                                                            | —                                                                                                                                                                                                    | 300  | ns    | 2.5V ≤ VCC ≤ 5.5V (Note 1)          |
|                    |         |                                                                                  | —                                                                                                                                                                                                    | 1000 | ns    | 1.7V ≤ VCC < 2.5V (24AA08) (Note 1) |
|                    |         |                                                                                  | —                                                                                                                                                                                                    | 1000 | ns    | 1.7V ≤ VCC ≤ 5.5V (24FC08) (Note 1) |
| 5                  | TF      | SDA and SCL Fall Time                                                            | —                                                                                                                                                                                                    | 300  | ns    | Note 1                              |
| 6                  | THD:STA | Start Condition Hold Time                                                        | 600                                                                                                                                                                                                  | —    | ns    | 2.5V ≤ VCC ≤ 5.5V                   |
|                    |         |                                                                                  | 4000                                                                                                                                                                                                 | —    | ns    | 1.7V ≤ VCC < 2.5V (24AA08)          |
|                    |         |                                                                                  | 250                                                                                                                                                                                                  | —    | ns    | 1.7V ≤ VCC ≤ 5.5V (24FC08)          |
| 7                  | TSU:STA | Start Condition Setup Time                                                       | 600                                                                                                                                                                                                  | —    | ns    | 2.5V ≤ VCC ≤ 5.5V                   |
|                    |         |                                                                                  | 4700                                                                                                                                                                                                 | —    | ns    | 1.7V ≤ VCC < 2.5V (24AA08)          |
|                    |         |                                                                                  | 250                                                                                                                                                                                                  | —    | ns    | 1.7V ≤ VCC ≤ 5.5V (24FC08)          |
| 8                  | THD:DAT | Data Input Hold Time                                                             | 0                                                                                                                                                                                                    | —    | ns    | Note 2                              |
| 9                  | TSU:DAT | Data Input Setup Time                                                            | 100                                                                                                                                                                                                  | —    | ns    | 2.5V ≤ VCC ≤ 5.5V                   |
|                    |         |                                                                                  | 250                                                                                                                                                                                                  | —    | ns    | 1.7V ≤ VCC < 2.5V (24AA08)          |
|                    |         |                                                                                  | 50                                                                                                                                                                                                   | —    | ns    | 1.7V ≤ VCC ≤ 5.5V (24FC08)          |
| 10                 | TSU:STO | Stop Condition Setup Time                                                        | 600                                                                                                                                                                                                  | —    | ns    | 2.5V ≤ VCC ≤ 5.5V                   |
|                    |         |                                                                                  | 4000                                                                                                                                                                                                 | —    | ns    | 1.7V ≤ VCC < 2.5V (24AA08)          |
|                    |         |                                                                                  | 250                                                                                                                                                                                                  | —    | ns    | 1.7V ≤ VCC ≤ 5.5V (24FC08)          |
| 11                 | TSU:WP  | WP Setup Time                                                                    | 600                                                                                                                                                                                                  | —    | ns    | 1.7V ≤ VCC ≤ 5.5V (24FC08)          |
| 12                 | THD:WP  | WP Hold Time                                                                     | 600                                                                                                                                                                                                  | —    | ns    | 1.7V ≤ VCC ≤ 5.5V (24FC08)          |
| 13                 | TAA     | Output Valid from Clock                                                          | —                                                                                                                                                                                                    | 900  | ns    | 2.5V ≤ VCC ≤ 5.5V (Note 2)          |
|                    |         |                                                                                  | —                                                                                                                                                                                                    | 3500 | ns    | 1.7V ≤ VCC < 2.5V (24AA08) (Note 2) |
|                    |         |                                                                                  | —                                                                                                                                                                                                    | 450  | ns    | 1.7V ≤ VCC ≤ 5.5V (24FC08) (Note 2) |
| 14                 | TBUF    | Bus Free Time: The time the bus must be free before a new transmission can start | 1300                                                                                                                                                                                                 | —    | ns    | 2.5V ≤ VCC ≤ 5.5V                   |
|                    |         |                                                                                  | 4700                                                                                                                                                                                                 | —    | ns    | 1.7V ≤ VCC < 2.5V (24AA08)          |
|                    |         |                                                                                  | 500                                                                                                                                                                                                  | —    | ns    | 1.7V ≤ VCC ≤ 5.5V (24FC08)          |

**Note 1:** Characterized but not 100% tested.

**2:** As a transmitter, the device must provide an internal minimum delay time to bridge the undefined region (minimum 300 ns) of the falling edge of SCL to avoid unintended generation of Start or Stop conditions.

**3:** CB = total capacitance of one bus line in pF.

**4:** This parameter is not tested but ensured by characterization.

# 24AA08/24LC08B/24FC08

**TABLE 1-1 AC CHARACTERISTICS (CONTINUED)**

| AC CHARACTERISTICS (Continued) |        |                                                   | Industrial (I): TA = -40°C to +85°C, VCC = +1.7V to +5.5V<br>Extended (E): TA = -40°C to +125°C, VCC = +2.5V to +5.5V (24LC08B)<br>Extended (E): TA = -40°C to +125°C, VCC = +1.7V to +5.5V (24FC08) |      |        |                                               |
|--------------------------------|--------|---------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|--------|-----------------------------------------------|
| Param. No.                     | Symbol | Characteristic                                    | Min.                                                                                                                                                                                                 | Max. | Units  | Conditions                                    |
| 15                             | TOF    | Output Fall Time from VIH Minimum to VIL Maximum  | —                                                                                                                                                                                                    | 250  | ns     | 2.5V ≤ VCC ≤ 5.5V (Notes 1, 3 and 4)          |
|                                |        |                                                   | —                                                                                                                                                                                                    | 250  | ns     | 1.7V ≤ VCC < 2.5V (24AA08) (Notes 1, 3 and 4) |
| 16                             | TSP    | Input Filter Spike Suppression (SDA and SCL pins) | —                                                                                                                                                                                                    | 50   | ns     | Note 1                                        |
|                                |        |                                                   | —                                                                                                                                                                                                    | 100  | ns     | 1.7V ≤ VCC ≤ 5.5V (24FC08) (Note 1)           |
| 17                             | TWC    | Write Cycle Time (byte or page)                   | —                                                                                                                                                                                                    | 5    | ms     |                                               |
| 18                             |        | Endurance                                         | 1,000,000                                                                                                                                                                                            | —    | cycles | 25°C, 5.5V, Page Mode (Note 4)                |


**Note 1:** Characterized but not 100% tested.

**2:** As a transmitter, the device must provide an internal minimum delay time to bridge the undefined region (minimum 300 ns) of the falling edge of SCL to avoid unintended generation of Start or Stop conditions.


**3:** CB = total capacitance of one bus line in pF.

**4:** This parameter is not tested but ensured by characterization.

**FIGURE 1-1: BUS TIMING DATA**



**FIGURE 1-2: BUS TIMING START/STOP**



## 2.0 PIN DESCRIPTIONS

The descriptions of the pins are listed in [Table 2-1](#).

**TABLE 2-1: PIN FUNCTION TABLE**

| Name | DFN <sup>(1)</sup> | MSOP | PDIP | SOIC | TDFN <sup>(1)</sup> | TSSOP | UDFN <sup>(1)</sup> | SOT-23 | CSP | Description             |
|------|--------------------|------|------|------|---------------------|-------|---------------------|--------|-----|-------------------------|
| A0   | 1                  | 1    | 1    | 1    | 1                   | 1     | 1                   | —      | —   | Not Connected           |
| A1   | 2                  | 2    | 2    | 2    | 2                   | 2     | 2                   | —      | —   | Not Connected           |
| A2   | 3                  | 3    | 3    | 3    | 3                   | 3     | 3                   | —      | —   | Not Connected           |
| Vss  | 4                  | 4    | 4    | 4    | 4                   | 4     | 4                   | 2      | 2   | Ground                  |
| SDA  | 5                  | 5    | 5    | 5    | 5                   | 5     | 5                   | 3      | 4   | Serial Address/Data I/O |
| SCL  | 6                  | 6    | 6    | 6    | 6                   | 6     | 6                   | 1      | 3   | Serial Clock            |
| WP   | 7                  | 7    | 7    | 7    | 7                   | 7     | 7                   | 5      | —   | Write-Protect Input     |
| Vcc  | 8                  | 8    | 8    | 8    | 8                   | 8     | 8                   | 4      | 1   | Power Supply            |

**Note 1:** The exposed pad on the DFN/TDFN/UDFN package can be connected to Vss or left floating.

### 2.1 A0, A1, A2

The A0, A1 and A2 pins are not used by the 24XX08. They may be left floating or tied to either Vss or Vcc.

### 2.2 Serial Address/Data Input/Output (SDA)

The SDA input is a bidirectional pin used to transfer addresses and data into and out of the device. Since it is an open-drain terminal, the SDA bus requires a pull-up resistor to Vcc (typical 10 kΩ for 100 kHz, 2 kΩ for 400 kHz and 1 MHz).

For normal data transfer, SDA is allowed to change only during SCL low. Changes during SCL high are reserved for indicating Start and Stop conditions.

### 2.3 Serial Clock (SCL)

The SCL input is used to synchronize the data transfer to and from the device.

### 2.4 Write-Protect (WP)

This pin must be connected to either Vss or Vcc.

If tied to Vss, normal memory operation is enabled (read/write the entire memory 000-3FF).

If tied to Vcc, write operations are inhibited. The entire memory will be write-protected. Read operations are not affected.

The Chip Scale package does not support the write-protect feature.

## 3.0 FUNCTIONAL DESCRIPTION

The 24XX08 supports a bidirectional, two-wire bus and data transmission protocol. A device that sends data onto the bus is defined as transmitter, while defining a device receiving data as a receiver. The bus has to be controlled by a host device which generates the Serial Clock (SCL), controls the bus access and generates the Start and Stop conditions, while the 24XX08 works as client. Both host and client can operate as transmitter or receiver, but the host device determines which mode is activated.

## 4.0 BUS CHARACTERISTICS

The following **bus protocol** has been defined:

- Data transfer may be initiated only when the bus is not busy.
- During data transfer, the data line must remain stable whenever the clock line is high. Changes in the data line while the clock line is high will be interpreted as a Start or Stop condition.

Accordingly, the following bus conditions have been defined (Figure 4-1).

### 4.1 Bus Not Busy (A)

Both data and clock lines remain high.

### 4.2 Start Data Transfer (B)

A high-to-low transition of the SDA line while the clock (SCL) is high determines a Start condition. All commands must be preceded by a Start condition.

### 4.3 Stop Data Transfer (C)

A low-to-high transition of the SDA line while the clock (SCL) is high determines a Stop condition. All operations must be ended with a Stop condition.

## 4.4 Data Valid (D)

The state of the data line represents valid data when, after a Start condition, the data line is stable for the duration of the high period of the clock signal.

The data on the line must be changed during the low period of the clock signal. There is one clock pulse per bit of data.

Each data transfer is initiated with a Start condition and terminated with a Stop condition. The number of data bytes transferred between the Start and Stop conditions is determined by the host device and is, theoretically, unlimited (although only the last sixteen will be stored when doing a write operation). When an overwrite does occur, it will replace data based on the first-in first-out (FIFO) principle.


## 4.5 Acknowledge

Each receiving device, when addressed, is obliged to generate an Acknowledge after the reception of each byte. The host device must generate an extra clock pulse which is associated with this Acknowledge bit.

**Note:** The 24XX08 does not generate any Acknowledge bits if an internal programming cycle is in progress.

The device that acknowledges has to pull down the SDA line during the Acknowledge clock pulse in such a way that the SDA line is stable-low during the high period of the Acknowledge-related clock pulse. Moreover, setup and hold times must be taken into account. During reads, a host must signal an end of data to the client by not generating an Acknowledge bit on the last byte that has been clocked out of the client. In this case, the client (24XX08) will leave the data line high to enable the host to generate the Stop condition.

**FIGURE 4-1: DATA TRANSFER SEQUENCE ON THE SERIAL BUS**



## 5.0 DEVICE ADDRESSING

A control byte is the first byte received following the Start condition from the host device. The control byte consists of a four-bit control code. For the 24XX08, this is set as '1010' binary for read and write operations. The next bit of the control byte is a "don't care" for the 24XX08. The last two bits, B1 and B0, are used by the host device to select which of the four 256-word blocks of memory are to be accessed. These bits, in effect, are the Most Significant bits of the word address. The combination of the 4-bit control code and the next three bits are called the client address.

The last bit of the control byte is the Read/Write ( $\overline{R/W}$ ) bit and it defines the operation to be performed. When set to '1', a read operation is selected. When set to '0', a write operation is selected. Following the Start condition, the 24XX08 monitors the SDA bus, checking the device type identifier being transmitted. Upon receiving a valid client address and the  $\overline{R/W}$  bit, the client device outputs an Acknowledge signal on the SDA line. Depending on the state of the  $\overline{R/W}$  bit, the 24XX08 will select a read or write operation.

The next byte received defines the address of the first data byte within the selected block (Figure 5-2). The word address byte uses all eight bits.

| Operation | Control Code | Block Select  | $\overline{R/W}$ |
|-----------|--------------|---------------|------------------|
| Read      | 1010         | Block Address | 1                |
| Write     | 1010         | Block Address | 0                |

FIGURE 5-1: CONTROL BYTE ALLOCATION





FIGURE 5-2: ADDRESS SEQUENCE BIT ASSIGNMENTS



## 6.0 WRITE OPERATION

### 6.1 Byte Write

Following the Start condition from the host, the device code (4 bits), the block address (1 bit is a “don't care”, plus B1 and B0 bits) and the R/W bit, which is a logic-low, is placed onto the bus by the host transmitter. This indicates to the addressed client receiver that a byte with a word address will follow after it has generated an Acknowledge bit during the ninth clock cycle. Therefore, the next byte transmitted by the host is the word address and will be written into the Address Pointer of the 24XX08. After receiving another Acknowledge signal from the 24XX08, the host device will transmit the data word to be written into the addressed memory location. The 24XX08 acknowledges again and the host generates a Stop condition. This initiates the internal write cycle, and, during this time, the 24XX08 will not generate Acknowledge signals (Figure 6-1).

### 6.2 Page Write


The write control byte, word address and first data byte are transmitted to the 24XX08 in the same way as in a byte write. However, instead of generating a Stop condition, the host transmits up to 16 data bytes to the 24XX08, which are temporarily stored in the on-chip page buffer and will be written into the memory once the host has transmitted a Stop condition. Upon receipt of each word, the four lower-order Address Pointer bits, which form the byte counter, are internally incremented by one. The higher-order four bits of the word address and bits B1 and B0 remain constant. If the host should transmit more than 16 words prior to generating the Stop condition, the Address Pointer will roll over and the previously received data will be overwritten. As with the byte write operation, once the Stop condition is received, an internal write cycle will begin (Figure 6-2).

**Note:** Page write operations are limited to writing bytes within a single physical page **regardless** of the number of bytes actually being written. Physical page boundaries start at addresses that are integer multiples of the page buffer size (or ‘page size’) and end at addresses that are integer multiples of page size – 1. If a page write command attempts to write across a physical page boundary, the result is that the data wraps around to the beginning of the current page (overwriting data previously stored there), instead of being written to the next page, as might be expected. It is therefore necessary for the application software to prevent page write operations that would attempt to cross a page boundary.


### 6.3 Write Protection

The WP pin allows the user to write-protect the entire array (000-3FF) when the pin is tied to VCC. If tied to VSS, the write protection is disabled. The Chip Scale package does not support the write-protect feature.

**FIGURE 6-1: BYTE WRITE**




**FIGURE 6-2: PAGE WRITE**



## 7.0 ACKNOWLEDGE POLLING

Since the device will not acknowledge during a write cycle, this can be used to determine when the cycle is complete (this feature can be used to maximize bus throughput). Once the Stop condition for a write command has been issued from the host, the device initiates the internally-timed write cycle. ACK polling can then be initiated immediately. This involves the host sending a Start condition followed by the control byte for a write command ( $R/\overline{W} = 0$ ). If the device is still busy with the write cycle, no ACK will be returned. If the cycle is complete, the device will return the ACK and the host can then proceed with the next read or write operation. See [Figure 7-1](#) for a flow diagram of this operation.

**FIGURE 7-1: ACKNOWLEDGE POLLING FLOW**



## 8.0 READ OPERATION

Read operations are initiated in the same way as write operations, with the exception that the R/W bit of the client address is set to '1'. There are three basic types of read operations: current address read, random read and sequential read.

### 8.1 Current Address Read

The 24XX08 contains an Address Pointer that maintains the address of the last word accessed, internally incremented by one. Therefore, if the previous access (either a read or write operation) was to address  $n$ , the next current address read operation would access data from address  $n + 1$ . Upon receipt of the client address with R/W bit set to '1', the 24XX08 issues an Acknowledge and transmits the 8-bit data word. The host will not acknowledge the transfer, but does generate a Stop condition and the 24XX08 discontinues transmission (Figure 8-1).

### 8.2 Random Read

Random read operations allow the host to access any memory location in a random manner. To perform this type of read operation, the word address must first be set. This is accomplished by sending the word address to the 24XX08 as part of a write operation. Once the word address is sent, the host generates a Start condition following the Acknowledge. This terminates the write operation, but not before the internal Address Pointer is set. The host then issues the control byte again, but with the R/W bit set to a '1'. The 24XX08 will then issue an Acknowledge and transmits the 8-bit data word. The host will not acknowledge the transfer, but does generate a Stop condition and the 24XX08 discontinues transmission (Figure 8-2).

### 8.3 Sequential Read


Sequential reads are initiated in the same way as a random read or current read, except that once the 24XX08 transmits the first data byte, the host issues an Acknowledge (as opposed to a Stop condition in a random read). This directs the 24XX08 to transmit the next sequentially addressed 8-bit word (Figure 8-3).

To provide sequential reads the 24XX08 contains an internal Address Pointer which is incremented by one at the completion of each operation. This Address Pointer allows the entire memory contents to be serially read during one operation.


### 8.4 Noise Protection

The SCL and SDA inputs have Schmitt Trigger and filter circuits which suppress noise spikes to assure proper device operation even on a noisy bus.


**FIGURE 8-1: CURRENT ADDRESS READ**



**FIGURE 8-2: RANDOM READ**




**FIGURE 8-3: SEQUENTIAL READ**




## 9.0 PACKAGING INFORMATION

### 9.1 Package Marking Information\*


8-Lead 2x3 DFN




Example




8-Lead MSOP




Example




8-Lead PDIP (300 mil)




Example




8-Lead SOIC (3.90 mm)




Example



8-Lead 2x3 TDFN




Example




# 24AA08/24LC08B/24FC08


8-Lead TSSOP




Example




8-Lead 2x3 UDFN




Example




5-Lead SOT-23 (1-Line Marking)




Example




5-Lead SOT-23 (2-Line Marking)




Example



4-Ball CSP



Example



# 24AA08/24LC08B/24FC08

| Part Number | 1st Line Marking Codes |         |                      |                         |         |         |       |      |                       |                       |     |
|-------------|------------------------|---------|----------------------|-------------------------|---------|---------|-------|------|-----------------------|-----------------------|-----|
|             | DFN                    |         | MSOP                 | SOIC                    | TDFN    |         | TSSOP | UDFN | SOT-23                |                       | CSP |
|             | I-Temp.                | E-Temp. |                      |                         | I-Temp. | E-Temp. |       |      | I-Temp.               | E-Temp.               |     |
| 24AA08      | 241                    | —       | 4A08T <sup>(1)</sup> | 24AA08T <sup>(1)</sup>  | A41     | —       | 4A08  | —    | B4NN <sup>(2,3)</sup> | —                     | 4N  |
| 24LC08B     | 244                    | 245     | 4L8BT <sup>(1)</sup> | 24LC08BT <sup>(1)</sup> | A44     | A45     | 4L08  | —    | M4NN <sup>(2,3)</sup> | N4NN <sup>(2,3)</sup> | —   |
| 24FC08      | —                      | —       | 24FC08               | 24FC08                  | —       | —       | AADY  | ADS  | AAFBYY <sup>(4)</sup> | AAFBYY <sup>(4)</sup> | —   |

**Note 1:** T = Temperature grade (I, E)

**2:** NN = Alphanumeric traceability code

**3:** These parts use the 1-line SOT-23 marking format

**4:** These parts use the 2-line SOT-23 marking format

**Legend:** XX...X Part number or part number code  
T Temperature (I, E)  
Y Year code (last digit of calendar year)  
YY Year code (last 2 digits of calendar year)  
WW Week code (week of January 1 is week '01')  
NNN Alphanumeric traceability code (2 characters for small packages)  
ⓔ3 JEDEC<sup>®</sup> designator for Matte Tin (Sn)


\* Standard OTP marking consists of Microchip part number, year code, week code, and traceability code.

**Note:** For very small packages with no room for the JEDEC<sup>®</sup> designator ⓔ3, the marking will only appear on the outer carton or reel label.

**Note:** In the event the full Microchip part number cannot be marked on one line, it will be carried over to the next line, thus limiting the number of available characters for customer-specific information.

## 8-Lead Plastic Dual Flat, No Lead Package (MC) – 2x3x0.9 mm Body [DFN]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



| Units                  |    | MILLIMETERS |      |      |
|------------------------|----|-------------|------|------|
| Dimension Limits       |    | MIN         | NOM  | MAX  |
| Number of Pins         | N  | 8           |      |      |
| Pitch                  | e  | 0.50 BSC    |      |      |
| Overall Height         | A  | 0.80        | 0.90 | 1.00 |
| Standoff               | A1 | 0.00        | 0.02 | 0.05 |
| Contact Thickness      | A3 | 0.20 REF    |      |      |
| Overall Length         | D  | 2.00 BSC    |      |      |
| Overall Width          | E  | 3.00 BSC    |      |      |
| Exposed Pad Length     | D2 | 1.30        | –    | 1.55 |
| Exposed Pad Width      | E2 | 1.50        | –    | 1.75 |
| Contact Width          | b  | 0.20        | 0.25 | 0.30 |
| Contact Length         | L  | 0.30        | 0.40 | 0.50 |
| Contact-to-Exposed Pad | K  | 0.20        | –    | –    |

### Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Package may have one or more exposed tie bars at ends.
- Package is saw singulated.
- Dimensioning and tolerancing per ASME Y14.5M.

BSC: Basic Dimension. Theoretically exact value shown without tolerances.


REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-123C

# 24AA08/24LC08B/24FC08

## 8-Lead Plastic Dual Flat, No Lead Package (MC) - 2x3x0.9mm Body [DFN]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

| Units                      |    | MILLIMETERS |      |      |
|----------------------------|----|-------------|------|------|
| Dimension Limits           |    | MIN         | NOM  | MAX  |
| Contact Pitch              | E  | 0.50 BSC    |      |      |
| Optional Center Pad Width  | W2 |             |      | 1.45 |
| Optional Center Pad Length | T2 |             |      | 1.75 |
| Contact Pad Spacing        | C1 |             | 2.90 |      |
| Contact Pad Width (X8)     | X1 |             |      | 0.30 |
| Contact Pad Length (X8)    | Y1 |             |      | 0.75 |
| Distance Between Pads      | G  | 0.20        |      |      |

**Notes:**

1. Dimensioning and tolerancing per ASME Y14.5M


BSC: Basic Dimension. Theoretically exact value shown without tolerances.

Microchip Technology Drawing No. C04-2123B

# 24AA08/24LC08B/24FC08

## 8-Lead Plastic Micro Small Outline Package (MS) [MSOP]


**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



Microchip Technology Drawing C04-111C Sheet 1 of 2

## 8-Lead Plastic Micro Small Outline Package (MS) [MSOP]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



| Dimension Limits         | Units | MILLIMETERS |      |      |
|--------------------------|-------|-------------|------|------|
|                          |       | MIN         | NOM  | MAX  |
| Number of Pins           | N     |             | 8    |      |
| Pitch                    | e     | 0.65 BSC    |      |      |
| Overall Height           | A     | -           | -    | 1.10 |
| Molded Package Thickness | A2    | 0.75        | 0.85 | 0.95 |
| Standoff                 | A1    | 0.00        | -    | 0.15 |
| Overall Width            | E     | 4.90 BSC    |      |      |
| Molded Package Width     | E1    | 3.00 BSC    |      |      |
| Overall Length           | D     | 3.00 BSC    |      |      |
| Foot Length              | L     | 0.40        | 0.60 | 0.80 |
| Footprint                | L1    | 0.95 REF    |      |      |
| Foot Angle               | φ     | 0°          | -    | 8°   |
| Lead Thickness           | c     | 0.08        | -    | 0.23 |
| Lead Width               | b     | 0.22        | -    | 0.40 |

**Notes:**


- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Dimensions D and E1 do not include mold flash or protrusions. Mold flash or protrusions shall not exceed 0.15mm per side.
- Dimensioning and tolerancing per ASME Y14.5M.  
BSC: Basic Dimension. Theoretically exact value shown without tolerances.  
REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-111C Sheet 2 of 2

# 24AA08/24LC08B/24FC08

## 8-Lead Plastic Micro Small Outline Package (MS) [MSOP]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

| Units                   |    | MILLIMETERS |      |      |
|-------------------------|----|-------------|------|------|
| Dimension Limits        |    | MIN         | NOM  | MAX  |
| Contact Pitch           | E  | 0.65 BSC    |      |      |
| Contact Pad Spacing     | C  |             | 4.40 |      |
| Overall Width           | Z  |             |      | 5.85 |
| Contact Pad Width (X8)  | X1 |             |      | 0.45 |
| Contact Pad Length (X8) | Y1 |             |      | 1.45 |
| Distance Between Pads   | G1 | 2.95        |      |      |
| Distance Between Pads   | GX | 0.20        |      |      |

**Notes:**

1. Dimensioning and tolerancing per ASME Y14.5M


BSC: Basic Dimension. Theoretically exact value shown without tolerances.

Microchip Technology Drawing No. C04-2111A

# 24AA08/24LC08B/24FC08

## 8-Lead Plastic Dual In-Line (P) - 300 mil Body [PDIP]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




Microchip Technology Drawing No. C04-018-P Rev E Sheet 1 of 2

## 8-Lead Plastic Dual In-Line (P) - 300 mil Body [PDIP]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>

### ALTERNATE LEAD DESIGN (NOTE 5)



| Units                      |    | INCHES   |      |      |
|----------------------------|----|----------|------|------|
| Dimension Limits           |    | MIN      | NOM  | MAX  |
| Number of Pins             | N  | 8        |      |      |
| Pitch                      | e  | .100 BSC |      |      |
| Top to Seating Plane       | A  | -        | -    | .210 |
| Molded Package Thickness   | A2 | .115     | .130 | .195 |
| Base to Seating Plane      | A1 | .015     | -    | -    |
| Shoulder to Shoulder Width | E  | .290     | .310 | .325 |
| Molded Package Width       | E1 | .240     | .250 | .280 |
| Overall Length             | D  | .348     | .365 | .400 |
| Tip to Seating Plane       | L  | .115     | .130 | .150 |
| Lead Thickness             | c  | .008     | .010 | .015 |
| Upper Lead Width           | b1 | .040     | .060 | .070 |
| Lower Lead Width           | b  | .014     | .018 | .022 |
| Overall Row Spacing        | §  | eB       | -    | .430 |

#### Notes:


- Pin 1 visual index feature may vary, but must be located within the hatched area.
- § Significant Characteristic
- Dimensions D and E1 do not include mold flash or protrusions. Mold flash or protrusions shall not exceed .010" per side.
- Dimensioning and tolerancing per ASME Y14.5M  
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
- Lead design above seating plane may vary, based on assembly vendor.

Microchip Technology Drawing No. C04-018-P Rev E Sheet 2 of 2

# 24AA08/24LC08B/24FC08

## 8-Lead Plastic Small Outline (SN) - Narrow, 3.90 mm (.150 In.) Body [SOIC]


**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



Microchip Technology Drawing No. C04-057-SN Rev F Sheet 1 of 2

## 8-Lead Plastic Small Outline (SN) - Narrow, 3.90 mm (.150 In.) Body [SOIC]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



| Units                    |    | MILLIMETERS |     |      |
|--------------------------|----|-------------|-----|------|
| Dimension Limits         |    | MIN         | NOM | MAX  |
| Number of Pins           | N  | 8           |     |      |
| Pitch                    | e  | 1.27 BSC    |     |      |
| Overall Height           | A  | -           | -   | 1.75 |
| Molded Package Thickness | A2 | 1.25        | -   | -    |
| Standoff §               | A1 | 0.10        | -   | 0.25 |
| Overall Width            | E  | 6.00 BSC    |     |      |
| Molded Package Width     | E1 | 3.90 BSC    |     |      |
| Overall Length           | D  | 4.90 BSC    |     |      |
| Chamfer (Optional)       | h  | 0.25        | -   | 0.50 |
| Foot Length              | L  | 0.40        | -   | 1.27 |
| Footprint                | L1 | 1.04 REF    |     |      |
| Foot Angle               | φ  | 0°          | -   | 8°   |
| Lead Thickness           | c  | 0.17        | -   | 0.25 |
| Lead Width               | b  | 0.31        | -   | 0.51 |
| Mold Draft Angle Top     | α  | 5°          | -   | 15°  |
| Mold Draft Angle Bottom  | β  | 5°          | -   | 15°  |

### Notes:


- Pin 1 visual index feature may vary, but must be located within the hatched area.
- § Significant Characteristic
- Dimensions D and E1 do not include mold flash or protrusions. Mold flash or protrusions shall not exceed 0.15mm per side.
- Dimensioning and tolerancing per ASME Y14.5M
  - BSC: Basic Dimension. Theoretically exact value shown without tolerances.
  - REF: Reference Dimension, usually without tolerance, for information purposes only.
- Datums A & B to be determined at Datum H.

Microchip Technology Drawing No. C04-057-SN Rev F Sheet 2 of 2

# 24AA08/24LC08B/24FC08

## 8-Lead Plastic Small Outline (SN) - Narrow, 3.90 mm (.150 In.) Body [SOIC]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



### RECOMMENDED LAND PATTERN

|                         |    | Units | MILLIMETERS |          |      |
|-------------------------|----|-------|-------------|----------|------|
| Dimension Limits        |    |       | MIN         | NOM      | MAX  |
| Contact Pitch           | E  |       |             | 1.27 BSC |      |
| Contact Pad Spacing     | C  |       |             | 5.40     |      |
| Contact Pad Width (X8)  | X1 |       |             |          | 0.60 |
| Contact Pad Length (X8) | Y1 |       |             |          | 1.55 |

#### Notes:

1. Dimensioning and tolerancing per ASME Y14.5M


BSC: Basic Dimension. Theoretically exact value shown without tolerances.

Microchip Technology Drawing C04-2057-SN Rev F

# 24AA08/24LC08B/24FC08

## 8-Lead Plastic Dual Flat, No Lead Package (MN) – 2x3x0.8 mm Body [TDFN] With 1.4x1.3 mm Exposed Pad (JEDEC Package type WDFN)

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




Microchip Technology Drawing No. C04-129-MN Rev E Sheet 1 of 2

# 24AA08/24LC08B/24FC08

## 8-Lead Plastic Dual Flat, No Lead Package (MN) – 2x3x0.8 mm Body [TDFN] With 1.4x1.3 mm Exposed Pad (JEDEC Package type WDFN)

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



|                        |    | Units | MILLIMETERS |      |      |
|------------------------|----|-------|-------------|------|------|
| Dimension Limits       |    |       | MIN         | NOM  | MAX  |
| Number of Pins         | N  |       | 8           |      |      |
| Pitch                  | e  |       | 0.50 BSC    |      |      |
| Overall Height         | A  |       | 0.70        | 0.75 | 0.80 |
| Standoff               | A1 |       | 0.00        | 0.02 | 0.05 |
| Contact Thickness      | A3 |       | 0.20 REF    |      |      |
| Overall Length         | D  |       | 2.00 BSC    |      |      |
| Overall Width          | E  |       | 3.00 BSC    |      |      |
| Exposed Pad Length     | D2 |       | 1.35        | 1.40 | 1.45 |
| Exposed Pad Width      | E2 |       | 1.25        | 1.30 | 1.35 |
| Contact Width          | b  |       | 0.20        | 0.25 | 0.30 |
| Contact Length         | L  |       | 0.25        | 0.30 | 0.45 |
| Contact-to-Exposed Pad | K  |       | 0.20        | -    | -    |

### Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Package may have one or more exposed tie bars at ends.
3. Package is saw singulated
4. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.


REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing No. C04-129-MN Rev E Sheet 2 of 2

# 24AA08/24LC08B/24FC08

## 8-Lead Plastic Dual Flat, No Lead Package (MN) – 2x3x0.8 mm Body [TDFN] With 1.4x1.3 mm Exposed Pad (JEDEC Package type WDFN)

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



### RECOMMENDED LAND PATTERN

| Units                      |    | MILLIMETERS |      |      |
|----------------------------|----|-------------|------|------|
| Dimension Limits           |    | MIN         | NOM  | MAX  |
| Contact Pitch              | E  | 0.50 BSC    |      |      |
| Optional Center Pad Width  | X2 |             |      | 1.60 |
| Optional Center Pad Length | Y2 |             |      | 1.50 |
| Contact Pad Spacing        | C  |             | 2.90 |      |
| Contact Pad Width (X8)     | X1 |             |      | 0.25 |
| Contact Pad Length (X8)    | Y1 |             |      | 0.85 |
| Thermal Via Diameter       | V  |             | 0.30 |      |
| Thermal Via Pitch          | EV |             | 1.00 |      |

#### Notes:

1. Dimensioning and tolerancing per ASME Y14.5M  
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
2. For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing No. C04-129-MN Rev. B

### 8-Lead Plastic Thin Shrink Small Outline (ST) - 4.4 mm Body [TSSOP]

Diagram illustrating the top view of a mechanical part with feature control frames and datum labels.

**Feature Control Frames:**

- Feature A:  $\text{0.10} \text{ (M) } \text{C B A}$
- Feature B:  $\text{0.20} \text{ C B A}$

**Datum Labels:**

- (DATUM A) points to the vertical centerline of the part.
- (DATUM B) points to the horizontal centerline of the part.

**Dimensions and Tolerances:**



- Dimension D: Overall width of the part.
- Dimension E1: Overall height of the part.
- Dimension e: Distance from the left edge to the centerline of the feature.
- Dimension 8X b: Distance from the centerline of the feature to the edge of the feature.

**Geometric Features:**

- Feature A: A circular feature with a diameter tolerance of 0.10 (Maximum Material Condition).
- Feature B: A circular feature with a diameter tolerance of 0.20.

**Sectional View:**


A vertical section line is shown, labeled 1 and 2, indicating a cross-section of the part.

Downloaded from [Arrow.com](https://www.Arrow.com).

# 24AA08/24LC08B/24FC08

## 8-Lead Plastic Thin Shrink Small Outline (ST) - 4.4 mm Body [TSSOP]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



| Units                    |        | MILLIMETERS |      |      |
|--------------------------|--------|-------------|------|------|
| Dimension Limits         |        | MIN         | NOM  | MAX  |
| Number of Pins           | N      | 8           |      |      |
| Pitch                    | e      | 0.65 BSC    |      |      |
| Overall Height           | A      | -           | -    | 1.20 |
| Molded Package Thickness | A2     | 0.80        | 1.00 | 1.05 |
| Standoff                 | A1     | 0.05        | -    | -    |
| Overall Width            | E      | 6.40 BSC    |      |      |
| Molded Package Width     | E1     | 4.30        | 4.40 | 4.50 |
| Overall Length           | D      | 2.90        | 3.00 | 3.10 |
| Foot Length              | L      | 0.45        | 0.60 | 0.75 |
| Footprint                | L1     | 1.00 REF    |      |      |
| Lead Thickness           | c      | 0.09        | -    | 0.25 |
| Foot Angle               | $\phi$ | 0°          | 4°   | 8°   |
| Lead Width               | b      | 0.19        | -    | 0.30 |

### Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Dimensions D and E1 do not include mold flash or protrusions. Mold flash or protrusions shall not exceed 0.20mm per side.
3. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.


REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-086 Rev C Sheet 2 of 2

# 24AA08/24LC08B/24FC08

## 8-Lead Plastic Thin Shrink Small Outline (ST) - 4.4 mm Body [TSSOP]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



### RECOMMENDED LAND PATTERN

| Units                          |    | MILLIMETERS |      |      |
|--------------------------------|----|-------------|------|------|
| Dimension Limits               |    | MIN         | NOM  | MAX  |
| Contact Pitch                  | E  | 0.65 BSC    |      |      |
| Contact Pad Spacing            | C  |             | 5.80 |      |
| Contact Pad Width (X8)         | X1 |             |      | 0.45 |
| Contact Pad Length (X8)        | Y1 |             |      | 1.50 |
| Contact Pad to Center Pad (X6) | G1 | 0.20        |      |      |

#### Notes:


- Dimensioning and tolerancing per ASME Y14.5M  
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
- For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-2086 Rev B

# 24AA08/24LC08B/24FC08

## 8-Lead Ultra Thin Plastic Dual Flat, No Lead Package (Q4B) - 2x3 mm Body [UDFN] Atmel Legacy Global Package Code YNZ

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




Microchip Technology Drawing C04-21355-Q4B Rev C Sheet 1 of 2

# 24AA08/24LC08B/24FC08

## 8-Lead Ultra Thin Plastic Dual Flat, No Lead Package (Q4B) - 2x3 mm Body [UDFN] Atmel Legacy Global Package Code YNZ

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



| Units                   |    | MILLIMETERS |      |      |
|-------------------------|----|-------------|------|------|
| Dimension Limits        |    | MIN         | NOM  | MAX  |
| Number of Terminals     | N  | 8           |      |      |
| Pitch                   | e  | 0.50 BSC    |      |      |
| Overall Height          | A  | 0.50        | 0.55 | 0.60 |
| Standoff                | A1 | 0.00        | 0.02 | 0.05 |
| Terminal Thickness      | A3 | 0.152 REF   |      |      |
| Overall Length          | D  | 2.00 BSC    |      |      |
| Exposed Pad Length      | D2 | 1.40        | 1.50 | 1.60 |
| Overall Width           | E  | 3.00 BSC    |      |      |
| Exposed Pad Width       | E2 | 1.20        | 1.30 | 1.40 |
| Terminal Width          | b  | 0.18        | 0.25 | 0.30 |
| Terminal Length         | L  | 0.25        | 0.35 | 0.45 |
| Terminal-to-Exposed-Pad | K  | 0.20        | -    | -    |

**Notes:**

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Package is saw singulated
3. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.


REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-21355-Q4B Rev C Sheet 2 of 2

# 24AA08/24LC08B/24FC08

## 8-Lead Ultra Thin Plastic Dual Flat, No Lead Package (Q4B) - 2x3 mm Body [UDFN] Atmel Legacy Global Package Code YNZ

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

| Units                           |    | MILLIMETERS |      |      |
|---------------------------------|----|-------------|------|------|
| Dimension Limits                |    | MIN         | NOM  | MAX  |
| Contact Pitch                   | E  | 0.50 BSC    |      |      |
| Optional Center Pad Width       | X2 |             |      | 1.60 |
| Optional Center Pad Length      | Y2 |             |      | 1.40 |
| Contact Pad Spacing             | C  |             | 2.90 |      |
| Contact Pad Width (X8)          | X1 |             |      | 0.30 |
| Contact Pad Length (X8)         | Y1 |             |      | 0.85 |
| Contact Pad to Center Pad (X8)  | G1 | 0.33        |      |      |
| Contact Pad to Contact Pad (X6) | G2 | 0.20        |      |      |
| Thermal Via Diameter            | V  |             | 0.30 |      |
| Thermal Via Pitch               | EV |             | 1.00 |      |

**Notes:**


- Dimensioning and tolerancing per ASME Y14.5M  
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
- For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-23355-Q4B Rev C



## 5-Lead Plastic Small Outline Transistor (OT) [SOT23]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



VIEW A-A  
SHEET 1

| Units                    |    | MILLIMETERS |     |      |
|--------------------------|----|-------------|-----|------|
| Dimension Limits         |    | MIN         | NOM | MAX  |
| Number of Pins           | N  | 5           |     |      |
| Pitch                    | e  | 0.95 BSC    |     |      |
| Outside lead pitch       | e1 | 1.90 BSC    |     |      |
| Overall Height           | A  | 0.90        | -   | 1.45 |
| Molded Package Thickness | A2 | 0.89        | -   | 1.30 |
| Standoff                 | A1 | -           | -   | 0.15 |
| Overall Width            | E  | 2.80 BSC    |     |      |
| Molded Package Width     | E1 | 1.60 BSC    |     |      |
| Overall Length           | D  | 2.90 BSC    |     |      |
| Foot Length              | L  | 0.30        | -   | 0.60 |
| Footprint                | L1 | 0.60 REF    |     |      |
| Foot Angle               | φ  | 0°          | -   | 10°  |
| Lead Thickness           | c  | 0.08        | -   | 0.26 |
| Lead Width               | b  | 0.20        | -   | 0.51 |


**Notes:**

- Dimensions D and E1 do not include mold flash or protrusions. Mold flash or protrusions shall not exceed 0.25mm per side.
- Dimensioning and tolerancing per ASME Y14.5M  
BSC: Basic Dimension. Theoretically exact value shown without tolerances.  
REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-091-OT Rev F Sheet 2 of 2

## 5-Lead Plastic Small Outline Transistor (OT) [SOT23]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

| Units                   |    | MILLIMETERS |      |      |
|-------------------------|----|-------------|------|------|
| Dimension Limits        |    | MIN         | NOM  | MAX  |
| Contact Pitch           | E  | 0.95 BSC    |      |      |
| Contact Pad Spacing     | C  |             | 2.80 |      |
| Contact Pad Width (X5)  | X  |             |      | 0.60 |
| Contact Pad Length (X5) | Y  |             |      | 1.10 |
| Distance Between Pads   | G  | 1.70        |      |      |
| Distance Between Pads   | GX | 0.35        |      |      |
| Overall Width           | Z  |             |      | 3.90 |

**Notes:**

1. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.


Microchip Technology Drawing No. C04-2091-OT Rev F



# 24AA08/24LC08B/24FC08

## 4-Lead Chip Scale Package (CS) - [CSP]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



| Units                   |        | MILLIMETERS |      |      |
|-------------------------|--------|-------------|------|------|
| Dimension               | Limits | MIN         | NOM  | MAX  |
| Number of Contacts      | N      |             | 4    |      |
| Adjacent Column X-Pitch | D1     | 0.400 BSC   |      |      |
| Adjacent Row Y-Pitch    | E1     | 0.900 BSC   |      |      |
| Overall Height          | A      | 0.47        | 0.51 | 0.55 |
| Die Height              | A2     | 0.33        | 0.35 | 0.37 |
| Bump Height             | A1     | 0.14        | 0.16 | 0.18 |
| Overall Width           | D      | NOTE 4      |      |      |
| Overall Length          | E      | NOTE 4      |      |      |
| Ball Diameter           | b      | 0.18        | 0.20 | 0.22 |


### Notes:

1. Orientation reference feature may vary, but must be located within the hatched area.
2. Package is saw singulated.
3. Dimensioning and tolerancing per ASME Y14.5M.  
BSC: Basic Dimension. Theoretically exact value shown without tolerances.  
REF: Reference Dimension, usually without tolerance, for information purposes only.
4. Package size varies with specific devices. Please see the specific Product Data Sheet.

Microchip Technology Drawing C04-6008A Sheet 2 of 2

## 4-Lead Chip Scale Package (CS) - [CSP]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

| Units                     |     | MILLIMETERS |      |     |
|---------------------------|-----|-------------|------|-----|
| Dimension Limits          |     | MIN         | NOM  | MAX |
| Number of Contacts        | N   | 4           |      |     |
| Contact Pad Spacing       | D1  |             | 0.40 |     |
| Contact Pad Spacing       | E1  |             | 0.90 |     |
| Contact Pad Diameter (X4) | ØX1 |             | 0.20 |     |
| Distance Between Pads     | G1  |             | 0.70 |     |
| Distance Between Pads     | G2  |             | 0.20 |     |

**Notes:**

1. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.

Microchip Technology Drawing No. C04-8008A

## APPENDIX A: REVISION HISTORY

### Revision M (03/2021)

Replaced terminology “Master” and “Slave” with “Host” and “Client” respectively. Changed “MUY” with “Q4B” part number for UDFN package. Updated TSSOP and UDFN package drawings. Added Automotive Product Identification System.

### Revision L (12/2019)

Added the 24FC08 device; Updated Package Drawings; Updated formatting throughout for clarification.

### Revision K (03/2012)

Added Chip Scale package; Revised Table 1-1, Table 2-1; Product Identification System.

### Revision J (02/2009)

Moved Pin Descriptions to Section 2.0, renumbered remaining sections. Added Figure 5-2.

### Revision H (03/2008)

Added TDFN package.

### Revision G (02/2007)

Replaced Package Drawings.

### Revision F (02/2007)

Updated Device Selection Table; Features section; Changed 1.8V to 1.7V throughout document; Revised Electrical Characteristics Ambient Temperature; Replaced Package Drawings; Revised Product ID System.

### Revision E (09/2005)

Revised Figure 3-1: Control Byte Allocation; Figure 4-1 Byte Write; Figure 4-2 Page Write; Section 6.0 Write Protection; Figure 7-1 Current Address Read; Figure 7-2 Random Read; Figure 7-3 Sequential Read; 8.3 Write-Protect (000-3FF).

### Revision D (02/2005)

Added DFN package.

### Revision C (12/2003)

Corrections to Section 1.0, Electrical Characteristics. Section 9.1, 24LC08B standard marking code.

## THE MICROCHIP WEBSITE

Microchip provides online support via our website at [www.microchip.com](http://www.microchip.com). This website is used as a means to make files and information easily available to customers. Accessible by using your favorite Internet browser, the website contains the following information:

- **Product Support** – Data sheets and errata, application notes and sample programs, design resources, user's guides and hardware support documents, latest software releases and archived software
- **General Technical Support** – Frequently Asked Questions (FAQ), technical support requests, online discussion groups, Microchip consultant program member listing
- **Business of Microchip** – Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

## CUSTOMER CHANGE NOTIFICATION SERVICE

Microchip's customer notification service helps keep customers current on Microchip products. Subscribers will receive e-mail notification whenever there are changes, updates, revisions or errata related to a specified product family or development tool of interest.

To register, access the Microchip website at [www.microchip.com](http://www.microchip.com). Under "Support", click on "Customer Change Notification" and follow the registration instructions.

## CUSTOMER SUPPORT

Users of Microchip products can receive assistance through several channels:

- Distributor or Representative
- Local Sales Office
- Field Application Engineer (FAE)
- Technical Support

Customers should contact their distributor, representative or Field Application Engineer (FAE) for support. Local sales offices are also available to help customers. A listing of sales offices and locations is included in the back of this document.

**Technical support is available through the website at: <http://microchip.com/support>**

## PRODUCT IDENTIFICATION SYSTEM (INDUSTRIAL)

To order or obtain information, e.g., on pricing or delivery, refer to the factory or the listed sales office.

| <u>PART NO.</u>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | <u>IXI</u> <sup>(1)</sup> | <u>-X</u>         | <u>/XX</u> |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|-------------------|------------|
| Device                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Tape and Reel Option      | Temperature Range | Package    |
| <b>Device:</b> 24AA08: = 1.7V, 8-Kbit I <sup>2</sup> C Serial EEPROM<br>24LC08B: = 2.5V, 8-Kbit I <sup>2</sup> C Serial EEPROM<br>24FC08: = 1.7V, High Speed, 8-Kbit I <sup>2</sup> C Serial EEPROM                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                           |                   |            |
| <b>Tape and Reel Option:</b> Blank = Standard packaging (tube or tray)<br>T = Tape and Reel <sup>(1)</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                           |                   |            |
| <b>Temperature Range:</b> I = -40°C to +85°C (Industrial)<br>E = -40°C to +125°C (Extended)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                           |                   |            |
| <b>Package:</b> MC = Plastic Dual Flat, No Lead Package – 2x3x0.9 mm Body, 8-lead (DFN)<br>MS = Plastic Micro Small Outline Package, 8-lead (MSOP)<br>P = Plastic Dual In-Line – 300 mil Body, 8-lead (PDIP)<br>SN = Plastic Small Outline - Narrow, 3.90 mm Body, 8-lead (SOIC)<br>OT = Plastic Small Outline Transistor, 5-lead (SOT-23) (Tape and Reel only)<br>MNY = Plastic Dual Flat, No Lead Package - 2x3x0.8 mm Body, 8-lead (TDFN)<br>ST = Plastic Thin Shrink Small Outline – 4.4 mm, 8-lead (TSSOP)<br>Q4B = Plastic Dual Flat, No Lead Package - 2x3x0.6 mm Body, 8-lead (UDFN)<br>CS16K <sup>(2)</sup> = Chip Scale, 4-lead (CSP)                                                                                                                                                                                    |                           |                   |            |
| <b>Examples:</b><br>a) 24AA08-I/P: Industrial Temperature, 1.7V, PDIP package.<br>b) 24AA08-I/SN: Industrial Temperature, 1.7V, SOIC package.<br>c) 24AA08T-I/OT: Tape and Reel, Industrial Temperature, 1.7V, SOT-23 package.<br>d) 24AA08T-I/CS16K: Tape and Reel, Industrial Temperature, 1.7V, Chip Scale package.<br>e) 24LC08B-I/P: Industrial Temperature, 2.5V, PDIP package.<br>f) 24LC08B-E/SN: Extended Temperature, 2.5V, SOIC package.<br>g) 24LC08BT-I/OT: Tape and Reel, Industrial Temperature, 2.5V, SOT-23 package.<br>h) 24AA08T-I/MNY: Tape and Reel, Industrial Temperature, 1.7V, TDFN package.<br>i) 24FC08-I/SN: Industrial Temperature, 1.7V, SOIC package.<br>j) 24FC08-E/ST: Extended Temperature, 1.7V, TSSOP package.<br>k) 24FC08T-I/Q4B: Tape and Reel, Industrial Temperature, 1.7V, UDFN package. |                           |                   |            |
| <b>Note 1:</b> Tape and Reel identifier only appears in the catalog part number description. This identifier is used for ordering purposes and is not printed on the device package. Check with your Microchip Sales Office for package availability with the Tape and Reel option.<br><br><b>2:</b> 16K indicates 160K technology.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                           |                   |            |

## PRODUCT IDENTIFICATION SYSTEM (AUTOMOTIVE)

To order or obtain information, e.g., on pricing or delivery, refer to the factory or the listed sales office.

| <u>PART NO.</u>                                                                                                                                                                                                                                                 | <u>IXI</u> <sup>(1)</sup> | <u>X</u>          | <u>XX</u> | <u>XXX</u> <sup>(2,3)</sup> | Examples: |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|-------------------|-----------|-----------------------------|-----------|
| Device                                                                                                                                                                                                                                                          | Tape and Reel Option      | Temperature Range | Package   | Variant                     |           |
| <b>Device:</b><br>24AA08: = 1.7V, 8Kbit I <sup>2</sup> C Serial EEPROM<br>24LC08B: = 2.5V, 8Kbit I <sup>2</sup> C Serial EEPROM                                                                                                                                 |                           |                   |           |                             |           |
| <b>Tape and Reel Option:</b><br>Blank = Standard packaging (tube or tray)<br>T = Tape and Reel <sup>(1)</sup>                                                                                                                                                   |                           |                   |           |                             |           |
| <b>Temperature Range:</b><br>I = -40°C to +85°C AEC-Q100 Grade 3<br>E = -40°C to +125°C AEC-Q100 Grade 1                                                                                                                                                        |                           |                   |           |                             |           |
| <b>Package:</b><br>OT = Plastic Small Outline Transistor, 5-Lead (SOT-23) (Tape and Reel Only)<br>SN = Plastic Small Outline – Narrow, 3.90 mm Body, 8-Lead (SOIC)<br>MS = Plastic Micro Small Outline Package, 8-Lead (MSOP)                                   |                           |                   |           |                             |           |
| <b>Variant<sup>(2,3)</sup>:</b><br>15KVAO =Standard Automotive, 15K Process <sup>(4)</sup><br>15KVXX =Customer-Specific Automotive, 15K Process <sup>(4)</sup><br>16KVAO =Standard Automotive, 16K Process<br>16KVXX =Customer-Specific Automotive, 16K Process |                           |                   |           |                             |           |

**Note 1:** Tape and Reel identifier only appears in the catalog part number description. This identifier is used for ordering purposes and is not printed on the device package. Check with your Microchip Sales Office for package availability with the Tape and Reel option.

**2:** The VAO/VXX automotive variants have been designed, manufactured, tested and qualified in accordance with AEC-Q100 requirements for automotive applications.

**3:** For customers requesting a PPAP, a customer-specific part number will be generated and provided. A PPAP is not provided for VAO part numbers.

**4:** Not recommended for new designs.

---

**Note the following details of the code protection feature on Microchip devices:**

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner and under normal conditions.
- There are dishonest and possibly illegal methods being used in attempts to breach the code protection features of the Microchip devices. We believe that these methods require using the Microchip products in a manner outside the operating specifications contained in Microchip's Data Sheets. Attempts to breach these code protection features, most likely, cannot be accomplished without violating Microchip's intellectual property rights.
- Microchip is willing to work with any customer who is concerned about the integrity of its code.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is "unbreakable." Code protection is constantly evolving. We at Microchip are committed to continuously improving the code protection features of our products. Attempts to break Microchip's code protection feature may be a violation of the Digital Millennium Copyright Act. If such acts allow unauthorized access to your software or other copyrighted work, you may have a right to sue for relief under that Act.

---

Information contained in this publication is provided for the sole purpose of designing with and using Microchip products. Information regarding device applications and the like is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications.

THIS INFORMATION IS PROVIDED BY MICROCHIP "AS IS". MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL OR CONSEQUENTIAL LOSS, DAMAGE, COST OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP'S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION. Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

**Trademarks**

The Microchip name and logo, the Microchip logo, Adaptec, AnyRate, AVR, AVR logo, AVR Freaks, BesTime, BitCloud, chipKIT, chipKIT logo, CryptoMemory, CryptoRF, dsPIC, FlashFlex, flexPWR, HELDO, IGLOO, JukeBlox, KeeLoq, Kleer, LANCheck, LinkMD, maXStylus, maXTouch, MediaLB, megaAVR, Microsemi, Microsemi logo, MOST, MOST logo, MPLAB, OptoLyzer, PackTime, PIC, picoPower, PICSTART, PIC32 logo, PolarFire, Prochip Designer, QTouch, SAM-BA, SenGenuity, SpyNIC, SST, SST Logo, SuperFlash, Symmetricom, SyncServer, Tachyon, TimeSource, tinyAVR, UNI/O, Vectron, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

AgileSwitch, APT, ClockWorks, The Embedded Control Solutions Company, EtherSynch, FlashTec, Hyper Speed Control, HyperLight Load, IntelliMOS, Libero, motorBench, mTouch, Powermite 3, Precision Edge, ProASIC, ProASIC Plus, ProASIC Plus logo, Quiet-Wire, SmartFusion, SyncWorld, Temux, TimeCesium, TimeHub, TimePictra, TimeProvider, WinPath, and ZL are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, Augmented Switching, BlueSky, BodyCom, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, Espresso T1S, EtherGREEN, IdealBridge, In-Circuit Serial Programming, ICSP, INICnet, Intelligent Paralleling, Inter-Chip Connectivity, JitterBlocker, maxCrypto, maxView, memBrain, Mindi, MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, RTAX, RTG4, SAM-ICE, Serial Quad I/O, simpleMAP, SimpliPHY, SmartBuffer, SMART-I.S., storClad, SQI, SuperSwitcher, SuperSwitcher II, Switchtec, SynchroPHY, Total Endurance, TSHARC, USBCheck, VariSense, VectorBlox, VeriPHY, ViewSpan, WiperLock, XpressConnect, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

The Adaptec logo, Frequency on Demand, Silicon Storage Technology, and Symmcom are registered trademarks of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2002-2021, Microchip Technology Incorporated, All Rights Reserved.

ISBN: 978-1-5224-7683-2

For information regarding Microchip's Quality Management Systems, please visit [www.microchip.com/quality](http://www.microchip.com/quality).

## Worldwide Sales and Service

### AMERICAS

**Corporate Office**  
2355 West Chandler Blvd.  
Chandler, AZ 85224-6199  
Tel: 480-792-7200  
Fax: 480-792-7277  
Technical Support:  
<http://www.microchip.com/support>  
Web Address:  
[www.microchip.com](http://www.microchip.com)

**Atlanta**  
Duluth, GA  
Tel: 678-957-9614  
Fax: 678-957-1455

**Austin, TX**  
Tel: 512-257-3370

**Boston**  
Westborough, MA  
Tel: 774-760-0087  
Fax: 774-760-0088

**Chicago**  
Itasca, IL  
Tel: 630-285-0071  
Fax: 630-285-0075

**Dallas**  
Addison, TX  
Tel: 972-818-7423  
Fax: 972-818-2924

**Detroit**  
Novi, MI  
Tel: 248-848-4000

**Houston, TX**  
Tel: 281-894-5983

**Indianapolis**  
Noblesville, IN  
Tel: 317-773-8323  
Fax: 317-773-5453  
Tel: 317-536-2380

**Los Angeles**  
Mission Viejo, CA  
Tel: 949-462-9523  
Fax: 949-462-9608  
Tel: 951-273-7800

**Raleigh, NC**  
Tel: 919-844-7510

**New York, NY**  
Tel: 631-435-6000

**San Jose, CA**  
Tel: 408-735-9110  
Tel: 408-436-4270

**Canada - Toronto**  
Tel: 905-695-1980  
Fax: 905-695-2078

### ASIA/PACIFIC

**Australia - Sydney**  
Tel: 61-2-9868-6733

**China - Beijing**  
Tel: 86-10-8569-7000

**China - Chengdu**  
Tel: 86-28-8665-5511

**China - Chongqing**  
Tel: 86-23-8980-9588

**China - Dongguan**  
Tel: 86-769-8702-9880

**China - Guangzhou**  
Tel: 86-20-8755-8029

**China - Hangzhou**  
Tel: 86-571-8792-8115

**China - Hong Kong SAR**  
Tel: 852-2943-5100

**China - Nanjing**  
Tel: 86-25-8473-2460

**China - Qingdao**  
Tel: 86-532-8502-7355

**China - Shanghai**  
Tel: 86-21-3326-8000

**China - Shenyang**  
Tel: 86-24-2334-2829

**China - Shenzhen**  
Tel: 86-755-8864-2200

**China - Suzhou**  
Tel: 86-186-6233-1526

**China - Wuhan**  
Tel: 86-27-5980-5300

**China - Xian**  
Tel: 86-29-8833-7252

**China - Xiamen**  
Tel: 86-592-2388138

**China - Zhuhai**  
Tel: 86-756-3210040

### ASIA/PACIFIC

**India - Bangalore**  
Tel: 91-80-3090-4444

**India - New Delhi**  
Tel: 91-11-4160-8631

**India - Pune**  
Tel: 91-20-4121-0141

**Japan - Osaka**  
Tel: 81-6-6152-7160

**Japan - Tokyo**  
Tel: 81-3-6880-3770

**Korea - Daegu**  
Tel: 82-53-744-4301

**Korea - Seoul**  
Tel: 82-2-554-7200

**Malaysia - Kuala Lumpur**  
Tel: 60-3-7651-7906

**Malaysia - Penang**  
Tel: 60-4-227-8870

**Philippines - Manila**  
Tel: 63-2-634-9065

**Singapore**  
Tel: 65-6334-8870

**Taiwan - Hsin Chu**  
Tel: 886-3-577-8366

**Taiwan - Kaohsiung**  
Tel: 886-7-213-7830

**Taiwan - Taipei**  
Tel: 886-2-2508-8600

**Thailand - Bangkok**  
Tel: 66-2-694-1351

**Vietnam - Ho Chi Minh**  
Tel: 84-28-5448-2100

### EUROPE

**Austria - Wels**  
Tel: 43-7242-2244-39  
Fax: 43-7242-2244-393

**Denmark - Copenhagen**  
Tel: 45-4485-5910  
Fax: 45-4485-2829

**Finland - Espoo**  
Tel: 358-9-4520-820

**France - Paris**  
Tel: 33-1-69-53-63-20  
Fax: 33-1-69-30-90-79

**Germany - Garching**  
Tel: 49-8931-9700

**Germany - Haan**  
Tel: 49-2129-3766400

**Germany - Heilbronn**  
Tel: 49-7131-72400

**Germany - Karlsruhe**  
Tel: 49-721-625370

**Germany - Munich**  
Tel: 49-89-627-144-0  
Fax: 49-89-627-144-44

**Germany - Rosenheim**  
Tel: 49-8031-354-560

**Israel - Ra'anana**  
Tel: 972-9-744-7705

**Italy - Milan**  
Tel: 39-0331-742611  
Fax: 39-0331-466781

**Italy - Padova**  
Tel: 39-049-7625286

**Netherlands - Drunen**  
Tel: 31-416-690399  
Fax: 31-416-690340

**Norway - Trondheim**  
Tel: 47-7288-4388

**Poland - Warsaw**  
Tel: 48-22-3325737

**Romania - Bucharest**  
Tel: 40-21-407-87-50

**Spain - Madrid**  
Tel: 34-91-708-08-90  
Fax: 34-91-708-08-91

**Sweden - Gothenberg**  
Tel: 46-31-704-60-40

**Sweden - Stockholm**  
Tel: 46-8-5090-4654

**UK - Wokingham**  
Tel: 44-118-921-5800  
Fax: 44-118-921-5820