

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Sealable No
Terminates To Printed Circuit Board
Hybrid Header No
Shielded Yes

Configuration Features

Number of Positions 4
Number of Rows 2
Number of Signal Positions 4

Electrical Characteristics

Nominal Voltage Architecture (V) 60
Operating Voltage (VAC) 40
Operating Voltage (VDC) 60

Body Features

Color White

Contact Features

Pin Diameter .6 mm [.023 in]
Interface Plating Gold (Au)

Termination Features

Termination Method Through Hole - Solder

Mechanical Attachment

Mounting Orientation Vertical/180°
Panel Mount Retention Without
PCB Mount Retention Type Solder Tails
Mounting Holes With
PCB Mount Alignment With
Locking Interface With
PCB Mount Retention With

Housing Features

Centerline (Pitch) (in) .078
Pitch (mm) 2

Dimensions

Profile Height from PCB 15.5 mm [.61 in]
Width 14.15 mm [.557 in]
PCB Thickness (Recommended) 1.6 mm [.063 in]
Length 12 mm [.472 in]

Usage Conditions

Operating Temperature Range -40 – 105 °C [-40 – 221 °F]
Operating Temperature (Max) (°C) 65, 70, 75, 80, 85, 90, 100, 105
Operating Temperature (Max) (°F) 149, 158, 167, 176, 185, 194, 212, 221

Operation/Application

Circuit Application Signal

Industry Standards

UL Flammability Rating UL 94V-0
Degree of Protection other

Packaging Features

Packaging Type Tape & Reel
Packaging Quantity 800

Statement of Compliance

Statement of Compliance
PDF