

1376357-8 Product Details



0.025 Series and Hybrid Connectors and Contacts

025/090 26POS CAP ASSY H SELECTIVE-TIN

1376357-8

TE Internal Number: 1376357-8

Active

View 3D PDF

Product Highlights

View All

- Product Series = 025/090
- Wire-to-Board
- Applies To Printed Circuit Board
- Connector
- Connector Assembly

Share

Print

Email

Pricing & Availability

Request Sample

Add to My Part List

Buy Product through Distributor

Feedback

Please Note:
Use the Product Drawing for all design activity

Product Type Features	
Product Series	025/090
Product Type	Connector
Connector Type	Connector Assembly
PCB Mounting Orientation	Right Angle
PCB Mount Retention	With
PCB Mount Retention Type	Tapping Screw
Sealed	No
PCB Mount Alignment	With
PCB Mount Alignment Type	Mounting Holes
Mechanical Attachment	
Contact Retention	Without
Mating Retention Type	Latch(ing)
Panel Mount Retention	Without
Electrical Characteristics	
Operating Voltage Reference	DC
Operating Voltage (VDC)	12
Termination Features	
Termination Method to Wire/Cable	Solder
Termination Method to PC Board	Through Hole - Solder
Dimensions	
Tab Width (mm [in])	0.64 [0.025], 2.3 [0.091]
Tail Length (mm [in])	4 [0.157]
PCB Thickness, Recommended (mm [in])	0.50 – 1.20 [0.0197 – 0.047], 1.60 – 2.00 [0.063 – 0.079]
Length (X-Axis) (mm [in])	19.50 [0.767]
Width (Z-Axis) (mm [in])	42.50 [1.6732]
Profile Height (Y-Axis) (mm [in])	17.60 [0.6929]
Body Features	
Mating Retention	With
Contact Features	
Contact Type	Tab
Multiple Contact Types	With
Contact Base Material	Brass
Contact Mating Area Plating (Signal)	Selective Tin
Contact Mating Area Plating (Power)	Selective Tin
Contact Plating, Termination Area, Material	Selective Tin
Contact Plating, Termination Area, Thickness (µm [µin])	2.5 [98.42]
Underplate Material	Nickel
Underplate Material Thickness (µm [µin])	0.80 – 1.50 [31.496 – 59.055]
Shunts/Shorting Bars	Without
Housing Features	
Connector Style	Receptacle
Housing Material	SPS
Housing Color	Natural
Mating Alignment	With
Mating Alignment Type	Polarization
Configuration Features	
Number of Positions	26
Number of Sections	1
Number of Positions/Section	20+6
Number of Rows	2
Strain Relief	Without
GET 0.64 Connector System	No
Industry Standards	
RoHS/ELV Compliance	RoHS compliant, ELV compliant
Lead Free Solder Processes	Wave solder capable to 240°C
RoHS/ELV Compliance History	Always was RoHS compliant
Environmental	
Operating Temperature (°C [°F])	-30 – +105 [-22 – +221]
Conditions for Usage	
Applies To	Printed Circuit Board
For Use With	Plug: 1376360
Operation/Application	
Application Use	Wire-to-Board
Contact Transmits (Typical Application)	Signal (Data)/Power
Packaging Features	
Packaging Method	Tube, Paper Box
Packaging Quantity	10
Other	
Brand	AMP

Related Products

Not quite the product you're looking for?

Find Similar Products

View Part in Product Feature Selector

Check for Tooling