

Customer View Model

3D\_IGS.ZIP

English

Customer View Model

3D\_STP.ZIP

English

Product Specifications

Application Specification

Flexible Flat Cable (FFC) Housings With Contact Cavities On 2.54-Mm (.100-In.) Centerline Spacing

PDF

English

Product Specification

Connector, Flexible Flat Conductor Cable, .100 Inch Centerline

PDF

English

Instruction Sheets

Instruction Sheet (U.S.)

Extraction Tools

PDF

English

Extraction Tools

TIF

English

Extraction Tool For Flexible Flat Cable (FFC)

PDF

English

Extraction Tool For Flexible Flat Cable (FFC)

TIF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Type Housing

Connector Style Receptacle

Connector System Wire-to-Board

Row-to-Row Spacing 2.54 mm [ .1 in ]

Connector & Contact Terminates To Wire & Cable

Type of Connector Standard

Wire/Cable Type FFC

Product Type Connector

Configuration Features

Number of Positions 20  
Number of Rows 2

Electrical Characteristics

Dielectric Withstanding Voltage (VAC) 720  
Insulation Resistance (MΩ) 5000  
Voltage 300 VAC

Body Features

Color Black

Contact Features

Contact Type Socket

Mechanical Attachment

Panel Mount Feature Type Mounting Ears  
Mating Connector Lock Type Detent Windows  
Mating Connector Lock With  
Mating Alignment With  
Panel Mount Feature With  
Mating Retention With  
Mating Alignment Type Polarization

Housing Features

Centerline (Pitch) 2.54 mm [ .1 in ]  
Housing Color Black  
Housing Material Nylon

Usage Conditions

Operating Temperature Range (°C) -65 – 105  
Flame Retardant Yes

Industry Standards

UL Flammability Rating UL 94V-0

Packaging Features

Packaging Method Package  
Packaging Quantity 1

Other

Comment Use Extraction Tool No. 91093-1 for round wire contacts.

PRODUCT COMPLIANCE



Statement of Compliance

**Statement of Compliance**

PDF

---