

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

Product Specifications

Product Specification

ET**AMP Superseal 1,5 SRS Connectors

PDF

English

Qualification Test Report

AMP Superseal 1.5 Series

TIF

English

AMP Superseal 1.5 Series

PDF

English

Instruction Sheets

Customer Manual (non U.S.)

AMP SUPERSEAL 1.5 SERIES

TIF

English

AMP SUPERSEAL 1.5 SERIES

PDF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

- Connector Style Housing for female terminals
- Connector System Wire-to-Board, Wire-to-Device, Wire-to-Wire
- Sealable No
- Hybrid Connector No
- Primary Locking Feature Integrated in Housing
- Strain Relief No

Configuration Features

- Number of Positions 2
- Number of Rows 1

Electrical Characteristics

Nominal Voltage Architecture (V) 12, 24
Operating Voltage (VDC) 24

Body Features

Color Gray
Cable Exit Angle 180°
Body Material PA GF

Contact Features

Mating Tab Width 1.5 mm [.059 in]

Mechanical Attachment

Mounting Feature No
Terminal Position Assurance Yes
Polarized Yes

Housing Features

Centerline (Pitch) 6 mm [.236 in]

Dimensions

Width 13.8 mm [.543 in]
Height 42 mm [1.654 in]
Length 19.8 mm [.78 in]

Usage Conditions

Operating Temperature Range -40 – 125 °C [-40 – 257 °F]

Operation/Application

Circuit Application Signal

Industry Standards

Degree of Protection IP67, Other

Packaging Features

Packaging Method Box
Packaging Quantity 1500

Other

Connector Position Assurance Capable No
Customer GEN
Serviceable Yes

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF
