

Power Matters.™

[Home](#) ▶ [2N5334 \(#23360\)](#)

Products

- ▶ [Product Directory](#)
- ▶ [Applications](#)
- ▶ [Parametric Search](#)

2N5334 (#23360)

Product Status

■ Obsolete

Related Links

- [Technical support](#)
- [How to Buy](#)
- [Available Stock](#)
- [Sales Contacts](#)

Overview

Diagrams

Electrical Rating	Symbol	Min	Typ	Max	Unit
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$			0.70	V
DC Current Gain	HFE	30.00		150.00	

Maximum Electrical Rating	Symbol	Min	Typ	Max	Unit
Breakdown Voltage, Collector-Base (Emitter Open)	$V_{BR(CBO)}$			60.00	V
Collector Current (dc)	I_C			3.00	A
Collector-Emitter Voltage (Base Open)	V_{CEO}			60.00	V
Emitter-Base Voltage (Collector Open)	V_{EBO}			8.00	V
Power Dissipation, Total	P_T			6.00	W

This part can be found in the following product categories:

- ▶ [Power Discretes & Modules](#) ▶ [BJT\(BiPolar Junction Transistor\)](#) ▶ [PNP Transistor](#)