THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION – ,– .
© COPYRIGHT – By – ALL RIGHTS RESERVED.

LOC	DIST
AD	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	–	SEE SHEET 1	–	–	–

1. .000030 GOLD IN LOCALIZED PLATE AREA, .000150 TIN–LEAD ON SOLDER TAILS ALL OVER .000050 NICKEL.
2. USE .0465±.0010 DRILLED HOLE (#56 DRILL) WITH .001 MIN COPPER.
3. CIRCUIT IDENTIFICATION FEATURE OMITTED ON 10 POSITION HEADER ASSEMBLIES.
4. DIMENSION APPLIES AT BASE OF SHROUD.
5. THE NOTED DIMENSIONS APPLY AT THE MATING FACE OF THE HOUSING.
6. (Y3) (Y4) ARE LOCATED THE SAME AS (Y1) (Y2) EXCEPT ON OPPOSITE SIDE OF HOUSING.
7. PADS ON THE OPPOSITE SIDE OF THE BOARD TO BE ø.065 MINIMUM.
8. REFER TO NO. OF POSN. IN CHART FOR NUMBER OF SURFACES THAT ARE TO BE COPLALAR.
9. .000030 GOLD IN LOCALIZED PLATE AREA, .000150 TIN ON SOLDER TAILS, ALL OVER .000050 NICKEL.
10. NO CIRCUIT IDENTIFICATION FEATURE ON 10,12,20,24 AND 30 POSITION PARTS.
11. FINISH: .000001 MIN. GOLD GOLD PLATED AREA, .000150–.000250 MATTE TIN LEAD ON TIN PLATE AREA, UNDER PLATING SHOULD BE .000050–.000100 NICKEL ON ENTIRE CONTACT, GOLD AND TIN PLATING MAY NOT OVERLAP.
12. FINISH: .000001 MIN GOLD ON GOLD PLATED AREA, .000150–.000250 MATTE TIN ON TIN PLATE AREA, UNDERPLATING TO BE .000050–.000100 NICKEL ON ENTIRE CONTACT, GOLD AND TIN PLATING MAY NOT OVERLAP.
13. PRELIMINARY – NOT FOR PRODUCTION
14. OBSOLETE

12	–	–	–	.000	.250	5	.430	12	13 8–104549–1
	–	.000	1.150	1.150	2.450	49	2.630	100	8–104549–0
	–	.000	.900	.900	1.950	39	2.130	80	13 7–104549–9
	–	.000	.650	.650	1.450	29	1.630	60	13 7–104549–8
	–	.025	.525	.525	1.200	24	1.380	50	13 7–104549–7
	–	–	.400	.400	.950	19	1.130	40	13 7–104549–6
	–	–	.275	.275	.700	14	.880	30	7–104549–5
	–	–	.225	.225	.600	12	.780	26	13 7–104549–4
	–	–	.200	.200	.550	11	.730	24	13 7–104549–3
	–	–	.150	.150	.450	9	.630	20	13 7–104549–2
	.494	–	–	.025	.200	4	–	10	13 7–104549–1
9	–	–	–	.000	.250	5	.430	12	6–104549–1
	–	.000	1.150	1.150	2.450	49	2.630	100	6–104549–0
	–	.000	.900	.900	1.950	39	2.130	80	5–104549–9
	–	.000	.650	.650	1.450	29	1.630	60	5–104549–8
	–	.025	.525	.525	1.200	24	1.380	50	5–104549–7
	–	–	.400	.400	.950	19	1.130	40	5–104549–6
	–	–	.275	.275	.700	14	.880	30	5–104549–5
	–	–	.225	.225	.600	12	.780	26	14 ~~5–104549–4~~
	–	–	.200	.200	.550	11	.730	24	5–104549–3
	–	–	.150	.150	.450	9	.630	20	5–104549–2
	.494	–	–	.025	.200	4	–	10	5–104549–1
FINISH	G	F	E	D	C	B	A	NO OF POSN	PART NUMBER

11	–	–	–	.000	.250	5	.430	12	13 3–104549–1
	–	.000	1.150	1.150	2.450	49	2.630	100	13 3–104549–0
	–	.000	.900	.900	1.950	39	2.130	80	13 2–104549–9
	–	.000	.650	.650	1.450	29	1.630	60	13 2–104549–8
	–	.025	.525	.525	1.200	24	1.380	50	2–104549–7
	–	–	.400	.400	.950	19	1.130	40	13 2–104549–6
	–	–	.275	.275	.700	14	.880	30	13 2–104549–5
	–	–	.225	.225	.600	12	.780	26	13 2–104549–4
	–	–	.200	.200	.550	11	.730	24	13 2–104549–3
	–	–	.150	.150	.450	9	.630	20	13 2–104549–2
	.494	–	–	.025	.200	4	–	10	13 2–104549–1
1	–	–	–	.000	.250	5	.430	12	1–104549–1
	–	.000	1.150	1.150	2.450	49	2.630	100	1–104549–0
	–	.000	.900	.900	1.950	39	2.130	80	104549–9
	–	.000	.650	.650	1.450	29	1.630	60	104549–8
	–	.025	.525	.525	1.200	24	1.380	50	104549–7
	–	–	.400	.400	.950	19	1.130	40	104549–6
	–	–	.275	.275	.700	14	.880	30	104549–5
	–	–	.225	.225	.600	12	.780	26	14 ~~104549–4~~
	–	–	.200	.200	.550	11	.730	24	104549–3
	–	–	.150	.150	.450	9	.630	20	104549–2
	.494	–	–	.025	.200	4	–	10	104549–1
FINISH	G	F	E	D	C	B	A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± .005
4 PLC ± –
ANGLES ± –

MATERIAL: HOUSING: PPA, COLOR: BLACK, CONTACT: COPPER ALLOY
FINISH: SEE TABLE

DWN 13JUL92 R.K. SEIFRIED/UTA
CHK 23OCT92 B ELICKER
APVD 23OCT92 B ELICKER
PRODUCT SPEC –
APPLICATION SPEC –
WEIGHT –

TE Connectivity

NAME: HEADER ASSEMBLY, W/SIDE & END LATCHES, VERTICAL, SHROUDED, DOUBLE ROW,SURFACE MOUNT, AMPMODU System 50, W/HOLDDOWNS

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	00779	C–104549	–

CUSTOMER DRAWING | SCALE 4:1 | SHEET 2 OF 2 | REV U

4805 (3/11)

Downloaded from Arrow.com.