

3D\_IGS.ZIP  
English

Customer View Model  
3D\_STP.ZIP  
English

Product Specifications  
Product Specification

UNSEALD GET/MCP 81P/40P SLIDELEVER TYPE CONNECTORS PLUG HOUSING ASSEMBLY  
TIF  
Japanese

UNSEALD GET/MCP 81P/40P SLIDELEVER TYPE CONNECTORS PLUG HOUSING ASSEMBLY  
PDF  
Japanese

MQS CLEAN BODY PLUG ASSY 81P & 40P  
PDF  
Japanese

MQS CLEAN BODY PLUG ASSY 81P & 40P  
TIF  
Japanese

SEALED MQS/JPT 81P/40P SLIDE LEVER TYPE CONNECTOR  
PDF  
English  
Application Specification

Junior Power Timer  
PDF  
English

MICRO QUADLOCK SYSTEM  
PDF  
English  
Qualification Test Report

SEALED MQS/JPT 81P/40P SLIDE LEVER TYPE CONNECTORS  
PDF  
Japanese

SEALED MQS/JPT 81P/40P SLIDE LEVER TYPE CONNECTORS  
TIF  
Japanese

UNSEALED GET/MCP 81P/40P SLIDELEVER TYPE CONNECTOR  
TIF  
Japanese

UNSEALED GET/MCP 81P/40P SLIDELEVER TYPE CONNECTOR  
PDF  
Japanese

Instruction Sheets  
Instruction Sheet (non U.S.)

Sealed MQS/JST 81/40pos Connector

PDF  
Japanese

Sealed MQS/JST 81/40pos Connector

PDF  
Japanese

UNSEALED GET/MCP 81/40 SLIDER LEVER TYPE CONNECTOR

TIF  
Japanese

UNSEALED GET/MCP 81/40 SLIDER LEVER TYPE CONNECTOR

PDF  
Japanese

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

**Connector System** Wire-to-Board, Wire-to-Component  
**Accessory Type** Cover Assembly  
**Strain Relief** With  
**Sealed** Yes

Configuration Features

**Number of Positions** 81

Body Features

**Cable Exit Angle** 90 (Right Angle)  
**Color** Black  
**Material** PBT GF

Usage Conditions

**Operating Temperature (Max) (°C)** 85, 90, 100, 105, 110, 120  
**Operating Temperature (Max) (°F)** 185, 194, 212, 221, 230, 248  
**Operating Temperature Range** -40 – 120 °C [ -40 – 248 °F ]

Packaging Features

**Packaging Method** Bag  
**Packaging Quantity** 70

Statement of Compliance

Statement of Compliance

PDF