

ATC 100 B Capacitance Values

CAP. CODE	CAP. (pF)	TOL.	RATED WVDC STD.	EXT.	CAP. CODE	CAP. (pF)	TOL.	RATED WVDC STD.	EXT.	CAP. CODE	CAP. (pF)	TOL.	RATED WVDC STD.	EXT.	CAP. CODE	CAP. (pF)	TOL.	RATED WVDC STD.	EXT.
0R1	0.1	B			2R4	2.4				200	20				151	150			
0R2	0.2				2R7	2.7				220	22				161	160			
0R3	0.3	B, C			3R0	3.0				240	24				181	180		300	1000
0R4	0.4				3R3	3.3				270	27				201	200			
0R5	0.5				3R6	3.6				300	30				221	220			
0R6	0.6				3R9	3.9	B, C, D			330	33				241	240			
0R7	0.7				4R3	4.3				360	36				271	270			
0R8	0.8				4R7	4.7				390	39				301	300			
0R9	0.9				5R1	5.1				430	43				331	330		200	600
1R0	1.0				5R6	5.6				470	47		500	1500	361	360			
1R1	1.1	B, C, D	500	1500	6R2	6.2		500	1500	510	51	F, G, J, K, M			391	390			
1R2	1.2				6R8	6.8				560	56				431	430			
1R3	1.3				7R5	7.5	B, C, J, K, M			620	62				471	470			
1R4	1.4				8R2	8.2				680	68				511	510		100	
1R5	1.5				9R1	9.1				750	75				561	560			
1R6	1.6				100	10				820	82				621	620			
1R7	1.7				110	11				910	91				681	680			
1R8	1.8				120	12				101	100				751	750			
1R9	1.9				130	13	F, G, J, K, M			111	110				821	820		50	300
2R0	2.0				150	15				121	120		300	1000	911	910			
2R1	2.1				160	16				131	130				102	1000			
2R2	2.2				180	18													

VRMS = 0.707 X WVDC

• SPECIAL VALUES, TOLERANCES, HIGHER WVDC AND MATCHING AVAILABLE. PLEASE CONSULT FACTORY.
NOTE: EXTENDED WVDC DOES NOT APPLY TO CDR PRODUCTS.

ATC PART NUMBER CODE

Series ATC100 B 91 0 J W 500 X T Packaging

Case Size _____

Capacitance Code: _____
First 2 significant digits for capacitance.
R=Decimal Point

Indicates number of zeros following digits of capacitance in picofarads except for decimal values.

Capacitance Tolerance _____

T - Tape and Reel, 1000 pc. qty.*
TV - Vertical Orientation of Product, Tape and Reel, 1000 pc. qty.*
I - Special Packaging. Consult Factory.
*Consult ATC for other quantities
ATC Cap-Pac® packaging (100 pc. qty. std.) is also available.
For this option, leave last field blank.

Laser Marking
WVDC
Termination Code

CAPACITANCE TOLERANCE								
Code	B	C	D	F	G	J	K	M
Tol.	±0.1 pF	±0.25 pF	±0.5 pF	±1%	±2%	±5%	±10%	±20%

The above part number refers to a 100 B Series (case size B) 91 pF capacitor, J tolerance (±5%), 500 WVDC, with W termination (Tin /Lead, Solder Plated over Nickel Barrier), laser marking and Tape and Reel packaging.

ATC accepts orders for our parts using designations **with** or **without** the "ATC" prefix. Both methods of defining the part number are equivalent, i.e., part numbers referenced with the "ATC" prefix are interchangeable to parts referenced without the "ATC" prefix. Customers are free to use either in specifying or procuring parts from American Technical Ceramics.

For additional information and catalogs contact your ATC representative or call direct at (+1-631) 622-4700.

Consult factory for additional performance data.








A M E R I C A N T E C H N I C A L C E R A M I C S

ATC North America
sales@atceramics.com

ATC Europe
sales@atceramics.com

ATC Asia
sales@atceramics-asia.com

ATC 100 B Capacitors: Mechanical Configurations

ATC SERIES & CASE SIZE	ATC TERM. CODE	MIL-PRF- 55681	CASE SIZE & TYPE	OUTLINES W/T IS A TERMINATION SURFACE	BODY DIMENSIONS INCHES (mm)			LEAD AND TERMINATION DIMENSIONS AND MATERIALS			
					LENGTH (L)	WIDTH (W)	THICKNESS (T)	OVERLAP (Y)	MATERIALS		
100B	W	CDR14BG	B  Solder Plate.1		.110 +.020 -.010 (2.79 +0.51 -0.25)	.110 ±.015 (2.79 ±0.38)	.102 (2.59) max.	.015 (0.38) ±.010 (0.25)	Tin /Lead, Solder Plated over Nickel Barrier Termination		
100B	P	CDR14BG	B  Pellet		.110 +.035 -.010 (2.79 +0.89 -0.25)	.110 ±.015 (2.79 ±0.38)			Heavy Tin/Lead Coated, over Nickel Barrier Termination		
100B	T	N/A	B  Solderable Nickel Barrier		.110 +.020 -.010 (2.79 +0.51 -0.25)	.110 ±.015 (2.79 ±0.38)			RoHS Compliant Tin Plated over Nickel Barrier Termination		
100B	CA	CDR13BG	B  Gold Chip		.110 ±0. 15 020 -.010 (2.79 +0.51 -0.25)	.110 ±.015 (2.79 ±0.38)			RoHS Compliant Gold Plated over Nickel Barrier Termination		
100B	MS	CDR21BG	B  Microstrip		.135 ±.015 (3.43 ±0.38)	.110 ±.015 (2.79 ±0.38)	.120 (3.05) max.	N/A	Length (L _L)	Width (W _L)	Thickness (T _L)
100B	AR	CDR22BG	B  Axial Ribbon				.250 (6.35) min.		.093 ±.005 (2.36 ±0.13)	.004 ±.001 (.102 ±.025)	
100B	RR	CDR24BG	B  Radial Ribbon				.102 (2.59) max.				
100B	RW	CDR23BG	B  Radial Wire		.145 ±.020 (3.68 ±0.51)				.500 (12.7)in. min.	#26 AWG., .016 (.406) dia. nominal	
100B	AW	CDR25BG	B  Axial Wire								

Additional lead styles available: Narrow Microstrip (NM), Narrow Axial Ribbon (NA) and Vertical Narrow Microstrip (H). Other lead lengths are available; consult factory. All leads are high purity silver attached with high temperature solder and are **RoHS** compliant. For a complete military catalog, request American Technical Ceramics document ATC 001-818.








A M E R I C A N T E C H N I C A L C E R A M I C S

ATC North America
sales@atceramics.com

ATC Europe
sales@atceramics.com

ATC Asia
sales@atceramics-asia.com

ATC 100 B Non-Magnetic Capacitors: Mechanical Configurations

ATC SERIES & CASE SIZE	ATC TERM. CODE	MIL-PRF- 55681	CASE SIZE & TYPE	OUTLINES W/T IS A TERMINATION SURFACE	BODY DIMENSIONS INCHES (mm)			LEAD AND TERMINATION DIMENSIONS AND MATERIALS				
					LENGTH (L)	WIDTH (W)	THICKNESS (T)	OVERLAP (Y)	MATERIALS			
100B	WN	Meets Require- ments	B  Non-Mag Solder Plate		.110 +.025 -.010 (2.79 +0.64 -0.25)	.110 ±.015 (2.79 ±0.38)	.102 (2.59) max	.015 (0.38) ±.010 (0.25)	Tin/Lead, Solder Plated over Non-Magnetic Barrier Termination			
100B	PN	Meets Require- ments	B  Non-Mag Pellet		.110 +.035 -.010 (2.79 +0.89 -0.25)	.110 ±.015 (2.79 ±0.38)			Heavy Tin/Lead Coated, over Non-Magnetic Barrier Termination			
100B	TN	Meets Require- ments	B  Non-Mag Solderable Barrier		.110 +.025 -.010 (2.79 +0.64 -0.25)	.110 ±.015 (2.79 ±0.38)			RoHS Compliant Tin Plated over Non-Magnetic Barrier Termination			
100B	MN	Meets Require- ments	B  Non-Mag Microstrip		.135 ±.015 (3.43 ±0.38)	.110 ±.015 (2.79 ±0.38)	.120 (3.05) max.	N/A	Length (L _L)	Width (W _L)	Thickness (T _L)	
100B	AN	Meets Require- ments	B  Non-Mag Axial Ribbon				.250 (6.35) min		.093 ±.005 (2.36 ±0.13)	.004 ±.001 (.102 ±.025)		
100B	FN	Meets Require- ments	B  Non-Mag Radial Ribbon									
100B	RN	Meets Require- ments	B  Non-Mag Radial Wire		.145 ±.020 (3.68 ±0.51)				.500 (12.7) in. min.	#26 AWG., .016 (.406) dia. nominal		
100B	BN	Meets Require- ments	B  Non-Mag Axial Wire									

Additional lead styles available: Narrow Microstrip (DN), Narrow Axial Ribbon (GN) and Vertical Narrow Microstrip (HN). Other lead lengths are available; consult factory. All leads are high purity silver attached with high temperature solder and are **RoHS** compliant.

Suggested Mounting Pad Dimensions

Case B Vertical Mount						
Cap Value	Pad Size	A Min.	B Min.	C Min.	D Min.	
0.1 pF	Normal	.065	.050	.075	.175	
	High Density	.045	.030	.075	.135	
0.2 pF	Normal	.090	.050	.075	.175	
	High Density	.070	.030	.075	.135	
0.3 to 510 pF	Normal	.110	.050	.075	.175	
	High Density	.090	.030	.075	.135	
> 510 pF	Normal	.120	.050	.075	.175	
	High Density	.100	.030	.075	.135	
Horizontal Mount						
All values	Normal	.130	.050	.075	.175	
	High Density	.110	.030	.075	.135	

AMERICAN TECHNICAL CERAMICS


ATC North America
sales@atceramics.com

ATC Europe
saleseur@atceramics.com


ATC Asia
sales@atceramics-asia.com

ATC 100 B Performance Data


ESR VS. CAPACITANCE
ATC SERIES 100, CASE B




Q VS. CAPACITANCE
ATC SERIES 100, CASE B




ESR VS. CAPACITANCE
ATC SERIES 100, CASE B




Q VS. CAPACITANCE
ATC SERIES 100, CASE B



SERIES RESONANCE VS. CAPACITANCE
ATC SERIES 100, CASE B



CAPACITANCE CHANGE VS. TEMPERATURE
ATC SERIES 100, CASE B



A M E R I C A N T E C H N I C A L C E R A M I C S


ATC North America
sales@atceramics.com

ATC Europe
sales@atceramics.com


ATC Asia
sales@atceramics-asia.com

ATC 100 B Performance Data


**CURRENT RATING VS. CAPACITANCE
ATC SERIES 100, CASE B**



**CURRENT RATING VS. CAPACITANCE
ATC SERIES 100, CASE B**



**CURRENT RATING VS. CAPACITANCE
ATC SERIES 100, CASE B, EXTENDED VOLTAGE**



Sales of ATC products are subject to the terms and conditions contained in American Technical Ceramics Corp. Terms and Conditions of Sale (ATC document #001-992). Copies of these terms and conditions will be provided upon request. They may also be viewed on ATC's website at www.atceramics.com/productfinder/default.asp. Click on the link for Terms and Conditions of Sale.

ATC has made every effort to have this information as accurate as possible. However, no responsibility is assumed by ATC for its use, nor for any infringements of rights of third parties which may result from its use. ATC reserves the right to revise the content or modify its product without prior notice.

© 1996 American Technical Ceramics Corp. All Rights Reserved

ATC # 001-807 Rev. S, 8/18



AMERICAN

ATC North America
sales@atceramics.com

TECHNICAL

ATC Europe
sales@atceramics.com

CERAMICS

ATC Asia
sales@atceramics-asia.com



THE
ENGINEERS'
CHOICE®

ISO 9001 REGISTERED
COMPANY

THE ENGINEERS' CHOICE®

www.atceramics.com