

#### **Temperature Rerating Curve**



#### Note:

1. Rerating depicted in this curve is in addition to the standard derating of 25% for continuous operation.

#### Example:

- For continuous operation at 70 degrees celsius, the fuse should be derated as follows:  $I = (0.75) (0.80) I_{RAT} = (0.60) I_{RAT}$
- The temperature derating curve represents the nominal conditions. For questions about temperature derating curve, please consult Littelfuse technical support for assistance.

#### **Soldering Parameters**

Reflow Condition		Pb – Free assembly
Pre Heat	-Temperature Min (T <sub>s(min)</sub> )	150°C
	-Temperature Max (T <sub>s(max)</sub> )	200°C
	-Time (Min to Max) (t <sub>s</sub> )	60 – 180 secs
Average ramp up rate (LiquidusTemp $(T_L)$ to peak		5°C/second max
$T_{S(max)}$ to $T_L$ - Ramp-up Rate		5°C/second max
Reflow	-Temperature (T <sub>L</sub> ) (Liquidus)	217°C
	-Temperature (t <sub>L</sub> )	60 – 150 seconds
PeakTemperature (T <sub>P</sub> )		250 <sup>+0/-5</sup> °C
Time within 5°C of actual peak Temperature (t <sub>p</sub> )		20 – 40 seconds
Ramp-down Rate		5°C/second max
Time 25°C to peak Temperature (T <sub>P</sub> )		8 minutes Max.
Do not exceed		260°C

Wave Soldering260°C, 10 seconds max.



#### **Average Time Current Curves**





### **Product Characteristics**

Materials	<b>Body:</b> Advanced High Temperature Substrate <b>Terminations:</b> 100% Tin over Nickel over Copper <b>Element Cover Coat:</b> Conformal Coating
Operating Temperature	<ul> <li>– 55°C to 90°C. Consult temperature re-rating curve chart. For operation above 90°C contact Littelfuse.</li> </ul>
Humidity	MIL-STD-202, Method 103, Condition D

#### Dimensions



Packaging					
Packaging Option	Packaging Specification	Quantity	Quantity & Packaging Code		
8mm Tape and Reel	EIA-481 Rev. D (IEC 60286, part 3)	5000	NR		

Thermal Shock	Withstands 5 cycles of – 55°C to 125°C
Vibration	Per MIL-STD-202
Insulation Resistance (After Opening)	Greater than 10,000 ohms.
Resistance to Soldering Heat	MIL-STD-202, Method 210, Condition D

#### **Part Marking System**

Amp Code	Marking Code
.250	D
.375	E
.500	F
.750	G
001.	н
1.25	J
01.5	К
1.75	L

Amp Code	Marking Code
002.	N
02.5	0
003.	Р
03.5	R
004.	S
005.	Т

### Part Numbering System

## 0467002.NRHF

# SERIES ———

### AMP Code

The dot is poisitioned before the Packaging Suffix with whole ratings and within the numbering sequence for fractional ratings. Refer to Amp Code column in the Electrical Specifications table.

PACKAGING Code —

NR = Tape and Reel, 5000 pcs

#### 'HF' SUFFIX HALOGEN FREE ITEM

Example:

1.5 amp product is 0467<u>01.5</u>NRHF (2 amp product shown above).

**Disclaimer Notice** - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littlefuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at: <u>www.littlefuse.com/disclaimer-electronics</u>.