

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

Product Specifications

Product Specification

040II/070II Hybrid I/O Connector MK-II For Wire-TO-Board Termination

PDF

Japanese

Qualification Test Report

040II/070II Hybrid I/O Connector MK-II For Wire-TO-Board Termination

PDF

Japanese

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

- Connector System Wire-to-Wire
- Sealable No
- Hybrid Connector No
- Strain Relief No
- Row-to-Row Spacing 5.2 mm [.205 in]

Configuration Features

- Number of Positions 10
- Number of Rows 2

Body Features

- Color Gray
- Body Material PBT GF

Contact Features

- Mating Tab Width 1 mm [.039 in]

Mechanical Attachment

- Mounting Feature No
- Terminal Position Assurance No
- Polarized Yes

Housing Features

Centerline (Pitch) 2.5 mm [.098 in]

Dimensions

Width 18.4 mm [.724 in]

Height 21 mm [.8268 in]

Length 14 mm [.551 in]

Usage Conditions

Operating Temperature Range -30 – 105 °C [-22 – 221 °F]

Operation/Application

Circuit Application Signal

Packaging Features

Packaging Method Package

Packaging Quantity 100

Other

Connector Position Assurance Capable No

Serviceable No

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF