

Moisture Sensitivity Level (MSL)	3
Floor Life	168 HOURS
Peak Package Body Temperature (PPT)(°C)	260
Maximum Time at Peak Temperature (s)	40
Number of Reflow Cycles	3
REACH SVHC	NXP REACH Statement
UL94 (plastics flammability test)	V0;Burning stops within 10 seconds on a vertical specimen;no drips allowed

Manufacturing Information

Micron Size(μm)	.18
-----------------	-----

Ordering Information

Minimum Package Quantity (MPQ)	1250
MPQ Container	BRICK
Exempt from Minimum Delivery Value	Yes
Preferred Order Quantity (POQ)	2500
POQ Container	BOX
Export Control Classification Number (US)	3A991A2
Harmonized Tariff (US) Disclaimer	8542.31.0000
CCATS Document	-
ENC Status	-
Other Trade Compliance Documents	-
Budgetary Price excluding tax(US\$) Change Currency	-
Order	

Operating Characteristics

Sample Exception Availability	N
-------------------------------	---

ABOUT NXP

[Investors](#)
[Partners](#)
[Careers](#)

RESOURCES

[Mobile Apps](#)
[Press, News, Blogs](#)
[Contact Us](#)

FOLLOW US



News 15 Feb 2017



NXP Wins Prestigious Automotive Innovation Award with Radar

[Read More](#)

