

Material - Plating Mating	Tin	acid, dihexyl ester, bra
Material - Plating Termination	Tin	diisohexyl phthalate
Material - Resin	High Temperature Thermoplastic	1,2-
Net Weight	1.628/g	Benzenedicarboxylic acid, dipentyl ester, br
Number of Rows	2	Zirconia
Orientation	Right Angle	Aluminosilicate
PCB Locator	Yes	Refractory Ceramic
PCB Retention	Yes	Fibr
PCB Thickness - Recommended	1.60mm	Nonadecafluorodecanoic acid (PFDA) and its
Packaging Type	Embossed Tape on Reel	sodiu
Pitch - Mating Interface	3.00mm	Tris(4-nonylphenyl, branched and linear)
Plating min - Mating	0.254µm	phosphi
Polarized to PCB	Yes	Perfluorobutane sulfonic acid (PFBS) and its sal
Shrouded	Fully	Fluoranthene
Stackable	No	Pyrene
Surface Mount Compatible (SMC)	N/A	Dodecachloropentacyclo[12.2.1.16,9.02,13.05,10]o
Temperature Range - Operating	-40° to +105°C	Diocetyl tin dilaurate, stannane, dioctyl-, bis(co
Termination Interface: Style	Surface Mount	Perfluorononan-1-oic acid (2,2,3,3,4,4,5,5,6,6,7 Perfluorohexane-1-sulphonic acid and its salts
Electrical		Dipentyl phthalate
Current - Maximum per Contact	8.5A	Cobalt-dichloride
Voltage - Maximum	600V	Alkanes, C10-13, chloro
Solder Process Data		Bis(tributyltin) oxide
Duration at Max. Process Temperature (seconds)	030	Lead chromate
Lead-freeProcess Capability	REFLOW	Lead chromate molybdate sulfate red
Max. Cycles at Max. Process Temperature	003	Tris(2-chloroethyl) phosphate
Process Temperature max. C	260	bis(2-methoxyethyl) ether
Material Info		1,2-Dimethoxyethane
Reference - Drawing Numbers		1,2-bis(2-methoxyethoxy)ethane
Application Specification	AS-43045-001-001	Decabromodiphenylether
Packaging Specification	430450001-PK-000	Diboron-trioxide
Product Specification	430450001-PS-KO-000, 430450001-PS-SP-000, PS-43045-001	Cadmium-oxide
Sales Drawing	SD-43045-004-000	Lead(II,IV)-oxide
Symbol/Footprint Data	SYM-43045-1009-001	Lead
Test Summary	430450004-TS-000, TS-43045-001-001, TS-46235-001-001	Cadmium
		Lead-dinitrate
		Lead-titanium-trioxide
		Pentalead-tetraoxide-sulphate
		Tetralead-trioxide-sulphate
		Dioxobis(stearato)trilead
		Lead titanium zirconium oxide
		Cyanamide, lead(2+) salt (1:1)
		Sulfurous Acid, Lead Salt, Dibasic

Silicic acid (H2Si2O5),
barium salt (1:1),
lead-
[Phthalato(2-)]dioxotrilead
4-aminoazobenzene
N,N-
Dimethylformamide
Phenanthrene
Imidazolidine-2-thione
Halogen-Free
Status
Low-Halogen
For more information, please visit [Contact US](#)

China ROHS	Green Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

Search Parts in this Series
[43045](#) Series

Mates With
Micro-Fit 3.0 Receptacle Housing [43025](#)

Micro-Fit 3.0 TPA Receptacle Housing
[172952](#)
 Micro-Fit 3.0 Cable Assembly
[245132](#) , [214755](#) , [214756](#)

This document was generated on 11/11/2021
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION