

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

Product Specifications

Application Specification

Flexible Flat Cable (FFC) Housings With Contact Cavities On 2.54-Mm (.100-In.) Centerline Spacing

PDF

English

Product Specification

Connector, Flexible Flat Conductor Cable, .100 Inch Centerline

PDF

English

Instruction Sheets

Instruction Sheet (U.S.)

Extraction Tools

PDF

English

Extraction Tools

TIF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Type Housing

Connector Style Receptacle

Connector System Wire-to-Board

Connector & Contact Terminates To Wire & Cable

Wire/Cable Type FFC

Product Type Connector

Type of Connector Slimline

Configuration Features

Number of Positions 9

Number of Rows 1

Electrical Characteristics

Insulation Resistance (MΩ) 5000
Voltage 300 VACrms
Dielectric Withstanding Voltage (VAC) 720

Contact Features

Contact Type Socket

Mechanical Attachment

Mating Connector Lock Without
Mating Alignment Without
Panel Mount Retention Without
Mating Retention Without

Housing Features

Centerline (Pitch) 2.54 mm [.1 in]
Housing Color Black
Housing Material Thermoplastic

Usage Conditions

Operating Temperature Range (°C) -65 – 105
Flame Retardant Yes

Industry Standards

UL Flammability Rating UL 94V-0

Packaging Features

Packaging Method Package
Packaging Quantity 1

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance
PDF