



249-8771
887

249-860

Lithium Coin Cells

These super-slim cells offer all the advantages of the Lithium MnO₂ system where space is at a premium. With a shelf life in excess of 5 years, Varta Lithium Coin cells are available with pins for horizontal (PCB) mounting or vertical (SLF) mounting.

Pin Spacing




Storage	-55 to +75°C
Discharge	-30 to +75°C

Part No.	Capacity (mAh)	Dimensions (mm)	Voltage (V)	Mounting	Notes
CR1620	50	16.0 x 2.0	1.2	-	Plain Cell
CR2016	80	20.0 x 1.6	1.8	-	Plain Cell
CR2025	150	20.0 x 2.5	2.5	-	Plain Cell
CR2032	220	20.0 x 3.2	3.0	-	Plain Cell
CR2430	280	24.5 x 3.0	4.0	-	Plain Cell
CR2450	560	24.7 x 5.0	6.2	-	Plain Cell
CR2032PCB	220	20.0 x 3.2	3.1	18.0	Horizontal PCB Mount
CR2430PCB	280	24.5 x 3.0	4.1	18.0	Horizontal PCB Mount
CR2032SLF	220	20.0 x 3.2	3.1	3.2	Vertical PCB Mount
CR2430SLF	280	24.5 x 3.0	4.1	4.1	Vertical PCB Mount

Special Battery Packs

Nortronic are able to supply battery packs designed and built by Varta to suit applications where a standard battery is not suitable. With the backing of the Varta technical division, our engineers are available to discuss your application and your completion of our master fax sheet will ensure that we give you the best advice. In the majority of cases we are able to provide prototype batteries for further evaluation within a matter of days when required.



VARTA
THE BATTERY EXPERTS

NORTRONIC